

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 1 of 14

Version: 1.1

Revision Date: 3/30/2015

XTRABOND PATCHMAX CONCRETE & MASONRY REPAIR CAULK

1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Product Brand Name: XtraBond PatchMax
Other Names/Synonyms: None
Recommended Use: Sealant - Other
Uses advised against: No information available

Company Contact Information

Premier Building Solutions, Inc.
480 Nova Drive
Massillon, OH. 44646
Telephone: 330-244-2907

Emergency Telephone Number

CHEMTREC: 1-800-424-9300 (24 hours) or 1-703-527-3887

2. HAZARDS IDENTIFICATION

GHS Classification



Classification: This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation: Category 2

Acute toxicity (oral): Category 4

Specific target organ toxicity (repeated exposure): Category 2

Emergency Overview: Signal word - Warning

Hazard Statements: Causes serious eye irritation; Harmful if swallowed; May cause damage to organs through prolonged or repeated exposure

Appearance: Varies

Physical State: Paste Liquid

Odor: Latex

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 2 of 14

Version: 1.1

Revision Date: 3/30/2015

XTRABOND PATCHMAX CONCRETE & MASONRY REPAIR CAULK

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling; Wear eye/face protection; Do not eat, drink or smoke when using this product; Do not breathe dust/fume/gas/mist/vapors/spray

Precautionary Statements - Response

Get medical advice/attention if you feel unwell

Eyes

IF IN EYES: Rinse cautiously with water for several minutes; Remove contact lenses, if present and easy to do; continue rinsing; if eye irritation persists: Get medical advice/attention

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician if you feel unwell; Rinse mouth

Precautionary Statements - Storage

None

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

29.46% of the mixture consists of ingredient(s) of unknown toxicity

Other information

No information available

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance: Mixture

Chemical Nature: Latex

<u>CAS Number</u>	<u>*Wt %</u>	<u>Component Name</u>
471-34-1	30 - 60	Calcium Carbonate
Proprietary	20 - 30	Aqueous emulsion copolymer of styrene and acrylic ester

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 3 of 14

Version: 1.1

Revision Date: 3/30/2015

XTRABOND PATCHMAX CONCRETE & MASONRY REPAIR CAULK

14808-60-7	10 - 30	Quartz
107-21-1	1 - 5	Ethylene Glycol

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

General Advice: Show this safety data sheet to the doctor in attendance.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Do not rub affected area.

Skin Contact

Wash with soap and water.

Inhalation

Remove to fresh air.

Ingestion

Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.

Most important symptoms and effects, both acute and delayed

Burning sensation

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 4 of 14

Version: 1.1

Revision Date: 3/30/2015

XTRABOND PATCHMAX CONCRETE & MASONRY REPAIR CAULK

Specific Hazards Arising from the Chemical

No information available

Uniform Fire Code

Irritant: Liquid

Hazardous Combustion Products

Carbon oxides

Explosion Data

Sensitivity to Mechanical Impact: No

Sensitivity to Static Discharge: No

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions

Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas.

Other Information

Refer to protective measures listed in Sections 7 and 8.

Environmental Precautions

Environmental Precautions

Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for Containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 5 of 14

Version: 1.1

Revision Date: 3/30/2015

XTRABOND PATCHMAX CONCRETE & MASONRY REPAIR CAULK

7. HANDLING AND STORAGE

Precautions for safe handling

Handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children.

Incompatible Products

None known based on information supplied

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Calcium Carbonate (CAS# 471-34-1)	-	TWA: 15 mg/m ³ TWA: 5 mg/m ³ (vacated) TWA: 15 mg/m ³ (vacated) TWA: 5 mg/m ³	TWA: 5 mg/m ³ respirable dust TWA: 10 mg/m ³ total dust
Quartz (CAS# 14808-60-7)	TWA: 0.025 mg/m ³ respirable fraction	TWA: 0.1 mg/m ³ (vacated)	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust
Ethylene Glycol (CAS# 107-21-1)	Ceiling: 100 mg/m ³ aerosol only	(vacated) Ceiling: 50 ppm (vacated) Ceiling: 125 mg/m ³	

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Showers
Eyewash stations
Ventilation systems

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 6 of 14

Version: 1.1

Revision Date: 3/30/2015

XTRABOND PATCHMAX CONCRETE & MASONRY REPAIR CAULK

Individual protection measures, such as personal protective equipment

Eye/Face Protection

If splashes are likely to occur: Wear safety glasses with side shields (or goggles). None required for consumer use.

Skin and Body Protection

Wear protective gloves and protective clothing.

Respiratory Protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes, and clothing. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL & CHEMICAL PROPERTIES

Physical Form: Paste, Liquid
Color: Varies
Odor: Latex
Odor Threshold: No information available
Appearance: Varies

<u>Property</u>	<u>Values</u>	<u>Remarks Method</u>
pH	UNKNOWN	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity	No data available	None known
Water Solubility	No data available	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 7 of 14

Version: 1.1

Revision Date: 3/30/2015

XTRABOND PATCHMAX CONCRETE & MASONRY REPAIR CAULK

Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No data available	
Oxidizing Properties	No data available	

Other Information

Softening Point	No data available
VOC Content (g/L)	16
Particle Size	No data available
Particle Size Distribution	No data available

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

None known based on information supplied.

Incompatible materials

None known based on information supplied.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation:

Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 8 of 14

Version: 1.1

Revision Date: 3/30/2015

XTRABOND PATCHMAX CONCRETE & MASONRY REPAIR CAULK

Eye Contact:

Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to eyes. May cause redness, itching, and pain. May cause temporary eye irritation.

Skin Contact:

Specific test data for the substance or mixture is not available. May cause irritation. Prolonged contact may cause redness and irritation.

Ingestion:

Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be harmful if swallowed (based on components).

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Calcium carbonate 471-34-1	= 6450 mg/kg (Rat)	-	-
Quartz 14808-60-7	= 500 mg/kg (Rat)	-	-
Ethylene glycol 107-21-1	= 4000 mg/kg (Rat)	-	-

Information on toxicological effects

Symptoms:

May cause redness and tearing of the eyes

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization:

No information available.

Mutagenic Effects:

No information available.

Carcinogenicity:

The table below indicates whether each agency has listed any ingredient as a carcinogen

Chemical Name	ACGIH	IARC	NTP	OSHA
Quartz 14808-60-7	A2	Group 1	Known	X

OSHA (Occupational Safety and Health Administration of the USE Department of Labor)

X = Present

NTP (National Toxicology Program)

Known = Known Carcinogen

IARC (International Agency for Research on Cancer)

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 9 of 14

Version: 1.1

Revision Date: 3/30/2015

XTRABOND PATCHMAX CONCRETE & MASONRY REPAIR CAULK

Group 1 = Carcinogenic to humans

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 = Suspected Human Carcinogen

Reproductive Toxicity

No information available.

STOT - single exposure

No information available.

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).

Chronic Toxicity

Avoid repeated exposure. Prolonged exposure may cause chronic effects. Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human carcinogen (Group 1). This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product.

Target Organ Effects

Eyes. Skin. Respiratory system. Gastrointestinal tract (GI). Central Nervous System (CNS). Lungs. Heart. Kidney.

Aspiration Hazard

No information available.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) = 1,688.00 mg/kg

12. ECOLOGICAL CONSIDERATIONS

Ecotoxicity

The environmental impact of this product has not been fully investigated.

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 10 of 14

Version: 1.1

Revision Date: 3/30/2015

XTRABOND PATCHMAX CONCRETE & MASONRY REPAIR CAULK

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Ethylene glycol 107-21-1	96h EC50: 6500 - 13000 mg/L (Pseudokirchneriella subcapitata)	96h LC50: = 41000 mg/L (Oncorhynchus mykiss) 96h LC50: 14 - 18 mL/L (Oncorhynchus mykiss) 96h LC50: = 40761 mg/L (Oncorhynchus mykiss) 96h LC50: = 27540 mg/L (Lepomis macrochirus) 96h LC50: = 16000 mg/L (Poecilia reticulata) 96h LC50: 40000 - 60000 mg/L (Pimephales promelas)	EC50 = 10000 mg/L 16 h EC50 = 620 mg/L 30 min EC50 = 620.0 mg/L 30 min	48h EC50: = 46300 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

Chemical Name	Log Pow
Ethylene glycol 107-21-1	-1.93

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Dispose of contents/containers in accordance with local regulations.

14. TRANSPORT INFORMATION

DOT NOT REGULATED

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 11 of 14

Version: 1.1

Revision Date: 3/30/2015

XTRABOND PATCHMAX CONCRETE & MASONRY REPAIR CAULK

TDG Not regulated

MEX Not regulated

ICAO Not regulated

IATA Not regulated

IMDG/IMO Not regulated

RID Not regulated

ADR Not regulated

ADN Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies

DSL All components are listed either on the DSL or NDSL

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Ethylene glycol - 107-21-1	107-21-1	1 - 5	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard: Yes
Chronic Health Hazard: Yes
Fire Hazard: No

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 12 of 14

Version: 1.1

Revision Date: 3/30/2015

XTRABOND PATCHMAX CONCRETE & MASONRY REPAIR CAULK

Sudden release of pressure hazard: No
Reactive Hazard: No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Ethylene glycol 107-21-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations

California Proposition 65

None reportable

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Calcium carbonate 471-34-1	X	X	X		
Quartz 14808-60-7	X	X	X		
Ethylene glycol 107-21-1	X	X	X	X	X

International Regulations

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 13 of 14

Version: 1.1

Revision Date: 3/30/2015

XTRABOND PATCHMAX CONCRETE & MASONRY REPAIR CAULK

Mexico

Component	Carcinogen Status	Exposure Limits
Calcium carbonate 471-34-1 (30 - 60)		Mexico: TWA 10 mg/m ³ Mexico: STEL 20 mg/m ³
Quartz 14808-60-7 (10 - 30)		Mexico: TWA= 0.1 mg/m ³
Ethylene glycol 107-21-1 (1 - 5)		Mexico: Ceiling 100 mg/m ³

Mexico – Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

D2B - Toxic materials



16. OTHER INFORMATION

NFPA

Health Hazards: 2
Flammability: 0
Instability: 0
Physical/Chemical Haz. -

HMIS

Health Hazards: 2*
Flammability: 0
Physical Hazard: 0
Personal Protection: X

Chronic Hazard Star Legend * = Chronic Health Hazard

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 14 of 14

Version: 1.1

Revision Date: 3/30/2015

XTRABOND PATCHMAX CONCRETE & MASONRY REPAIR CAULK

Note: The responsibility to provide a safe workplace remains with the user. The user should consider the health hazards and safety information contained herein as a guide and should take those precautions required in an individual operation to instruct employees and develop work practice procedures for a safe work environment. The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by the use of this material. It is the responsibility of the user to comply with all applicable laws and regulations. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

<http://www.xtrabond.com>