

XtraBond®9500XHS

HIGH-STRENGTH ADVANCED POLYMER SEALANT



XtraBond®9500XHS is a high strength advanced polymer sealant. The product's unique formula offers excellent adhesion to a wide range of industrial materials, including vinyl, sheet metal, steel, pre-painted metals, wood glass, aluminum and plastic. It provides a highly weatherable, paintable surface that allows for a reduction in the number of fasteners that are required.

XtraBond®9500XHS has been engineered for a wide range of industrial and transportation applications, including recreational vehicles, automotive seams and transportation trailers. The product's fast-curing formula contains no solvents, and very low VOCs, so the product is environmentally friendly.

FEATURES

- Industrial & Transportation Applications
- High Green Strength Formula
- Paintable in 2 Hours
- Extreme Adhesion
- No Solvents
- Low VOCs

APPLICATIONS

- Recreational Vehicles
- Tractor Trailers & Buses
- Industrial

Green Advantage Program

This XtraBond® product is a part of Premier's "Green Advantage" Program – the designation of our commitment to not only superior products & services, but also the environment. Our engineering formulations, manufacturing standards and production practices allow us to be a leader in the supply of eco-friendly and VOC compliant products. Learn more at www.PremierBuildingSolutions.net/green



Weather Defense System

This XtraBond® product is a part of the XtraGuard Weather Defense System™, an integrated product line of building components developed from advanced materials research that increase the durability and comfort of residential and commercial structures by effectively managing moisture. The product's aggressive adhesion and compatibility with all major building materials makes it a critical link in the XtraGuard Weather Defense System, when combined with the company's complete line of Wraps and Flashing Products.



Who is Premier?

This XtraBond® product is manufactured and distributed by Premier Building Solutions, a manufacturer of high performance systems that provide protection in commercial and residential buildings – as well as a variety of other industrial and transportation applications.

The company's history of innovation has led to the development of breakthrough adhesive chemistries and new industrial-strength products that help customers increase the efficiency and durability of their critical assets.



PREMIER BUILDING SOLUTIONS, INC
866-512-GLUE (4583) • Massillon, OH
www.PremierBuildingSolutions.net





XTRABOND®9500XHS

HIGH-STRENGTH ADVANCED POLYMER SEALANT

PROPERTIES:

Skin Time	15 minutes @ 77 degF/ 50% RH
Tack Free Time	40 minutes @ 77 degF / 50% RH
Cure Rate	1/4" Bead per 24 Hrs
VOC	9 g/L (0.14%)
Elongation @ Break	300%
Shore A	45
Movement Capability	25%
UV Rating	No discoloration or change in appearance after 2500 hrs of UV
Lap Shear	405 psi
Tensile Strength	450 psi
Staining	None
Low Temp. Flexibility	Retained to -90 deg. F.
High Temp. Flexibility	Up to 425 deg. F for short periods
Sag	None

SPECIFICATIONS: XtraBond®9500XHS meets or exceeds the requirements of ASTM C 920, Type S, Grade NS, Class 25, Use NT, M, G and A • Federal Specification TT-S-00230C, Type II, Class A • CAN/CGSB-1913-M87

COLORS: Standard Colors include: White, Aluminum Stone, and Black. This product is also offered in a wide range of colors using our Custom Color Matching & Mixing System. For current color offerings, please visit our website at www.premierbuildingsolutions.net

SURFACE PREPARATIONS: The substrate must be clean, frost free and free of any oils, greases or incompatible sealers that may interfere with adhesion. Do not apply if surface is contaminated. It is recommended to test all substrates prior to applications.

DIRECTIONS: For best results, prepare clean surface. Cut nozzle to desired bead size. Apply with caulking gun, forcing sealant onto the substrate, then tool if needed. Clean excess material with mineral spirits or similar solvent.

STORAGE: Material is to be stored under controlled dry environment (below 75° F). Use within 6 months from date of manufacture.

LIMITED LIFETIME WARRANTY: This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Building Solutions, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.

Premier Building Solutions specifically disclaims and makes no warranties, express or implied, about this product, its merchantability, or its fitness for a particular purpose. All recommendations, directions, and suggestions for its use are consistent with our testing and research for a variety of applications, but no promises, guarantees, or warranties are being made with regard to its use, whether or not consistent with the directions, or its effectiveness for any given application. Users of this product should do so in compliance with all applicable laws and regulations. User of this product should conduct its own field test, to assure results.

PACKAGING



CARTRIDGES



SAUSAGES



PAILS



55GAL DRUMS