

Universal

HYBRID SEALANT

SILICONE
ALTERNATIVE

PRODUCT DESCRIPTION:

Universal Hybrid Sealant provides aggressive adhesion to a wide variety of substrates. The low odor, 100% solids formula is a permanently flexible, paintable sealant.

DIRECTIONS FOR USE:

For best results, prepare clean surface. Cut nozzle to desired bead size. Apply with caulking gun, forcing sealant onto the substrate, then tool if needed. Clean excess material with mineral spirits or similar solvent.

SURFACE PREPARATION:

The substrate must be clean, frost free and free of any oils, greases or incompatible sealers that may interfere with adhesion. Do not apply if surface is contaminated. It is recommended to test all substrates prior to applications.

APPLICATION:

Cut nozzle to desired bead size. Apply with caulking gun, forcing sealant onto the substrate. Tool if necessary.

CLEAN-UP:

Clean excess material with mineral spirits or similar solvent

CURING:

Under normal conditions (70°F, 50% RH) material cures at roughly 1/4" per 24 hours. The higher the humidity and temperature, the faster the cure.

FEATURES:

- Approved for cultured marble & granite
- Kitchen & bath sealant
- Trailer & rv sealant
- Does not promote mold or mildew growth
- Paintable
- NSF Certified

APPLICATIONS:

- Trailer & RV
- Cultured Marble & Granite
- Kitchen & Bath
- Other Common Construction Substrates

From the makers of
XTRABOND



Nonfood Compounds
Category Code: P1
Registration No. 157834



PHYSICAL PROPERTIES TABLE

Specifications:	Conforms to the requirements for ASTM C-920 Type S, Grade NT
Skin Time	<20 minutes @ 77°F/50%
Tack Free Time	40 minutes
Cure Rate	1/4" Bead per 24 Hrs
VOC	<20 g/L
Elongation @ Break	200-300%
Shore A	<40-50
Lap Shear	90 psi
Maximum Tensile Strength	150-165 psi
UV Rating	No discoloration or change in appearance after 2500 hrs of UV

LIMITATIONS:

Do not apply over damp or contaminated surfaces. Always utilize the Safety Data Sheet (SDS) for information on Personal Protective Equipment (PPE) and health hazards.

STORAGE/SHELF LIFE:

Material is to be stored under controlled dry environment (below 75° F). Use within 12 months from date of manufacture.

APPROXIMATE* LINEAR FEET/COVERAGE PER 10.1 FL. OZ. CARTRIDGE (298 ML)

DEPTH	WIDTH							
	1/8"	1/4"	3/8"	1/2"	5/8"	3/4"	7/8"	1"
1/8"	99	49	33	24	20	16	14	12
1/4"		24	20	12	10	8	7	6
3/8"			11	8	6	5	5	4
1/2"				6	5	4	3	3

*All values are approximations based upon industry information and can vary dramatically due to joint dimensions/configurations, porosity, texture of substrates, irregularities, installation techniques, waste, etc. that are beyond Premier Building Solutions' control. Premier Building Solutions is not liable for variances to linear feet/coverage; do a test area to determine material required to use.

PACKAGING:

10.1 oz. Cartridge: 24/case, 80 cases/pallet
 20.0 oz. Sausage: 20/case, 60 cases/pallet
 5 Gallon Pail: 36 pails/pallet
 55 Gallon: Drum



CARTRIDGES



SAUSAGES



PAILS



55GAL DRUMS

LIMITED LIFETIME WARRANTY:

This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Building Solutions, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.

Premier Building Solutions specifically disclaims and makes no warranties, express or implied, about this product, its merchantability, or its fitness for a particular purpose. All recommendations, directions, and suggestions for its use are consistent with our testing and research for a variety of applications, but no promises, guarantees, or warranties are being made with regard to its use, whether or not consistent with the directions, or its effectiveness for any given application. Users of this product should do so in compliance with all applicable laws and regulations. User of this product should conduct its own field test, to assure results.

Oct 31, 2018 Version 7