

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 1 of 12
Version: 1.1
Revision Date: 6/7/2017

XTRABOND 350 NEUTRAL CURE SILICONE SEALANT

1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Product Brand Name: XB 350 Neutral Cure Silicone Sealant (Colors)

Other Names/Synonyms: None

Recommended Use: Sealant - Other

Uses advised against: No information available

Company Contact Information

Premier Building Solutions, Inc.
480 Nova Drive
Massillon, OH. 44646
Telephone: 330-244-2907

Emergency Telephone Number

CHEMTREC: 1-800-424-9300 (24 hours) or 1-703-527-3887

2. HAZARDS IDENTIFICATION

GHS Classification



Skin sensitization: Category 1

Serious eye damage/eye irritation: Category 2A

Emergency Overview: Signal word - Warning

Hazard Statements: May cause an allergic skin reaction; causes serious eye irritation

Appearance: Varies

Physical State: Paste Liquid

Odor: Neutral

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves/eye protection/face protection

Wash face, hands, and any exposed skin thoroughly after handling

Precautionary Statements - Response

Specific treatment (see supplemental first aid instructions on this label)

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 2 of 12
Version: 1.1
Revision Date: 6/7/2017

XTRABOND 350 NEUTRAL CURE SILICONE SEALANT

Skin

IF ON SKIN: Wash with plenty of soap and water
If skin irritation or rash occurs: Get medical advice/attention
Wash contaminated clothing before reuse

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Unknown Acute Toxicity

98.37% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Causes mild skin irritation

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance: Not applicable

Mixture:

Chemical name	CAS-No	Percent	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Limestone	1317-65-3	35 - 60	-	-
2-Butanone, O,O',O''-(methylsilylidyne)trioxime	22984-54-9	1 - 5	-	-

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

General Advice: Show this safety data sheet to the doctor in attendance.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 3 of 12

Version: 1.1

Revision Date: 6/7/2017

XTRABOND 350 NEUTRAL CURE SILICONE SEALANT

Skin Contact

Wash with soap and water. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.

Inhalation

Remove to fresh air.

Ingestion

Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.

Self-protection of the first aider

Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see Section 8).

Most Important Symptoms and Effects, both Acute and Delayed

Itching. Rashes. Hives. Burning sensation.

Indication of any Immediate medical attention and special treatment needed

Note to Physicians: May cause sensitization in susceptible persons; treat symptomatically.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

Product is or contains a sensitizer. May cause sensitization by skin contact.

Hazardous Combustion Products

Carbon oxides

Explosion Data

Sensitivity to Mechanical Impact: None

Sensitivity to Static Discharge: None

Protective equipment and precautions for firefighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 4 of 12
Version: 1.1
Revision Date: 6/7/2017

XTRABOND 350 NEUTRAL CURE SILICONE SEALANT

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions

Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Other Information

Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for Containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 5 of 12
Version: 1.1
Revision Date: 6/7/2017

XTRABOND 350 NEUTRAL CURE SILICONE SEALANT

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH	
Limestone 1317-65-3	-	TWA: 15 mg/m ³ TWA: 5 mg/ m ³ (vacated) TWA: 15 mg/ m ³ (vacated) TWA: 5 mg/ m ³	TWA: 5 mg/ m ³ respirable dust TWA: 10 mg/ m ³ total dust	
Chemical Name	Alberta	British Columbia	Ontario TWAEV	Quebec
Limestone 1317-65-3	TWA: 10 mg/ m ³	TWA: 10 mg/ m ³ TWA: 3 mg/ m ³ STEL: 20 mg/ m ³	-	TWA: 10 mg/ m ³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value

OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992)

Appropriate engineering controls

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Wear safety glasses with side shields (or goggles). If splashes are likely to occur, wear safety glasses with side shields.

Skin and Body Protection

Wear suitable protective clothing.

Hand protection

Wear suitable gloves.

Respiratory Protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations

Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 6 of 12
Version: 1.1
Revision Date: 6/7/2017

XTRABOND 350 NEUTRAL CURE SILICONE SEALANT

9. PHYSICAL & CHEMICAL PROPERTIES

Physical State: Paste; Liquid
Color: Varies
Odor: Neutral
Odor Threshold: No information available
Appearance: Varies

<u>Property</u>	<u>Values</u>	<u>Remarks Method</u>
pH	UNKNOWN	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative Density	1.44	None known
Water Solubility	No data available	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No data available	None known
Oxidizing Properties	No data available	None known

Other Information

Softening Point	No data available
VOC Content (g/L)	No data available
Particle Size	No data available
Particle Size Distribution	No data available

10. STABILITY AND REACTIVITY

Reactivity

No data available.

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 7 of 12
Version: 1.1
Revision Date: 6/7/2017

XTRABOND 350 NEUTRAL CURE SILICONE SEALANT

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

None known based on information supplied.

Incompatible materials

None known based on information supplied.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation:

Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.

Eye Contact:

Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.

Skin Contact:

May cause sensitization by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). May cause irritation. Prolonged contact may cause redness and irritation.

Ingestion:

Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Information on toxicological effects

Symptoms:

Itching. Rashes. Hives. May cause redness and tearing of the eyes.

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 8 of 12
Version: 1.1
Revision Date: 6/7/2017

XTRABOND 350 NEUTRAL CURE SILICONE SEALANT

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation:

May cause skin irritation

Serious eye damage/eye irritation:

Classification based on data available for ingredients. Irritating to eyes.

Respiratory or skin sensitization: May cause sensitization by skin contact.

Reproductive Toxicity

No information available.

STOT - single exposure

No information available.

STOT - repeated exposure

No information available.

Germ cell mutagenicity

No information available.

Carcinogenicity

No information available.

Aspiration Hazard

No information available.

Numerical measures of toxicity

Unknown acute toxicity

98.37 % of the mixture consists of ingredient(s) of unknown toxicity

12. ECOLOGICAL CONSIDERATIONS

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Persistence and Degradability

No information available.

Bioaccumulation

No information available

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 9 of 12
Version: 1.1
Revision Date: 6/7/2017

XTRABOND 350 NEUTRAL CURE SILICONE SEALANT

Mobility

No information available

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods

Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislations.

Contaminated Packaging

Do not reuse empty containers

*This product contains one or more substances that are listed with the State of California as a hazardous waste

14. TRANSPORT INFORMATION

DOT NOT REGULATED
Proper Shipping Name: Non regulated
Hazard Class: N/A

TDG Not regulated

MEX Not regulated

ICAO Not regulated

IATA Not regulated
Proper Shipping Name: Non regulated
Hazard Class: N/A

IMDG/IMO Not regulated
Hazard Class: N/A

RID Not regulated

ADR Not regulated

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 10 of 12

Version: 1.1

Revision Date: 6/7/2017

XTRABOND 350 NEUTRAL CURE SILICONE SEALANT

ADN Not regulated

15. REGULATORY INFORMATION

International Inventories

Ozone-depleting substances (ODS)

Not applicable

Persistent Organic Pollutants

Not applicable

Export Notification requirements

Not applicable

TSCA

Contact supplier for inventory compliance status

DSL/NDSL

Contact supplier for inventory compliance status

EINECS/ELINCS

Contact supplier for inventory compliance status

ENCS

Contact supplier for inventory compliance status

KECL

Contact supplier for inventory compliance status

PICCS

Contact supplier for inventory compliance status

AICS

Contact supplier for inventory compliance status

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute Health Hazard:	Yes
Chronic Health Hazard:	No
Fire Hazard:	No
Sudden release of pressure hazard:	No
Reactive Hazard:	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 11 of 12

Version: 1.1

Revision Date: 6/7/2017

XTRABOND 350 NEUTRAL CURE SILICONE SEALANT

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Limestone 1317-65-3	X	X	X		

16. OTHER INFORMATION

NFPA

Health Hazards: 2
Flammability: 0
Instability: 0
Physical/Chemical Haz. -

HMIS

Health Hazards: 2
Flammability: 0
Physical Hazard: 0
Personal Protection: X

Note: The responsibility to provide a safe workplace remains with the user. The user should consider the health hazards and safety information contained herein as a guide and should take those precautions required in an individual operation to instruct employees and develop work practice procedures for a safe work environment. The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 12 of 12

Version: 1.1

Revision Date: 6/7/2017

XTRABOND 350 NEUTRAL CURE SILICONE SEALANT

guarantee of results, and assume no liability for damages incurred by the use of this material. It is the responsibility of the user to comply with all applicable laws and regulations. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

<http://www.xtrabond.com>