

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 1 of 14
Version: 1.1
Revision Date: 3/10/2015

XTRABOND 250 100% RTV SILICONE SEALANT

1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Product Brand Name: XtraBond 250
Other Names/Synonyms: None
Recommended Use: Sealant - Other
Uses advised against: No information available

Company Contact Information

Premier Building Solutions, Inc.
480 Nova Drive
Massillon, OH. 44646
Telephone: 330-244-2907

Emergency Telephone Number

CHEMTREC: 1-800-424-9300 (24 hours) or 1-703-527-3887

2. HAZARDS IDENTIFICATION

GHS Classification



Classification: This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization: Category 2

Serious eye damage/eye irritation: Category 2A

Aspiration toxicity: Category 1

Emergency Overview: Signal word - Warning

Hazard Statements: Causes skin irritation; Causes serious eye irritation; May be fatal if swallowed and enters airway

Appearance: Varies

Physical State: Paste Liquid

Odor: Acetic

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling; Wear protective gloves/protective clothing/ face protection; Wear eye/face protection

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 2 of 14
Version: 1.1
Revision Date: 3/10/2015

XTRABOND 250 100% RTV SILICONE SEALANT

Precautionary Statements - Response

Specific treatment (see supplemental first aid instructions on this label)

Skin

IF ON SKIN: Wash with plenty of soap and water; If skin irritation or rash occurs: Get medical advice/attention; Take off contaminated clothing and wash before reuse

Eyes

IF IN EYES: Rinse cautiously with water for several minutes; Remove contact lenses, if present and easy to do; Continue rinsing; If eye irritation persists: Get medical advice/attention

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician; Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

64.4% of the mixture consists of ingredient(s) of unknown toxicity

Other information

No information available

Interactions with Other Chemicals

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance: Mixture

Chemical Nature: Silicone

<u>CAS Number</u>	<u>*Wt %</u>	<u>Component Name</u>
17689-77-9/4253-34-3	1 - 10	Methyltriacetoxysilane/Ethyltriacetoxysilane
70131-67-8	55 - 75	Hydroxy functional polydimethyl siloxane polymer
112945-52-5	1 - 10	Silicone Dioxide

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 3 of 14
Version: 1.1
Revision Date: 3/10/2015

XTRABOND 250 100% RTV SILICONE SEALANT

1333-86-4	0 - 1	Carbon Black (if needed)
13463-67-7	0 - 1	Titanium Dioxide (if needed)

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

General Advice: Show this safety data sheet to the doctor in attendance.
Immediate medical attention is required.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Do not rub affected area.

Skin Contact

Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.

Inhalation

Remove to fresh air. Get medical attention immediately if symptoms occur. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur.

Ingestion

Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Aspiration hazard if swallowed - can enter lungs and cause damage. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Call a physician or poison control center immediately.

Self-protection of the first aider

Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8). Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

Most important symptoms and effects, both acute and delayed

Burning sensation; Difficulty in breathing; Coughing and/or wheezing; Dizziness

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 4 of 14
Version: 1.1
Revision Date: 3/10/2015

XTRABOND 250 100% RTV SILICONE SEALANT

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

No information available.

Uniform Fire Code

Irritant: Liquid

Hazardous Combustion Products

Carbon oxides

Explosion Data

Sensitivity to Mechanical Impact: No

Sensitivity to Static Discharge: No

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions

Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required.

Other Information

Refer to protective measures listed in Sections 7 and 8.

Environmental Precautions

Environmental Precautions

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so.

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC..

Page 5 of 14
Version: 1.1
Revision Date: 3/10/2015

XTRABOND 250 100% RTV SILICONE SEALANT

Methods and material for containment and cleaning up

Methods for Containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Store locked up. Keep out of the reach of children; Store away from other materials.

Incompatible Products

Strong acids; Strong oxidizing agents; Strong bases

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Supplier Trade Secret	TWA: 5 mg/m ³ STEL: 10 mg/m ³ (as oil mist)	TWA: 5 mg/m ³ (as oil mist)	
Supplier Trade Secret	10 mg/m ³	TWA: 20 mppcf; ((80)/(%) SiO ₂) mg/m ³)	IDLH: 3000 mg/m ³ TWA: 6 mg/m ³
Supplier Trade Secret	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 6 of 14
Version: 1.1
Revision Date: 3/10/2015

XTRABOND 250 100% RTV SILICONE SEALANT

Supplier Trade Secret	TWA: 3 mg/m3 inhalable fraction	TWA: 3.5 mg/m3 (vacated) TWA: 3.5 mg/m3	IDLH: 1750 mg/m3 TWA: 3.5 mg/m3 TWA: 0.1 mg/m3 Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
-----------------------	------------------------------------	--	---

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection

If splashes are likely to occur: Wear safety glasses with side shields (or goggles). None required for consumer use.

Skin and Body Protection

Wear protective gloves and protective clothing. Long sleeved clothing; impervious gloves.

Respiratory Protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Take off contaminated clothing and wash before reuse. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL & CHEMICAL PROPERTIES

Physical Form: Paste, Liquid
Color: Varies
Odor: Acetic
Odor Threshold: No information available
Appearance: Varies

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 7 of 14
Version: 1.1
Revision Date: 3/10/2015

XTRABOND 250 100% RTV SILICONE SEALANT

<u>Property</u>	<u>Values</u>	<u>Remarks Method</u>
pH	UNKNOWN	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity	No data available	None known
Water Solubility	No data available	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No data available	
Oxidizing Properties	No data available	

Other Information

Softening Point	No data available
VOC Content (g/L)	30
Particle Size	No data available
Particle Size Distribution	No data available

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

None known based on information supplied.

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 8 of 14
Version: 1.1
Revision Date: 3/10/2015

XTRABOND 250 100% RTV SILICONE SEALANT

Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation:

Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal.

Eye Contact:

Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to eyes. May cause redness, itching, and pain. May cause temporary eye irritation. May cause irritation.

Skin Contact:

Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to skin. Prolonged contact may cause redness and irritation. Repeated exposure may cause skin dryness or cracking.

Ingestion:

Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Supplier Trade Secret	> 5000 mg/kg (rat)	> 2000 mg/kg (rabbit)	> 5.2 mg/L (rat) 4 h
Supplier Trade Secret	> 10000 mg/kg (rat)	-	-
Supplier Trade Secret	> 15400 mg/kg (rat)	> 3 g/kg (rat)	-

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC..

Page 9 of 14
Version: 1.1
Revision Date: 3/10/2015

XTRABOND 250 100% RTV SILICONE SEALANT

Information on toxicological effects

Symptoms:

Erythema (skin redness). May cause redness and tearing of the eyes. Difficulty in breathing. Coughing and/ or wheezing. Asthma-like and/ or skin allergy-like symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization:

No information available

Mutagenic Effects:

No information available.

Carcinogenicity:

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Supplier Trade Secret	-	Group 3	-	-
Supplier Trade Secret	-	Group 2B	-	X
Supplier Trade Secret	A3	Group 2B	-	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive Toxicity

No information available.

STOT - single exposure

No information available.

STOT - repeated exposure

No information available.

Chronic Toxicity

Aspiration may cause pulmonary edema and pneumonitis. Titanium dioxide has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation. This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC..

Page 10 of 14
Version: 1.1
Revision Date: 3/10/2015

XTRABOND 250 100% RTV SILICONE SEALANT

unlikely to occur from exposure to this product. Carbon black has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation. This product contains carbon black in a non-respirable form. Inhalation of carbon black is unlikely to occur from exposure to this product.

Target Organ Effects

Skin. Respiratory system. Eyes. Gastrointestinal tract (GI). Lungs.

Aspiration Hazard

No information available.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) = 11,867.00 mg/kg

12. ECOLOGICAL CONSIDERATIONS

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Supplier Trade Secret		96h LC50: = 2.2 mg/L (Lepomis macrochirus) 96h LC50: = 2.4 mg/L (Oncorhynchus mykiss) 96h LC50: = 45 mg/L (Pimephales promelas)		96h LC50: = 4720 mg/L
Supplier Trade Secret				24h EC50: > 5600 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

No information available

Other adverse effects

No information available.

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 11 of 14
Version: 1.1
Revision Date: 3/10/2015

XTRABOND 250 100% RTV SILICONE SEALANT

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Dispose of contents/containers in accordance with local regulations.

14. TRANSPORT INFORMATION

DOT NOT REGULATED

TDG Not regulated

MEX Not regulated

ICAO Not regulated

IATA Not regulated

IMDG/IMO Not regulated

RID Not regulated

ADR Not regulated

ADN Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies

DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 12 of 14
Version: 1.1
Revision Date: 3/10/2015

XTRABOND 250 100% RTV SILICONE SEALANT

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute Health Hazard: Yes
Chronic Health Hazard: Yes
Fire Hazard: No
Sudden release of pressure hazard: No
Reactive Hazard: No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

None Reportable

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Supplier Trade Secret	X	X	X		
Supplier Trade Secret	X	X	X		X

SAFETY DATA SHEET



PREMIER BUILDING SOLUTIONS, INC.

Page 13 of 14
Version: 1.1
Revision Date: 3/10/2015

XTRABOND 250 100% RTV SILICONE SEALANT

International Regulations

Mexico

Component	Carcinogen Status	Exposure Limits
Supplier Trade Secret (1-5)		TWA= 10 mg/m3 STEL= 20 mg/m3
Supplier Trade Secret (0.1-1)		TWA= 3.5 mg/m3 STEL= 7 mg/m3

Canada

WHMIS Hazard Class
D2B - Toxic materials



16. OTHER INFORMATION

NFPA

Health Hazards: 2
Flammability: 0
Instability: 0
Physical/Chemical Haz. -

HMIS

Health Hazards: 2
Flammability: 0
Physical Hazard: 0
Personal Protection: X



PREMIER BUILDING SOLUTIONS, INC..

Page 14 of 14

Version: 1.1

Revision Date: 3/10/2015

XTRABOND 250 100% RTV SILICONE SEALANT

Note: The responsibility to provide a safe workplace remains with the user. The user should consider the health hazards and safety information contained herein as a guide and should take those precautions required in an individual operation to instruct employees and develop work practice procedures for a safe work environment. The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by the use of this material. It is the responsibility of the user to comply with all applicable laws and regulations. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

<http://www.xtrabond.com>