



Phase three of shared use facility between Needingworth & Bluntnisham - Rockmeadow to Bluntnisham

Notes
 -Footway construction to consist of 25mm AC6 surface course, 60mm AC14 binder course, 150mm compacted plantings as sub base (HSC/SD/601).
 -Signs to be mounted outside usable footway where possible, mounting height 2.1m.
 -Signs above footway to have min mounting height of 2.3m.
 -Footway to be bounded by timber edgings to rear (both sides where offset), HB2 concrete kerbs to carriageway.

Standard details
 HSC/SD/601 - Footway construction;
 HSC/SD/501 & 502 - Kerbs/channels/edgings;
 HSC/SD/308 - Kerb offsets;

Signs/markings
 -Diag 1057 - 750mm;
 -Ped symbol - 980mm;
 -Diag 1058: 1 - 1m letters;
 -Diag 1059 - 1m arrow;
 -Diag 956 - 300mm Ø;
 -Diag 956 - 40mm x+height;
 -Diag 950 - 900mm;
 -Diag 950:1 - 100 x+height;

Date	Ref.	Revisions



Project
 St Ives
 Cycle Route 12

Title
 Phase 3
 A1123
 Sheet 2 of 2

Scale	Drawn	Checked	Date
1:500	RH	RH	05/01/16

Based upon Ordnance Survey material with the permission of the controller of Her Majesty's Stationery Office © Crown Copyright. Unauthorised reproduction infringes copyright and may lead to prosecution. Cambridgeshire County Council
 100023205 (2006)

Drawing Number
 RH/PROJA/14696/07B