



## ALLBÄCK LINSEED OIL PAINT – QUALITY CONTROL FOR HANDLING, USE AND MAINTENANCE

Allbäck Linoljeprodukter AB	Product name:	Allbäck Linseed Oil Paint
Balkåkravägen 18	Binder:	Cleaned, boiled and matured linseed oil
271 91 Ystad, Sweden	Thinner:	Cleaned boiled linseed oil max 5%

### Areas of use:

The Linseed Oil Paint contains only cleaned boiled linseed oil, titanium dioxide and chalk. Where required, add max 20% Allbäck pure zinc paint to all colours. The paint is solvent-free and must never be thinned with solvent.

Surface	The paint may be used on <b>all</b> clean, dry surfaces, exterior and interior. Max. moisture content 15%. Temperature approx. 5–35°C. May be applied in direct sunlight.
Application	Stir the paint thoroughly. Brush (stiff natural bristles) or spray (high pressure, small nozzle).
Cleaning	Ammonia, Chlorine or Allbäck Linseed Soap. Wash hands and brushes with Linseed Soap and water.
Storage	Store <b>brushes</b> suspended in raw linseed oil (never in water).
Keeping	May be kept indefinitely even below freezing.
Coverage	15–20 m <sup>2</sup> per litre. Each coat should <u>cover the surface completely</u> and be painted in <u>even</u> layers. Apply the same paint in <b>at least three</b> coats on exterior surfaces. Apply four coats to particularly exposed surfaces.
Dry matter	100%
Transport	No restrictions – <b>not</b> hazardous goods

*Risk of self-ignition – always soak rags in water and discard!*

### Waste management

No specific restrictions. Paint remnants can be used down to the last drop. Combine any remaining paint and use as primer or mix with about 30% water to make an emulsion for concrete floors and brick walls. Tins can be discarded as normal metal waste. In Sweden, we have an agreement with REPA on recycling packaging.

### Technical specifications, safety data sheet and emission tests

These are available on our website [www.allbackpaint.com](http://www.allbackpaint.com)

VOC – Allbäck Linseed Oil Paint contains <1.1% VOC

### Cleaning & Maintenance

Linseed Oil Paint is elastic and thus absorbs more dirt in the initial phase. After a few years, the pigment grains start to fall out and the paint becomes “self-cleaning”.

Assuming that the surface has been given three full coats of paint, dirt and mould can be cleaned off using Allbäck Linseed Soap. Avoid too high a pH. Mix the Linseed Soap with water until it foams. Clean the surface using a sponge or a brush. Rinse thoroughly and allow to dry. When the surface turns matt and starts to become chalky, treat with Linseed Oil or Linseed Oil Wax or a coat of Linseed Oil Paint. The need for maintenance varies considerably depending on the original treatment, exposure to the elements and other stresses. Interior surfaces have much longer maintenance intervals and retain their shine for many years. Touch-up work will have a different shine initially.

### Comments:

The results of applying Allbäck Linseed Oil Paint depend on the structure, surface, preparation, temperature, humidity, light and method of application. **Detailed instructions** can be found in the **Little Handbook** on our website [www.allbackpaint.com](http://www.allbackpaint.com).

**Always paint a test area first.** In the event of a complaint, please include your documentation and quality control details.

Treated surface.....  
With paint type..... Date.....

I/We have read the instructions, carried out the preparatory work and painted.....