

# THE FIREWALL FR® COMMITMENT

Viking® Firewall FR® is committed to providing industry leading Flame Resistant garments that offer the highest level of safety for workers exposed to electrical arc and hydrocarbon flash fire hazards.



Viking® Firewall FR® has partnered with Westex® by Milliken® to supply best-in-class inherent and treated flame-resistant fabrics for Viking Firewall FR® FR garment. Milliken & Company, with the recent acquisition of Westex®, is the largest flame resistant fabric manufacturer in the world and a market leader in innovation and technology.

## Fabric Choices for All Industry Applications

Viking® Firewall FR® garments are offered in inherent or treated flame-resistant fabrics by Westex® by Milliken®. Westex® by Milliken® treated FR fabric® is made of 88% cotton, 12% nylon blend with a proprietary permanent FR treatment process guaranteed for the life of the garment. Westex® CXP® flame-resistant fabric, made of Nomex® IIIA fibres, offers greater comfort and durability than other Nomex® IIIA fabrics. Nomex® CXP® combines the Softouch Technology™ process with Leap® technology to provide a soft Nomex® fabric that protects against both arc flash and flash fire hazards.

## Westex® by Milliken® Flame Resistant Fabrics

Westex® by Milliken® 88% cotton / 12% Nylon are high performance flame-resistant (FR) fabrics specifically designed for industrial workwear. The proprietary fabrics use a specialized ammonia-free FR treatment process and are constructed of an optimized blend of Pima cotton and high-tenacity Nylon designed to help mitigate potential injuries due to electric arc and flash fire exposure, while providing enhanced durability and comfort. The combination of these capabilities makes it an ideal fabric for industrial workwear occupations in manufacturing, utilities, electrical maintenance, petrochemical, welding, and steel.



Westex® by Milliken®'s excellent protection against Flash Fire and Arc Flash can significantly reduce the risk of burns. With high air permeability, fabrics breathe, keeping the wearer more comfortable.

Westex® by Milliken® fabric is UL Certified to NFPA 2112, CAN/CGSB-155.20, NFPA 1975 (7 oz only), NFPA 1977 and Arc Rated according to ASTM F1506 for NFPA 70E as HRC/CAT 2.

## Westex® CXP® Nomex® Flame Resistant Fabric

Westex® CXP® is a patented, flame-resistant fabric made of DuPont™ Nomex® IIIA. The fabric is more comfortable and lasts longer than comparable Nomex® fabrics, and is the best choice for protective industrial uniforms and for fire service.



Milliken®'s Softouch Technology® ensures that Westex® CXP® is soft to the touch and has improved airflow through the fabric and the proprietary Visa® technology provides superior wicking for moisture management and helps oily stains wash out. Plus, Westex® CXP® is 40% lighter than FR Cotton/Nylon 9 oz. fabrics, an important factor in overall comfort. All of this keeps you cool and dry while working in hot environments.

Westex® CXP® fabric is UL Certified to NFPA 2112, CAN/CGSB-155.20 (155.22), NFPA 1975, NFPA 1977 and Arc Rated according to ASTM F1506 for NFPA 70E as HRC/CAT 1.

## Milliken® DuPont™ Nomex® CXP® HRC 2 Inherent Flame Resistant Fabric

Nomex® CXP® fabric by Milliken® was specifically developed to provide

improved comfort with dual-hazard fire and electric arc protection. This uniquely made fabric also offers the proven durability, life cycle value and inherent flame resistance that you have come to expect from Nomex®.



Nomex® CXP® is a patented, inherently flame-resistant fabric innovation that helps protect against both fire and electric arc flash hazards. This dual-hazard solution combines proprietary technology engineered by Milliken® to enhance arc protection for DuPont™ Nomex®—which is recognized as a leading flame-resistant (FR) fabric for fire protection in oil and gas, military, emergency response and automobile racing applications.

Nomex® CXP® is UL Certified to NFPA 2112, CAN/CGSB-155.20 (155.22), NFPA 1975, NFPA 1977 and Arc Rated according to ASTM F1506 for NFPA 70E as HRC/CAT2.

**Viking® Firewall FR® products offer superior safety performance, improved comfort and durability, and best value in FR safety workwear**



**Flame-resistant hook-and-loop closures**

**Fully stitched bi-swing back to provide more comfort and mobility**

**All seams are sewn with 100% flame-resistant Nomex<sup>x</sup> thread**

**Use only high YKK® flame-resistant zippers**

**All metal is thermally protected from the skin**

**All stress points are bar tacked to offer ultimate durability**

**Industrial wash 3M™ Scotchlite™ Retroreflective trim with flame-resistant backing**

### Viking® Firewall FR® Button Front Shirt



- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- 7 oz. Westex® by Milliken® flame-resistant fabric – 88% cotton/ 12% nylon
- TPP Value: Contact 8.5, Spaced 9.0
- ARC rating ATPV: 9.2 cal/cm² CAT 2
- Button front closure with full-length placket with a button-down collar
- Full sleeves with adjustable button cuffs
- 2 chest pockets with button closure and box pleat on back
- Dual hazard protection from electrical arc and hydrocarbon flash fire

31B77

- 1100 Dark Navy
- 1800 Light Blue

Size SR - 4XLT



### Viking® Firewall FR® Cargo Pants



- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- 9 oz. Westex® by Milliken® flame-resistant fabric – 88% cotton / 12% nylon
- TPP Value: Contact 10.3, Spaced 11.4
- ARC rating ATPV: 12.4 cal/cm² CAT 2
- All brass closures thermally protected from the skin
- Dual hazard protection from electrical arc and hydrocarbon flash fire
- Cargo style work pants
- Reinforced front slant pockets and back seat pockets
- Generous sized side pockets with flaps, and hook-and-loop closure
- Belt loops, metal button waist closure and Nomex® backed YKK® zipper fly

20179

- 1100 Dark Navy

Size 30 - 48



## Viking® Firewall FR® Striped Coveralls

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- "Oil Patch" style reflective striping configuration
- RT80 featuring 3M Scotchlite™ Reflective Material – 9740 industrial wash flame resistant trim (2" yellow/silver/yellow) with X on back and stripes around each forearm and each leg below the knee
- Two-way breakaway Nomex® backed YKK® front zipper
- Adjustable cuffs, tunnel collar with hook-and-loop closure
- 2 front upper pockets (including 1 mesh gas monitor pocket), and 2 lower front pouch pockets with side access vents
- 1 tool pocket on rear right leg, and 1 left sleeve pencil pocket
- Elasticized waist on the back and fully stitched bi-swing back for better fit and mobility
- All seams double-stitched and stress points bar tacked for ultimate durability
- Dual hazard protection from electrical arc and hydrocarbon flash fire



Size **SR - 5XLT** **3M Scotchlite™** **WESTEX®** *by Milliken*

### 40577 Viking® Firewall FR® Striped Coveralls 7 oz.

- 7 oz. Westex by Milliken® flame-resistant fabric - 88% cotton / 12% nylon
- TPP Value: Contact 8.5, Spaced 9.0
- ARC rating ATPV: 9.2 cal/cm² CAT 2

### 40579 Viking® Firewall FR® Striped Coveralls 9 oz.

- 9 oz. Westex by Milliken® flame-resistant fabric - 88% cotton / 12% nylon
- TPP Value: Contact 10.3, Spaced 11.4
- ARC rating ATPV: 12.4 cal/cm² CAT 2

#### 40577

- 1200 Royal Blue
- 5000 Red

#### 40579

- 1100 Dark Navy
- 1200 Royal Blue
- 5000 Red

## Viking® Firewall FR® CSA High Visibility FR Coveralls

- Fully compliant with CSA Z96-15 Class 3, level 2
- Meets WCB/Worksafe BC/DOT configuration
- RT80 featuring 3M Scotchlite™ Reflective Material–9740 industrial wash flame-resistant trim (4" yellow/silver/yellow)
- Two-way breakaway Nomex® backed YKK® front zipper, adjustable cuffs, tunnel collar with hook-and-loop closure
- 2 front upper pockets (including 1 mesh gas monitor pocket), and 2 lower front pouch pockets with side access vents
- 2 chest straps
- 1 tool pocket on rear right leg, and 1 left sleeve pencil pocket
- Elasticized waist on the back and fully stitched bi-swing back for better fit and mobility
- All seams double-stitched and stress points bar tacked for ultimate durability
- Dual hazard protection from electrical arc and hydrocarbon flash fire

40479 available in SR - 5XLT

Size **SR - 4XLR** **3M Scotchlite™** **WESTEX®** *by Milliken*

### 40477 Viking® Firewall FR® CSA High Visibility FR Coveralls 7 oz.

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- 7 oz. Westex by Milliken® flame-resistant fabric - 88% cotton / 12% nylon
- TPP Value: Contact 8.5, Spaced 9.0
- ARC rating ATPV: 9.2 cal/cm² CAT 2

### 40479 Viking® Firewall FR® CSA High Visibility FR Coveralls 9 oz.

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- 9 oz. Westex by Milliken® flame-resistant fabric - 88% cotton / 12% nylon
- TPP Value: Contact 10.3, Spaced 11.4
- ARC rating ATPV: 12.4 cal/cm² CAT 2



#### 40477 40479

- 5400 Orange



**40677**

	1100 Dark Navy
	1200 Royal Blue
	5000 Red
	5400 Orange

**40679**

	5400 Orange
--	-------------

**Viking® Firewall FR® CSA Striped Coveralls**

- RT80 featuring 3M Scotchlite™ Reflective Material – 9740 industrial wash flame resistant trim (2" yellow/silver/yellow). CSA Z96-15 Class 1, Level FR striping pattern.
- Two-way breakaway Nomex® backed YKK® front zipper
- Adjustable cuffs, tunnel collar with hook-and-loop closure
- 2 front upper pockets (including 1 mesh gas monitor pocket), and 2 lower front pouch pockets with side access vents
- 2 chest straps
- One tool pocket on rear right leg, one left sleeve pencil pocket
- Elasticized waist on the back and fully stitched bi-swing back for better fit and mobility
- All seams double-stitched and stress points bar tacked for ultimate durability
- Dual hazard protection from electrical arc and hydrocarbon flash fire

1100 and 1200 available in XSR - 5XLR; 5400 available in SR - 4XLR

Size **SR - 5XLR**



**40677 Viking® Firewall FR® CSA Striped Coveralls 7 oz.**

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269, CSA Z96-15 Class 1, Level FR.
- High visibility orange (5400) complies with CSA Z96-15 Class 3, Level FR
- 7 oz. Westex® by Milliken® flame-resistant fabric - 88% cotton / 12% nylon
- TPP Value: Contact 8.5, Spaced 9.0
- ARC rating ATPV: 9.2 cal/cm² CAT 2

**40679 Viking® Firewall FR® CSA Striped Coveralls 9 oz.**

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269, CSA Z96-15 Class 3, Level FR
- 9 oz. Westex® by Milliken® flame-resistant fabric - 88% cotton / 12% nylon
- TPP Value: Contact 10.3, Spaced 11.4
- ARC rating ATPV: 12.4 cal/cm² CAT 2



**VC49**

	5400 Orange
--	-------------

**Viking® Firewall FR® Miner 49er Mining Coveralls**

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269, CSA Z96-15 Class 3, Level 2
- 2" Vi-brance® flame-resistant industrial wash reflective tape
- 7 oz. Westex® by Milliken® flame-resistant fabric - 88% cotton / 12% nylon
- TPP Value: Contact 8.5, Spaced 9.0
- ARC rating ATPV: 9.2 cal/cm² CAT 2
- Two-way breakaway Nomex® backed YKK® front zipper
- Adjustable cuffs, tunnel collar with snap closure
- 2 front upper pockets, and 2 lower front pouch pockets
- Fully stitched bi-swing back for better fit and mobility
- All seams double-stitched and stress points bar tacked for ultimate durability
- Dual hazard protection from electrical arc and hydrocarbon flash fire

Size **S - 4XL**





**Viking® Firewall FR® CXP® Nomex® CSA Striped Coveralls**

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269, CSA Z96-15 (Class 1/Level FR)
- 5.8 oz. DuPont® CXP® HRC2 Nomex® IIIA
- TPP Value: Contact 7.9, Spaced 13.5
- ARC rating ATPV: 10.2 cal/cm² CAT 2
- RT80 featuring 3M Scotchlite™ Reflective Material-9740 industrial wash flame-resistant trim (2" yellow/silver/yellow)
- Two-way breakaway Nomex® backed YKK® front zipper
- Adjustable cuffs, tunnel collar with hook-and-loop closure
- 2 front upper pockets (including 1 mesh gas monitor pocket), and 2 lower front pouch pockets with side access vents
- 1 tool pocket on rear right leg, and 1 left sleeve pencil pocket
- Elasticized waist on the back and fully stitched bi-swing back for better fit and mobility
- All seams double-stitched and stress points bar tacked for ultimate durability
- Dual hazard protection from electrical arc and hydrocarbon flash fire



Size **SR - 3XLT**



**40665**  
1200 Royal Blue

**Viking® Firewall FR® CXP® Nomex® IIIA CSA Striped Bib Overalls**

- Meets safety standards: PPE Category 1, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269, CSA Z96-15 (Class 1/Level FR)
- 5.8 oz. DuPont® CXP® HRC2 Nomex® IIIA
- TPP Value: Contact 7.9, Spaced 13.5
- ARC rating ATPV: 10.2 cal/cm² CAT 2
- RT80 featuring 3M Scotchlite™ Reflective Material – 9740 industrial wash flame-resistant trim (2" yellow/silver/yellow)
- Two-way breakaway Nomex® backed YKK® front zipper with exterior storm flap closure
- Shoulder suspenders with adjustable buckles
- 2 front upper chest pockets, 2 large back pockets, and 2 lower front patch pockets
- Right tool pocket and hammer loop on left rear
- All seams double-stitched and stress points bar tacked for ultimate durability
- Dual hazard protection from electrical arc and hydrocarbon flash fire



Size **S - 5XL**




**41666**  
1200 Royal Blue

### Viking® Firewall FR® CSA Striped Bib Overalls



41679

	1100 Dark Navy
	1200 Royal Blue
	5400 Orange

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269, CSA Z96-15 Class 1, Level FR.
- High visibility orange (5400) complies with CSA Z96-15 Class 2, Level FR
- 9 oz. Westex® by Milliken® flame-resistant fabric - 88% cotton / 12% nylon
- TPP Value: Contact 10.3, Spaced 11.4
- ARC rating ATPV: 12.4 cal/cm<sup>2</sup> CAT 2
- RT80 featuring 3M Scotchlite™ Reflective Material – 9740 industrial wash flame-resistant trim (2" yellow/silver/yellow)
- Two-way breakaway Nomex® backed YKK® front zipper with exterior storm flap closure
- Shoulder suspenders with adjustable buckles
- 2 front upper chest pockets, 2 large back pockets, and 2 lower front patch pockets
- Right tool pocket and hammer loop on left rear
- All seams double-stitched and stress points bar tacked for ultimate durability
- Dual hazard protection from electrical arc and hydrocarbon flash fire

Size S - 5XL



### Viking® Firewall FR® CSA Striped Insulated Coveralls



52679

	1200 Royal Blue
---	-----------------

- Meets safety standards: PPE Category 3, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269, CSA Z96-15 Class 1, Level FR
- 9 oz. Westex® by Milliken® Flame Resistant Fabric – 88% cotton/ 12% nylon (outer layer)
- 12 oz. Quilted modacrylic lining with wind and vapour barrier
- TPP Value: Contact 10.3, Spaced 11.4
- ARC rating ATPV: 35 cal/cm<sup>2</sup> CAT 3
- RT80 featuring 3M Scotchlite™ Reflective Material–9740 industrial wash flame-resistant trim (2" yellow/silver/yellow)
- Two-way breakaway Nomex® backed YKK® front zipper with exterior storm flap closure
- FR storm cuffs
- Tunnel collar with closure
- 2 upper front pockets, 2 lower front patch pockets, and 2 large hip patch pockets
- 1 tool pocket on rear right leg, and 1 left sleeve pencil pocket
- Easy boot access with 33" Nomex® backed YKK® #10 side two-way brass leg zippers
- Double knees and elastic waistband
- Snap-on hard hat hood sold separately (68G79)
- Dual hazard protection from electrical arc and hydrocarbon flash fire

Size XS - 3XL



## Viking® Firewall FR® CXP® Nomex® Striped Insulated Overalls

- Meets safety standards: PPE Category 3, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- 5.8 oz. DuPont® CXP® HRC2 Nomex® IIIA (outer shell)
- 12 oz. quilted modacrylic lining with wind and vapor barrier
- TPP Value: Contact 7.9, Spaced 13.5
- ARC rating ATPV: 32 cal/cm² CAT 3
- RT80 featuring 3M Scotchlite™ Reflective Material–9740 industrial wash flame-resistant trim (2" yellow/silver/yellow)-striping around lower legs
- Easy boot access with 15.5" Nomex® backed YKK® leg zippers
- Elastic shoulder suspenders with adjustable buckles
- 1 upper pocket with closure and pencil slot, 2 rear patch pockets, 2 lower front patch pockets, 1 right tool pocket
- Double knees and elastic waistband
- Dual hazard protection from electrical arc and hydrocarbon flash fire



Size **S - 4XL** **3M Scotchlite™** **DuPont® CXP®** **Milliken® Nomex®**  
HRC 2 Inherent FR Fabric

**51566**  
1200 Royal Blue

## Viking® Firewall FR® Striped Insulated Overalls

- Meets safety standards: PPE Category 3, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- 9 oz. Westex® by Milliken® flame-resistant fabric - 88% cotton / 12% nylon (outer shell)
- 12 oz. quilted modacrylic lining with wind and vapor barrier
- TPP Value: Contact 10.3, Spaced 11.4
- ARC rating ATPV: 35 cal/cm² CAT 3
- RT80 featuring 3M Scotchlite™ Reflective Material – 9740 industrial wash flame resistant trim (2" yellow/silver/yellow) – Striping around Lower Legs.
- Nomex® backed YKK® two-way breakaway front zipper with exterior storm flap closure
- Easy boot access with 15.5" Nomex® backed YKK® leg zippers
- Elastic shoulder suspenders with adjustable buckles
- 1 upper pocket with closure and pencil slot, 2 rear patch pockets, 2 lower front patch pockets, 1 right tool pocket
- Double knees and elastic waistband
- Dual hazard protection from electrical arc and hydrocarbon flash fire




Size **XS - 5XL** **3M Scotchlite™** **WESTEX®**  
by Milliken

**51579**  
1100 Dark Navy  
1200 Royal Blue



51679



### Viking® Firewall FR® Striped Insulated Overalls

- Meets safety standards: PPE Category 3, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269, CSA Z96-15 Class 2/Level FR
- 9 oz. Westex® by Milliken® flame-resistant fabric - 88% cotton / 12% nylon (outer shell)
- 12 oz. quilted modacrylic lining with wind and vapor barrier
- TPP Value: Contact 10.3, Spaced 11.4
- ARC rating ATPV: 35 cal/cm<sup>2</sup> CAT 3
- Nomex® backed YKK® Two-way breakaway front zipper with exterior storm flap closure
- Easy boot access with 15.5" Nomex® backed YKK® leg zippers
- Elastic shoulder suspenders with adjustable buckles
- 2 rear patch pockets, 2 lower front patch pockets, 1 right tool pocket
- Double knees and elastic waistband
- Dual hazard protection from electrical arc and hydrocarbon flash fire

Size M - 4XL



55679



### Viking® Firewall FR® CSA Striped Insulated Parka

- Meets safety standards: PPE Category 3, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70-2015, OSHA 1910.269, CSA Z96-15 Class 1/Level FR
- High visibility orange (5400) is compliant with CSA Z96-15 Class 2/Level FR
- 9 oz. Westex® by Milliken® flame-resistant fabric - 88% cotton / 12% nylon (outer shell)
- 12 oz. Quilted modacrylic lining with wind and vapour barrier
- TPP Value: Contact 10.3, Spaced 11.4
- ARC rating ATPV: 35 cal/cm<sup>2</sup> CAT 3
- RT80 featuring 3M Scotchlite™ Reflective Material – 9740 industrial wash flame-resistant trim (2" yellow/silver/yellow)
- Two-way breakaway Nomex® backed YKK® front zipper with exterior storm flap closure
- Tunnel collar with closure
- 2 large upper chest pockets (including 1 mesh gas monitor pocket), 2 oversized lower front patch pockets with closure flaps and side entry hand warmer pockets with FR fleece pocket lining
- Left sleeve pencil pocket and 1 left inside pocket
- 2 chest straps
- Bi-swing back with elasticized waistband and drawstring with cord locks
- FR storm cuffs
- Snap-on hard hat hood sold separately (68G79)
- Dual hazard protection from electrical arc and hydrocarbon flash fire

5400 available in SR - 4XLR  
5000 available in SR - 5XLR

Size XSR - 5XLT





**Viking® Firewall FR® CXP® Nomex® Striped Insulated Parka**



- Meets safety standards: PPE Category 3, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- 5.8 oz. DuPont® CXP® HRC2 Nomex® IIIA (outer shell)
- 12 oz. Quilted modacrylic lining with wind and vapour barrier
- TPP Value: Contact 7.9, Spaced 13.5
- ARC rating ATPV: 32 cal/cm² CAT 3
- RT80 featuring 3M Scotchlite™ Reflective Material – 9740 industrial wash flame-resistant trim (2" yellow/silver/yellow)
- Two-way breakaway Nomex® backed YKK® front zipper with exterior storm flap closure
- Tunnel collar with closure
- 2 large upper pockets (including 1 mesh gas monitor pocket), 2 lower front patch pockets with closure flaps and side entry
- Left sleeve pencil pocket, and 1 left inside pocket
- 2 chest straps
- Bi-swing back with elasticized waistband and drawstring with cord locks
- FR storm cuffs, thread, and tape
- Snap-on hard hat hood sold separately (68G66)
- Dual hazard protection from electrical arc and hydrocarbon flash fire

**55566**

1200 Royal Blue

Size SR - 5XLR



### Viking® Firewall FR® Hard Hat Winter Hood



68G79

- 1100 Dark Navy
- 1200 Royal Blue
- 5000 Red
- 5400 Orange

- Meets safety standards: PPE Category 3, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- 9 oz. Westex® by Milliken® Flame Resistant Fabric - 88% cotton/12% nylon (outer shell)
- 12 oz. Quilted modacrylic lining with wind and vapour barrier
- TPP Value: Contact: 10.3, Spaced 11.4
- ARC rating ATPV: 35cal/cm<sup>2</sup>
- CAT 3
- Front drawstring closure with cord locks
- FR hook-and-loop closing storm flap face protector
- Snap onto Style 55679 Parka, 52679 Insulated Coveralls, 55566 Insulated Parka

Size Fits all



62F00

- 1000 Black

### Nomex® IIIA Knit Toque

- Meets safety standards: CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- Nomex® IIIA knit fabric
- Double thick knit construction
- Flat seaming for comfort

Size Fits all



6T779

- 1200 Royal Blue

### Viking® Firewall FR® Ankle Guard

- Meets safety standards: PPE Category 2, CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- 9 oz. Westex® by Milliken® Flame Resistant Fabric - 88% cotton/12% nylon blend
- TPP Value: Contact: 10.3, Spaced 11.4
- ARC rating ATPV: 12.4 cal/cm<sup>2</sup> CAT 2
- 2 layers of fabric
- Hook and loop closure

Size Fits all

