



Model	Temperature	Dimension	Volume	Weight	Refrigerant	Power
SRR-681HP(E) (CHILLER)	-6°C ~ +12°C	Ext: W620xD800xH2000 Int: W484xD682xH1514	483 L	98kg	R134A	Cooling: 220V / 375W (50Hz) Defrosting: 220V / 357W (50Hz)
SRR-781HP(E) (CHILLER)	-6°C ~ +12°C	Ext: W745xD800xH2000 Int: W609xD682xH1514	610 L	104kg	R134A	Cooling: 220V / 380W (50Hz) Defrosting: 220V / 357W (50Hz)
SRF-681HP(E) (FREEZER)	-25°C ~ -15°C	Ext: W620xD800xH2000 Int: W484xD682xH1514	471 L	98kg	R404A	Cooling: 220V / 580W (50Hz) Defrosting: 220V / 476W (50Hz)
SRF-781HP(E) (FREEZER)	-25°C ~ -15°C	Ext: W745xD800xH2000 Int: W609xD682xH1514	598 L	104kg	R404A	Cooling: 220V / 580W (50Hz) Defrosting: 220V / 476W (50Hz)

Design Features



**PILLARLESS
DESIGN**



**LOCKING
SYSTEM**



**EASY
CLEANING**

Stable Temperature Range

Refrigerator
-6°C to 12°C

Freezer
-25°C to -15°C