



Model	Temperature	Dimension	Volume	Weight	Refrigerant	Power
SUR-K1561S (CHILLER)	-6°C ~ +12°C	Ext: W1500xD600xH800 Int: W1130xD487xH609	328 L	72kg	R134a	Cooling: 100V / 125/125W (50/60Hz) Defrosting: 100V / 137/137W (50/60Hz)
SUF-K1561S (FREEZER)	-20°C	Ext: W1500xD600xH800 Int: W1130xD487xH609	328 L	73kg	R134a	Cooling: 100V / 175/175W (50/60Hz) Defrosting: 100V / 268/268W (50/60Hz)
SUR-K1571S (CHILLER)	-6°C ~ +12°C	Ext: W1500xD750xH800 Int: W1130xD637xH609	432 L	78kg	R134a	Cooling: 100V / 125/125W (50/60Hz) Defrosting: 100V / 137/137W (50/60Hz)
SUF-K1571S (FREEZER)	-20°C	Ext: W1500xD750xH800 Int: W1130xD637xH609	432 L	79kg	R134a	Cooling: 100V / 175/175W (50/60Hz) Defrosting: 100V / 268/268W (50/60Hz)

High energy saving performance

- Inverter compressor
- Automatic frame heater duty optimization
- Automatic condensing fan speed control

