



info@ionups.com.au
www.ionups.com.au

P: 1300 700 805

F-SP12

1RU Sensor Pod

12 Port



The ION SP12 sensor pod is an Australian designed and engineered system. This premium, compact, cost effective system has been designed for real time environmental monitoring. With capability of having up to twelve sensors per sensor pod the SP12 supports a large range of sensor options including temperature, dry contact, leak rope and reed switches, this fully integrated 1RU solution can be customized to meet your needs.



F-SP12 FEATURES

- 3 year advanced replacement warranty*
- Compact 1RU Design
- LCD Interface
- SNMP Communication
- Email Notification
- Ethernet and WiFi compatible
- Easy Integration

SENSORS SUPPORTED

- Temperature
- Humidity
- Smoke
- Water (Leakrope/ spot)
- Vibration
- Noise
- Dry Contact
- Reed Switch
- Dust

F-SP12

1RU Sensor Pod

Specifications

F-SP12	
Input	
Number of Power Cords	1
Input Power	10Amp
Input Cable	2m - C13 to Australian 3 Pin
Output	
Power Consumption	5 Watts Max Consumption
Physical	
Maximum Height	43mm
Maximum Width	440mm
Maximum Depth	90mm
Rack Height	1U
Net Weight	1.2kg
Environmental	
Operating Environment	0 - 45 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 65 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters
General	
Type of External Sensors Supported	Temperature, Humidity, Smoke, Water (Leakrope/ spot), Vibration, Noise, Dry Contact, Reed Switch, Dust
Included	2 x 4m temp sensor
Communication	
Standard Communication	Communication over SNMP and Web browser Ethernet and Wi-Fi compatible
Control Panel	LCD
Warranty	
Standard Warranty	3 Year Advanced Replacement*

*Product specifications are subject to change without further notice.

*3 Year advanced replacement warranty F-SP12 please refer to the ION website for more information.