



MODEL	Volume (L)	Temperature	Dimension	Refrigerant	Power	Accessories
<b>SRR-K961S</b> (CHILLER)	611 94kg	-6 ~ +12°C	Ext: W900xD650xH1950 Int: W800xD550xH1450	R134a	<b>Cooling:</b> 100V / 179/179W (50/60Hz) <b>Defrosting:</b> 100V / 324/324W (50/60Hz)	4 Shelves
<b>SRF-K961SA</b> (FREEZER)	605 100kg	-15 ~ -25°C	Ext: W900xD650xH1950 Int: W800xD550xH1450	R404A	<b>Cooling:</b> 100V / 380/380W (50/60Hz) <b>Defrosting:</b> 100V / 556/556W (50/60Hz)	4 Shelves
<b>SRR-K981S</b> (CHILLER)	803 102kg	-6 ~ +12°C	Ext: W900xD800xH1950 Int: W800xD700xH1450	R134a	<b>Cooling:</b> 100V / 179/179W (50/60Hz) <b>Defrosting:</b> 100V / 324/324W (50/60Hz)	4 Shelves
<b>SRF-K981SA</b> (FREEZER)	797 110kg	-15 ~ -25°C	Ext: W900xD800xH1950 Int: W800xD700xH1450	R404A	<b>Cooling:</b> 100V / 380/380W (50/60Hz) <b>Defrosting:</b> 100V / 556/556W (50/60Hz)	4 Shelves

ECONAVI



### High energy saving performance

- Inverter compressor
- Automatic frame heater duty optimization
- Automatic condensing fan speed control

