



Model	Temperature	Dimension	Volume	Weight	Refrigerant	Power
SRR-1281HP(E) (CHILLER)	-6°C ~ +12°C	Ext: W1210xD800xH2000 Int: W1074xD682xH1514	1080 L	131kg	R134A	Cooling: 220V / 740W (50Hz) Defrosting: 220V / 730W (50Hz)
SRR-1581HP(E) (CHILLER)	-6°C ~ +12°C	Ext: W1460xD800xH2000 Int: W1324xD682xH1514	1329 L	148kg	R134A	Cooling: 220V / 750W (50Hz) Defrosting: 220V / 730W (50Hz)
SRF-1281HP(E) (FREEZER)	-25°C ~ -15°C	Ext: W1210xD800xH2000 Int: W1074xD682xH1514	1080 L	131kg	R404A	Cooling: 220V / 1370W (50Hz) Defrosting: 220V / 886W (50Hz)
SRF-1581HP(E) (FREEZER)	-25°C ~ -15°C	Ext: W1460xD800xH2000 Int: W1324xD682xH1514	1312 L	148kg	R404A	Cooling: 220V / 1380W (50Hz) Defrosting: 220V / 897W (50Hz)

Design Features



**PILLARLESS
DESIGN**



**LOCKING
SYSTEM**



**EASY
CLEANING**

Stable Temperature Range

Refrigerator
-6°C to 12°C

Freezer
-25°C to -15°C