



| MODEL | Volume (L) | Temperature | Dimension | Refrigrant | Power | Accessories |
|--------------------------------|---------------|-------------|------------------------------------------------|------------|-------------------------------------------------------------------------------------------------------|-------------|
| SRR-K1561S (CHILLER) | 1042 131kg | -6 ~ +12°C | Ext: W1460xD650xH1950 Int: W1360xD550xH1450 | R134a | Cooling: 100V / 222/222W (50/60Hz) Defrosting: 100V / 446/446W (50/60Hz) | 4 Shelves |
| SRF-K1563S (FREEZER) | 1042 141kg | -15 ~ -25°C | Ext: W1460xD650xH1950 Int: W1360xD550xH1450 | R404A | Cooling: 200V / 393/393W (50/60Hz) Defrosting: 200V / 567/567W (50/60Hz) | 4 Shelves |
| SRR-K1581S (CHILLER) | 1343 143kg | -6 ~ +12°C | Ext: W1460xD800xH1950 Int: W1360xD700xH1450 | R134a | Cooling: 100V / 222/222W (50/60Hz) Defrosting: 100V / 446/446W (50/60Hz) | 4 Shelves |
| SRF-K1583S (FREEZER) | 1343 148kg | -15 ~ -25°C | Ext: W1460xD800xH1950 Int: W1360xD700xH1450 | R404A | Cooling: 200V / 393/393W (50/60Hz) Defrosting: 200V / 567/567W (50/60Hz) | 4 Shelves |

ECONAVI



High energy saving performance

- Inverter compressor
- Automatic frame heater duty optimization
- Automatic condensing fan speed control

