

TWO-PIECE HOSE FITTING



VOSS & **FLEXEQUIP**

PARTNERS

TWO-PIECE HOSE FITTINGS

INTRODUCTION

SAFETY & FLEXIBILITY WITH VOSS HOSE FITTINGS –

Hydraulic systems are only as efficient as each individual component. So VOSS Fluid places the same high demands on the quality of its hose fittings as on the rest of the range. This is true for their leakage and assembly reliability as well as their versatility and durability. The synergy between VOSS Fluid hose fittings and other VOSS coupling systems guarantees the right fit for any application.

All components and systems from VOSS are perfectly matched. Uniform values and parameters make assembly easier, more reliable and increase protection against leakage while improving the load capacity. In addition, as the standard VOSS Fluid solutions provide exemplary corrosion protection that has set the benchmark in the market and significantly increase the product service lives.

THREAD TYPES STOCKED

BSP

JIC

METRIC

ORFS

**TWO-PIECE
BANJO FITTINGS**

STANDPIPE JETWASH

VOSS
FLEXEQUIP



TWO-PIECE HOSE FITTINGS

INTRODUCTION



PRECISION

Precision-engineering solutions developed from decades of competence and expertise.



HIGHEST LEAK-PROOFING

Highest leak-proofing thanks to standardisation of system components.



ASSEMBLY

Efficient assembly reliability thanks to consistent assembly criteria.



CORROSION PROTECTION

Standard, long service life through maximum corrosion protection with zinc nickel coating.



VERSATILITY

Versatility with multi-variant product solutions.

INDEX

FERRULES	B1-1
BSP FITTINGS	B1-4
BANJO BOLT BSP & METRIC	B1-11
JIC FITTINGS	B1-13
METRIC FITTINGS	B1-15
STANDPIPE FITTINGS	B1-21
ORFS FITTINGS	B1-23
JETWASH FITTINGS	B1-25
SAE FITTINGS	B1-26
CAT FLANGE FITTINGS	B1-30

VOSS & FLEXEQUIP FERRULES AVAILABLE FOR 3/16" UP TO 2" HOSE.
Skive and No-skive Ferrules available for different types of hose application.

FEATURES

- Precision-engineered solutions made from decades of expertise and know-how.
- Perfect alignment between fittings and couplings.
- Standard durability thanks to maximum corrosion-protection with a zinc-nickel base.


*NOTE

- Always ensure to push the ferrule onto the hose until it fully bottoms.
- Lubricate the insert with light oil and push into the hose.
- Check that tube is correctly placed before Swaging.

PF 11-

EN853-1ST/1SN & EN857-1SC/2SC HOSES SKIVE

Part No.	Hose Bore		Dimensions		Box Qty.	VOSS Designation
	Ins.	mm	lg	d		
PF 11 EN853-1ST/1SN & EN857-1SC/2SC Hoses Skive						
PF 11 05	3/16"	5	26	17	150	HF-FER/PF11-DN05-OS
PF 11 06	1/4"	6	31	20	150	HF-FER/PF11-DN06-OS
PF 11 08	5/16"	8	31	21	150	HF-FER/PF11-DN08-OS
PF 11 10	3/8"	10	31	24	200	HF-FER/PF11-DN10-OS
PF 11 13	1/2"	13	35	28	150	HF-FER/PF11-DN12-OS
PF 11 16	5/8"	16	36	31	125	HF-FER/PF11-DN16-OS
PF 11 19	3/4"	19	43	35	80	HF-FER/PF11-DN19-OS
PF 11 25	1"	25	51	42	50	HF-FER/PF11-DN25-OS
PF 11 32	1.1/4"	32	59	52	15	HF-FER/PF11-DN32-OS
PF 11 38	1.1/2"	38	63	58	10	HF-FER/PF11-DN38-OS
PF 11 50	2"	50	70	71	10	HF-FER/PF11-DN50-OS



AVAILABLE IN STAINLESS STEEL

AVAILABLE IN STAINLESS STEEL

PF 12-

EN853-2ST/2SN & EN856-4SP/R12 HOSES SKIVE

Part No.	Hose Bore		Dimensions		Box Qty.	VOSS Designation
	Ins.	mm	lg	d		
PF 12 EN853-2ST/2SN & EN856-4SP/R12 Hoses Skive						
PF 12 05	3/16"	5	26	21	150	HF-FER/PF12-DN05-OS
PF 12 06	1/4"	6	30	22	150	HF-FER/PF12-DN06-OS
PF 12 08	5/16"	8	30	23	150	HF-FER/PF12-DN08-OS
PF 12 10	3/8"	10	31	26	200	HF-FER/PF12-DN10-OS
PF 12 13	1/2"	13	32	30	150	HF-FER/PF12-DN13-OS
PF 12 16	5/8"	16	38	33	125	HF-FER/PF12-DN16-OS
PF 12 19	3/4"	19	43	38	75	HF-FER/PF12-DN19-OS
PF 12 25	1"	25	51	46	40	HF-FER/PF12-DN25-OS
PF 12 32	1.1/4"	32	58	57	10	HF-FER/PF12-DN32-OS
PF 12 38	1.1/2"	38	62	65	10	HF-FER/PF12-DN38-OS
PF 12 50	2"	50	74	79	10	HF-FER/PF12-DN51-OS

AVAILABLE IN STAINLESS STEEL


PF13-

EN853-2ST/2SN & EN856-4SP/R12 HOSES – SKIVE

Part No.	Hose Bore		Dimensions		Box Qty.	VOSS Designation
	Ins.	mm	lg	d		

PF 13

EN853-2ST/2SN & EN856-4SP/R12 Hoses Skive



PF 13 16	5/8"	16	33	38	125	HF-FER/PF13-DN16-OS
PF 13 19	3/4"	19	38	43	75	HF-FER/PF13-DN19-OS
PF 13 25	1"	25	46	51	40	HF-FER/PF13-DN25-OS

AVAILABLE IN STAINLESS STEEL


PF15-

EN857-1SC/2SN & EN853-1SC HOSES – NO SKIVE

Part No.	Hose Bore		Dimensions		Box Qty.	VOSS Designation
	Ins.	mm	lg	d		

PF 15

EN857-1SC/2SC & EN853 1SN Hoses - No Skive



PF 15 06	1/4"	6	30	20	150	HF-FER/PF15-DN06-OS
PF 15 08	5/16"	8	30	22	150	HF-FER/PF15-DN08-OS
PF 15 10	3/8"	10	31	24	200	HF-FER/PF15-DN10-OS
PF 15 13	1/2"	13	32	28	150	HF-FER/PF15-DN13-OS
PF 15 16	5/8"	16	36	31	125	HF-FER/PF15-DN16-OS
PF 15 19	3/4"	19	43	35	75	HF-FER/PF15-DN19-OS
PF 15 25	1"	25	51	43	40	HF-FER/PF15-DN25-OS


PF22-

EN853-1SN/2SN & R1AT/R2T HOSES – NO SKIVE

Part No.	Hose Bore		Dimensions		Box Qty.	VOSS Designation
	Ins.	mm	lg	d		

PF 22

EN853-1SN/2SN & R1AT/R2T Hoses - No Skive



PF 22 05	3/16"	5	24	21	150	HF-FER/PF22-DN05-OS
PF 22 06	1/4"	6	30	23	150	HF-FER/PF22-DN06-OS
PF 22 08	5/16"	8	30	24	150	HF-FER/PF22-DN08-OS
PF 22 10	3/8"	10	31	26	200	HF-FER/PF22-DN10-OS
PF 22 13	1/2"	13	32	29	175	HF-FER/PF22-DN13-OS
PF 22 16	5/8"	16	36	33	125	HF-FER/PF22-DN16-OS
PF 22 19	3/4"	19	43	37	75	HF-FER/PF22-DN19-OS
PF 22 25	1"	25	51	46	40	HF-FER/PF22-DN25-OS
PF 22 32	1.1/4"	32	58	59	10	HF-FER/PF22-DN32-OS
PF 22 38	1.1/2"	40	61	67	10	HF-FER/PF22-DN38-OS
PF 22 50	2"	50	74	80	10	HF-FER/PF22-DN51-OS

AVAILABLE IN STAINLESS STEEL


PF23-

**THERMOPLASTIC EN855-R7 & R8
HOSES - NO SKIVE**

Part No.	Hose Bore		Dimensions		Box Qty.	VOSS Designation
	Ins.	mm	lg	d		

PF 23

THERMOPLASTIC EN855-R7 & R8 Hoses - No Skive



PF 23 05	3/16"	5	27	14	200	HF-FER/PF23-DN05-OS
PF 23 06	1/4"	6	31	18	200	HF-FER/PF23-DN06-OS
PF 23 08	5/16"	8	32	19	200	HF-FER/PF23-DN08-OS
PF 23 10	3/8"	10	33	22	200	HF-FER/PF23-DN10-OS
PF 23 13	1/2"	13	34	26	200	HF-FER/PF23-DN13-OS

AVAILABLE IN STAINLESS STEEL


PTC-

**PTFE CONVOLUTED TAPE WRAPPED
& EXTRUDED**

Part No.	Hose Bore		Dimensions		Box Qty.	VOSS Designation
	Ins.	mm	lg	d		

PTC

PTFE CONVOLUTED TAPE WRAPPED & EXTRUDED



PTC 06	1/4"	6	27	17	500	
PTC 10	3/8"	10	31	19	125	
PTC 13	1/2"	13	33	23	250	
PTC 16	5/8"	16	35	28	200	
PTC 19	3/4"	19	41	31	150	
PTC 25	1"	25	47	38	100	
PTC 32	1.1/4"	32	53	49	50	
PTC 38	1.1/2"	38	59	54	40	
PTC 50	2"	50	72	68	15	

AVAILABLE IN STAINLESS STEEL


PTCE-

PTFE CONVOLUTED EXTRUDED

Part No.	Hose Bore		Dimensions		Box Qty.	VOSS Designation
	Ins.	mm	lg	d		

PTCE

PTFE CONVOLUTED EXTRUDED



PTCE 32	1.1/4"	32	56	50	50	
PTCE 38	1.1/2"	38	59	57	40	
PTCE 50	2"	50	72	67	15	

AVAILABLE IN STAINLESS STEEL


PTTB-

PTFE SMOOTH BORE

Part No.	Hose Bore		Dimensions		Box Qty.	VOSS Designation
	Ins.	mm	lg	d		

PTTB

PTFE SMOOTH BORE



PTTB 06	1/4"	6	27	16	500	
PTTB 10	3/8"	10	30	19	500	
PTTB 13	1/2"	13	32	24	250	
PTTB 16	5/8"	16	35	27	250	
PTTB 19	3/4"	19	40	30	150	
PTTB 25	1"	25	47	37	100	

AVAILABLE IN STAINLESS STEEL


DKR are the most common type of Female fitting used in UK & Ireland.

- Hose fittings with BSP thread and 60° taper.
- ISO 12151-6 (ISO 8434-6).
- Ideal for use in agricultural and standard hydraulic applications.

DKR- TYPE BSP FITTINGS

DKR

BSP FEMALES 60° CONE




Part No.	Thread d2	Hose Bore		Dimensions				Nut AF SW	VOSS Designation
		Ins.	DN (mm)	lg	lh	lx	dx		
DKR 02 05	G 1/8	3/16	5	42	20	16	3	14	HF/60-SWS-5-DN05
DKR 02 06	G 1/8	1/4	6	48	20	16	3	14	HF/60-SWS-5-DN06
DKR 04 06	G 1/4	1/4	6	50	22	17	4	19	HF/60-SWS-8-DN06
DKR 04 08	G 1/4	5/16	8	50	22	17	6	19	HF/60-SWS-8-DN08
DKR 06 06	G 3/8	1/4	6	53	25	19	4	22	HF/60-SWS-10-DN06
DKR 06 08	G 3/8	5/16	8	53	25	19	6	22	HF/60-SWS-10-DN08
DKR 06 10	G 3/8	3/8	10	55	25	19	7	22	HF/60-SWS-10-DN10
DKR 06 13	G 3/8	1/2	12	54	25	19	7	22	HF/60-SWS-10-DN12
DKR 08 10	G 1/2	3/8	10	57	27	21	7	27	HF/60-SWS-12-DN10
DKR 08 13	G 1/2	1/2	12	58	28	22	10	27	HF/60-SWS-12-DN12
DKR 10 13	G 5/8	1/2	12	59	30	20	10	30	HF/60-SWS-16-DN12
DKR 10 16	G 5/8	5/8	16	64	30	20	13	30	HF/60-SWS-16-DN16
DKR 12 13	G 3/4	1/2	12	61	32	22	10	32	HF/60-SWS-20-DN12
DKR 12 16	G 3/4	5/8	16	66	32	23	13	32	HF/60-SWS-20-DN16
DKR 12 19	G 3/4	3/4	19	73	34	25	15	32	HF/60-SWS-20-DN19
DKR 16 19	G 1	3/4	19	79	40	29	15	38	HF/60-SWS-25-DN19
DKR 16 25	G 1	1	25	87	40	29	20	38	HF/60-SWS-25-DN25
DKR 20 32	1.1/4"	1.1/4"	32	98	43	33	26	50	HF/60-SWOS-32-DN31
DKR 24 38	1.1/2"	1.1/2"	38	105	47	34	32	55	HF/60-SWOS-38-DN38
DKR 32 50	2"	2"	50	126	54	38	42	70	HF/60-SWOS-50-DN51

AVAILABLE IN STAINLESS STEEL

DKR 90- TYPE BSP FITTINGS

DKR 90

90° BSP FEMALES 60° CONE



Part No.	Thread d2	Hose Bore		Dimensions				Nut AF SW	VOSS Designation
		Ins.	DN (mm)	lg	lh	lx	dx		
DKR90 02 05	G 1/8	3/16	5	48	28	26	3	14	HF/60-SWE-5-DN05
DKR90 02 06	G 1/8	1/4	6	57	28	29	3	14	HF/60-SWE-5-DN06
DKR90 04 06	G 1/4	1/4	6	55	27	27	4	19	HF/60-SWE-8-DN06
DKR90 06 06	G 3/8	1/4	6	55	29	27	4	22	HF/60-SWE-10-DN06
DKR90 06 08	G 3/8	5/16	8	58	29	30	6	22	HF/60-SWE-10-DN08
DKR90 06 10	G 3/8	3/8	10	64	33	35	7	22	HF/60-SWE-10-DN10
DKR90 08 10	G 1/2	3/8	10	64	34	35	7	27	HF/60-SWE-12-DN10
DKR90 08 13	G 1/2	1/2	12	69	41	40	10	27	HF/60-SWE-12-DN12
DKR90 10 13	G 5/8	1/2	12	72	43	42	10	30	HF/60-SWE-16-DN12
DKR90 10 16	G 5/8	5/8	16	87	53	53	13	30	HF/60-SWE-16-DN16
DKR90 12 13	G 3/4	1/2	12	72	47	42	10	32	HF/60-SWE-20-DN12
DKR90 12 16	G 3/4	5/8	16	87	56	53	13	32	HF/60-SWE-20-DN16
DKR90 12 19	G 3/4	3/4	19	96	60	57	15	32	HF/60-SWE-20-DN19
DKR90 16 19	G 1	3/4	19	99	62	60	15	38	HF/60-SWE-25-DN19
DKR90 16 25	G 1	1	25	119	78	72	20	38	HF/60-SWE-25-DN25
DKR 90 20 32	1.1/4"	1.1/4"	32	151	92	96	26	50	HF/60-SWOE-32-DN31
DKR 90 24 38	1.1/2"	1.1/2"	38	176	105	118	32	55	HF/60-SWOE-38-DN38
DKR 90 32 50	2"	2"	50	217	136	144	42	70	HF/60-SWOE-50-DN51


AVAILABLE IN STAINLESS STEEL

DKRCFB- TYPE BSP FITTINGS

Part No.	Thread d2	Hose Bore		Dimensions				Nut AF SW	VOSS Designation
		Ins.	DN (mm)	lg	lh	lx	dx		

DKRCFB

BSP 90° COMPACT ELBOW (Forged Ball Type)




DKRCFB 04 06	1/4"	1/4"	6	48	22	21	6	19	
DKRCFB 06 10	3/8"	3/8"	10	55	23	26	10	22	
DKRCFB 08 13	1/2"	1/2"	13	58	27	27	13	27	
DKRCFB 12 19	3/4"	3/4"	19	77	36	37	19	32	
DKRCFB 16 25	1"	1"	25	88	40	42	25	38	

DKR 45- TYPE BSP FITTINGS

Part No.	Thread d2	Hose Bore		Dimensions				Nut AF SW	VOSS Designation
		Ins.	DN (mm)	lg	lh	lx	dx		

DKR 45

45° BSP FEMALES 60° CONE



DKR 45 02 06	1/8"	1/4"	6	63	14	35	3	14	HF/60-SWE45-5-DN06
DKR 45 04 06	1/4"	1/4"	6	61	13	33	4	19	HF/60-SWE45-8-DN06
DKR 45 06 06	3/8"	1/4"	6	62	14	34	4	22	HF/60-SWE45-10-DN06
DKR 45 06 08	3/8"	5/16"	8	64	15	36	6	22	HF/60-SWE45-10-DN08
DKR 45 06 10	3/8"	3/8"	10	70	17	40	7	22	HF/60-SWE45-10-DN10
DKR 45 08 10	1/2"	3/8"	10	71	18	41	7	27	HF/60-SWE45-12-DN10
DKR 45 08 13	1/2"	1/2"	12	79	18	49	10	27	HF/60-SWE45-12-DN12
DKR 45 10 13	5/8"	1/2"	12	81	21	51	10	30	HF/60-SWE45-16-DN12
DKR 45 10 16	5/8"	5/8"	16	96	25	62	13	30	HF/60-SWE45-16-DN16
DKR 45 12 13	3/4"	1/2"	12	84	24	54	10	32	HF/60-SWE45-20-DN12
DKR 45 12 16	3/4"	5/8"	16	98	27	64	13	32	HF/60-SWE45-20-DN16
DKR 45 12 19	3/4"	3/4"	19	109	30	70	15	32	HF/60-SWE45-20-DN19
DKR 45 16 19	1"	3/4"	19	111	32	72	15	38	HF/60-SWE45-25-DN19
DKR 45 16 25	1"	1"	25	137	35	90	20	38	HF/60-SWE45-25-DN25
DKR 45 20 32	1.1/4"	1.1/4"	32	188	50	130	32	55	HF/60-SWOE45-38-DN38
DKR 45 24 38	1.1/2"	1.1/2"	38	190	52	132	32	70	HF/60-SWOE45-50-DN38
DKR 45 32 50	2"	2"	50	232	67	159	42	70	HF/60-SWOE45-50-DN51


AVAILABLE IN STAINLESS STEEL

DKRF- TYPE BSP FITTINGS

Part No.	Thread d2	Hose Bore		Dimensions				Nut AF SW	VOSS Designation
		Ins.	DN (mm)	lg	lh	lx	dx		

DKRF

BSP FEMALE FLAT FACE




DKRF 04 06	1/4"	1/4"	6	50	22	17	4	19	
DKRF 08 08	1/2"	5/16"	8	57	27	21	7	27	
DKRF 08 10	1/2"	3/8"	10	57	27	21	7	27	
DKRF 08 13	1/2"	12"	13	58	28	22	10	27	
DKRF 12 13	3/4"	1/2"	13	61	32	22	10	32	
DKRF 12 16	3/4"	5/8"	16	66	32	23	13	32	
DKRF 12 19	3/4"	3/4"	19	73	34	25	15	32	

DKRI- TYPE BSP FITTINGS

Part No.	Thread d2	Hose Bore		Dimensions				Nut AF SW	VOSS Designation
		Ins.	DN (mm)	lg	lh	lx	dx		

DKRI


BSP FEMALE 60° INVERTED CONE - JIS (JAPANESE INDUSTRIAL STANDARD)



DKRI 04 06	1/4"	1/4"	6	50	22	17	4	19	
DKRI 06 10	3/8"	3/8"	10	64	33	35	7	22	
DKRI 08 13	1/2"	1/2"	13	58	28	22	10	27	
DKRI 12 19	3/4"	3/4"	19	73	34	25	15	32	
DKRI 16 25	1"	1"	25	87	40	29	20	38	
DKRI 20 32	1.1/4"	1.1/4"	32	98	43	33	26	50	
DKRI 24 38	1.1/2"	1.1/2"	38	105	47	34	32	55	


DKOR 45- DKOR O-RING TYPE BSP FITTINGS

Part No.	Thread d2	Hose Bore		Dimensions				Nut AF SW	VOSS Designation	Box Qty.
		Ins.	DN (mm)	lg	lh	lx	dx			
DKOR 45										
DKOR 45 04 06	1/4"	1/4"	6	61	13	33	4	19	HF/60-SWOE45-8-DN06	30
DKOR 45 06 10	3/8"	3/8"	10	70	17	40	7	22	HF/60-SWOE45-10-DN10	40
DKOR 45 08 13	1/2"	1/2"	12	79	18	49	10	27	HF/60-SWOE45-12-DN12	25
DKOR 45 10 16	5/8"	5/8"	16	96	25	62	13	30	HF/60-SWOE45-16-DN16	10
DKOR 45 12 19	3/4"	3/4"	19	108	29	69	15	32	HF/60-SWOE45-20-DN19	10
DKOR 45 16 25	1"	1"	25	137	35	90	20	38	HF/60-SWOE45-25-DN25	8
DKOR 45 20 25	1.1/4"	1"	25	135	32	88	20	50	HF/60-SWOE45-32-DN25	4
DKOR 45 20 32	1.1/4"	1.1/4"	31	165	46	111	26	50	HF/60-SWOE45-32-DN31	4
DKOR 45 24 32	1.1/2"	1.1/4"	31	165	45	111	26	55	HF/60-SWOE45-38-DN31	4
DKOR 45 24 38	1.1/2"	1.1/2"	38	188	50	130	32	55	HF/60-SWOE45-38-DN38	6
DKOR 45 32 38	2"	1.1/2"	38	190	52	132	32	70	HF/60-SWOE45-50-DN38	4
DKOR 45 32 50	2"	2"	51	232	67	159	42	70	HF/60-SWOE45-50-DN51	3



DKORD- DKOR O-RING TYPE BSP FITTINGS

Part No.	Thread d2	Hose Bore		Dimensions				Nut AF SW	VOSS Designation	Box Qty.
		Ins.	DN (mm)	lg	lh	lx	dx			
DKORD (Slip Nut)										
DKORD 04 06	1/4"	1/4"	6	50	22	17	4	19		100
DKORD 06 10	3/8"	3/8"	10	55	25	19	7	22		150
DKORD 08 13	1/2"	1/2"	13	58	28	22	10	27		100




DKORD 90- DKOR O-RING TYPE BSP FITTINGS

Part No.	Thread d2	Hose Bore		Dimensions				Nut AF SW	VOSS Designation	Box Qty.
		Ins.	DN (mm)	lg	lh	lx	dx			
[Slip Nut]										
DKRI 04 06	1/4"	1/4"	6	50	22	17	4	19		
DKRI 06 10	3/8"	3/8"	10	64	33	35	7	22		
DKRI 08 13	1/2"	1/2"	13	58	28	22	10	27		
DKRI 12 19	3/4"	3/4"	19	73	34	25	15	32		
DKRI 16 25	1"	1"	25	87	40	29	20	38		
DKRI 20 32	1.1/4"	1.1/4"	32	98	43	33	26	50		
DKRI 24 38	1.1/2"	1.1/2"	38	105	47	34	32	55		



DKORD 45- DKOR O-RING TYPE BSP FITTINGS

Part No.	Thread d2	Hose Bore		Dimensions				Nut	VOSS Designation	Box Qty.
		Ins.	DN (mm)	lg	lh	lx	dx	AF SW		
(Slip Nut)										
DKORD 45 04 06	1/4"	1/4"	6	61	13	33	4	19		30
DKORD 45 06 10	3/8"	3/8"	10	70	17	40	7	22		40
DKORD 45 08 13	1/2"	1/2"	13	79	18	49	10	27		25



AGR are the most common type of Male fitting used in UK & Ireland.


FEATURES

- Male Hose fittings with BSP or NPT thread BSP = ISO 12151-6 (ISO 8434-6).
- NPT fittings with NPTF thread tapered.
- SAE J 516
- Ideal for use in all medium to high pressure hydraulic applications.

AGR- BSP & NPT MALE FITTINGS

AGR

BSP MALES PARALLEL 60° CONE




Part No.	Thread d2	Hose Bore		Dimensions				Nut AF SW	VOSS Designation	Box Qty.
		Ins.	DN (mm)	lg	lh	lx	dx			
AGR 06 06	3/8"	1/4"	6	54	14	26	4	22	HF/60-S-10-DN06	
AGR 06 08	3/8"	5/16"	8	54	14	26	6	22	HF/60-S-10-DN08	
AGR 06 10	3/8"	3/8"	10	56	14	26	7	22	HF/60-S-10-DN10	
AGR 06 13	3/8"	1/2"	12	57	15	27	10	22	HF/60-S-10-DN12	
AGR 08 10	1/2"	3/8"	10	60	16	30	7	27	HF/60-S-12-DN10	
AGR 08 13	1/2"	1/2"	12	61	17	31	10	27	HF/60-S-12-DN12	
AGR 10 13	5/8"	1/2"	12	63	17	33	10	30	HF/60-S-16-DN12	
AGR 10 16	5/8"	5/8"	16	67	17	33	13	30	HF/60-S-16-DN16	
AGR 12 13	3/4"	1/2"	12	63	17	33	10	32	HF/60-S-20-DN12	
AGR 12 16	3/4"	5/8"	16	67	17	33	13	32	HF/60-S-20-DN16	
AGR 12 19	3/4"	3/4"	19	74	19	35	15	32	HF/60-S-20-DN19	
AGR 16 19	1"	3/4"	19	79	21	40	15	41	HF/60-S-25-DN19	
AGR 16 25	1"	1"	25	87	21	40	20	41	HF/60-S-25-DN25	
AGR 20 25	1.1/4"	1"	25	88	21	41	20	50	HF/60-S-32-DN25	
AGR 20 32	1.1/4"	1.1/4"	31	97	23	43	26	50	HF/60-S-32-DN31	
AGR 24 38	1.1/2"	1.1/2"	38	104	24	46	32	55	HF/60-S-38-DN38	
AGR 32 50	2"	2"	51	125	27	52	42	70	HF/60-S-50-DN51	

AVAILABLE IN STAINLESS STEEL

AGR K- BSP & NPT MALE FITTINGS

AGR K

BSP MALES TAPERED



Part No.	Thread d2	Hose Bore			Dimensions				Nut AF SW	VOSS Designation	Box Qty.
		Ins.	DN (mm)	lg	lh	lx	dx				
AGR K 02 06	1/8"	1/4"	6	49	12	21	4	12	HF/60-SDS-R1/8T-DN06	50	
AGR K 04 06	1/4"	1/4"	6	54	12	26	4	14	HF/60-SDS-R1/4T-DN06	100	
AGR K 06 06	3/8"	1/4"	6	54	12	26	4	19	HF/60-SDS-R3/8T-DN06	70	
AGR K 06 08	3/8"	5/16"	8	54	12	26	6	19	HF/60-SDS-R3/8T-DN08	70	
AGR K 06 10	3/8"	3/8"	10	57	13	27	7	19	HF/60-SDS-R3/8T-DN10	70	
AGR K 08 10	1/2"	3/8"	10	61	13	32	7	22	HF/60-SDS-R1/2T-DN10	40	
AGR K 08 13	1/2"	1/2"	12	62	14	33	10	22	HF/60-SDS-R1/2T-DN12	40	
AGR K 12 16	3/4"	5/8"	16	69	15	35	13	27	HF/60-SDS-R3/4T-DN16	25	
AGR K 12 19	3/4"	3/4"	19	77	18	38	15	27	HF/60-SDS-R3/4T-DN19	20	
AGR K 16 19	1"	3/4"	19	81	18	42	15	36	HF/60-SDS-R1T-DN19	10	
AGR K 16 25	1"	1"	25	89	18	42	20	36	HF/60-SDS-R1T-DN25	20	
AGR K 20 25	1.1/4"	1"	25	92	19	45	20	46	HF/60-SDS-R11/4T-DN25	15	
AGR K 20 32	1.1/4"	1.1/4"	31	101	21	47	26	46	HF/60-SDS-R11/4T-DN31	10	
AGR K 24 38	1.1/2"	1.1/2"	38	106	21	48	32	50	HF/60-SDS-R11/2T-DN38	8	
AGR K 32 50	2"	2"	51	128	24	55	42	65	HF/60-SDS-R2T-DN51	2	

AVAILABLE IN STAINLESS STEEL


AGRF-

BSP & NPT MALE FITTINGS

Part No.	Thread d2	Hose Bore		Dimensions				Nut AF SW	VOSS Designation	Box Qty.
		Ins.	DN (mm)	lg	lh	lx	dx			

AGR F

45° BSP FEMALES 60° CONE WITH 'O' RING



AGR F 04 06	1/4"	1/4"	6	52	13	24	4	19	HF/GP-SDS-G1/4A-DN06	100
AGR F 06 10	3/8"	3/8"	10	56	14	27	7	22	HF/GP-SDS-G3/8A-DN10	70
AGR F 08 10	1/2"	3/8"	10	61	16	32	7	27	HF/GP-SDS-G1/2A-DN10	40
AGR F 08 13	1/2"	1/2"	13	62	17	33	10	27	HF/GP-SDS-G1/2A-DN12	30
AGR F 12 19	3/4"	3/4"	19	74	19	35	15	32	HF/GP-SDS-G3/4A-DN19	20

AVAILABLE IN STAINLESS STEEL


AGN-

AGN BSP & NPT MALE FITTINGS

Part No.	Thread d2	Hose Bore		Dimensions				Nut AF SW	VOSS Designation	Box Qty.
		Ins.	DN (mm)	lg	lh	lx	dx			

AGN

NPT MALES



AGN 02 06	1/8"	1/4"	6	50	12	22	4	12	HF/GP-SDS-NF1/8T-DN06	75
AGN 04 06	1/4"	1/4"	6	54	12	25.5	4	14	HF/GP-SDS-NF1/4T-DN06	50
AGN 04 10	1/4"	3/8"	10	55	12	26	7	16	HF/GP-SDS-NF1/4T-DN10	50
AGN 06 06	3/8"	1/4"	6	54	12	26	4	19	HF/GP-SDS-NF3/8T-DN06	50
AGN 06 08	3/8"	5/16"	8	54	12	26	6	19	HF/GP-SDS-NF3/8T-DN08	50
AGN 06 10	3/8"	3/8"	10	57	13	27	7	19	HF/GP-SDS-NF3/8T-DN10	70
AGN 06 13	3/8"	1/2"	12	58	14	28	10	19	HF/GP-SDS-NF3/8T-DN12	50
AGN 08 10	1/2"	3/8"	10	61	13	32	7	22	HF/GP-SDS-NF1/2T-DN10	40
AGN 08 13	1/2"	1/2"	12	62	14	33	10	22	HF/GP-SDS-NF1/2T-DN12	40
AGN 08 16	1/2"	5/8"	16	68	15	34	13	24	HF/GP-SDS-NF1/2T-DN16	30
AGN 12 13	3/4"	1/2"	12	65	16	35	10	27	HF/GP-SDS-NF3/4T-DN12	25
AGN 12 16	3/4"	5/8"	16	69	16	35	13	27		25
AGN 12 19	3/4"	3/4"	19	77	18	38	15	27	HF/GP-SDS-NF3/4T-DN19	20
AGN 16 19	1"	3/4"	19	81	18	42	15	36	HF/GP-SDS-NF1T-DN19	10
AGN 16 25	1"	1"	25	89	18	42	20	36	HF/GP-SDS-NF1T-DN25	20
AGN 20 25	1.1/4"	1"	25	92	19	45	20	46	HF/GP-SDS-NF11/4T-DN25	15
AGN 20 32	1.1/4"	1.1/4"	31	101	21	47	26	46	HF/GP-SDS-NF11/4T-DN31	10
AGN 24 38	1.1/2"	1.1/2"	38	106	21	48	32	50	HF/GP-SDS-NF11/2T-DN38	8
AGN 32 50	2"	2"	51	128	24	55	42	65	HF/GP-SDS-NF2T-DN51	2

AVAILABLE IN STAINLESS STEEL

Ideal for use in Valve blocks on all medium to high-pressure hydraulic applications.

FEATURES

- Banjo ring eye & Bolt fittings with BSP thread.
- Banjo ring eye & Bolt fittings with Metric thread.
- Double eye bolts for assembling two fittings in tandem.

RNR- BSP RING EYE'S FOR BANJOS

Part No.	Bolt Type	Thread d2	Hose Bore Ins.	mm	lg	lx	lh	d	SW	VOSS Designation	Box Qty.
RNR BSP RING EYE'S FOR BANJOS											
RNR 02 06	1/8		1/4"	6	47	13	19			HF/GP-BFE-1/8-DN06	50
RNR 04 06	1/4		1/4"	6	50	14	22	13.3		HF/GP-BFE-1/4-DN06	50
RNR 06 06	3/8		1/4"	6	53	18	22	16.7		HF/GP-BFE-3/8-DN10	50
RNR 06 08	3/8		5/16"	8	53	18	25	16.7		HF/GP-BFE-3/8-DN08	50
RNR 06 10	3/8		3/8"	10	54	18	25	16.7		HF/GP-BFE-3/8-DN10	50
RNR 08 10	1/2		3/8"	10	60	22	30	21		HF/GP-BFE-1/2-DN10	25
RNR 08 13	1/2		1/2"	13	61	22	31	21		HF/GP-BFE-1/2-DN12	25
RNR 10 13	5/8		1/2"	13	63	24	34	23		HF/GP-BFE-5/8-DN12	10
RNR 10 16	5/8		5/8"	16	68	24	34	23		HF/GP-BFE-5/8-DN16	10
RNR 12 13	3/4		1/2"	13	79	29	40	26.5		HF/GP-BFE-3/4-DN13	10
RNR 12 19	3/4		3/4"	19	79	29	40	26.5		HF/GP-BFE-3/4-DN19	10
RNR 16 19	1"		3/4"	19	87	38	48	33.3		HF/GP-BFE-1-DN19	5
RNR 16 25	1"		1"	25	95	38	48	33.3		HF/GP-BFE-1-DN25	5


F15 R- BSP BOLT FOR BANJO

Part No.	Bolt Type	Thread d2	Hose Bore Ins.	mm	lg	lx	lh	d	SW	VOSS Designation	Box Qty.
F15 R BSP BOLT FOR BANJO											
F15 R 02	1/8"	1/8"			27		20	14			100
F15 R 04	1/4"	1/4"			31		26	17			50
F15 R 06	3/8"	3/8"			38		30	22			40
F15 R 08	1/2"	1/2"			48		40	27			30
F15 R 12	3/4"	3/4"			56		47	32			20
F15 R 16	1"	1"			70		58	41			10

F15 R- BSP DOUBLE EYE BOLT FOR BANJO

Part No.	Bolt Type	Thread d2	Hose Bore Ins.	mm	lg	lx	lh	d	SW	VOSS Designation	Box Qty.
F15 R BSP DOUBLE EYE BOLT FOR BANJO											
F15 R 04 04	1/4"	1/4"			50		43	19			50
F15 R 06 06	3/8"	3/8"			58		51	22			40
F15 R 08 08	1/2"	1/2"			73		64	27			30
F15 R 12 12	3/4"	3/4"			92		81	32			20
F15 R 16 16	1"	1"			110		96	41			10

RNM- METRIC BANJOS

Part No.	Bolt Type	Thread d2	Hose Bore Ins.	mm	lg	lx	lh	d	SW	VOSS Designation	Box Qty.
RNM 12 06	12	12 x 1.5	1/4"	6	47	13	19	12.2		HF/GP-BFE-M12-DN06	25
RNM 14 06	14	14 x 1.5	1/4"	6	50	14	22	14.2		HF/GP-BFE-M14-DN06	50
RNM 14 08	14	14 x 1.5	5/16"	8	55	14	27	14.2		HF/GP-BFE-M14-DN08	40
RNM 14 10	14	14 x 1.5	3/8"	10	56	14	27	14.2		HF/GP-BFE-M14-DN10	30
RNM 16 08	16	16 x 1.5	5/16"	8	53	18	25	16.2		HF/GP-BFE-M16-DN08	25
RNM 16 10	16	16 x 1.5	3/8"	10	54	18	25	16.2		HF/GP-BFE-M16-DN10	30
RNM 18 10	18	18 x 1.5	3/8"	10	57	20	28	18.2		HF/GP-BFE-M18-DN10	30
RNM 18 13	18	18 x 1.5	1/2"	12	58	20	29	18.2		HF/GP-BFE-M18-DN12	25
RNM 22 13	22	22 x 1.5	1/2"	12	61	22	31	22.2		HF/GP-BFE-M22-DN12	25
RNM 22 16	22	22 x 1.5	5/8"	16	70	22	36	22.2		HF/GP-BFE-M22-DN16	20
RNM 26 16	26	26 x 1.5	5/8"	16	72	29	38	26.2		HF/GP-BFE-M26-DN16	10
RNM 26 19	26	26 x 1.5	3/4"	19	79	29	40	26.2		HF/GP-BFE-M26-DN19	10
RNM 30 19	30	30 x 1.5	3/4"	19	82	30	43	30.2		HF/GP-BFE-M30-DN19	5

AVAILABLE IN STAINLESS STEEL

F15 M- METRIC BOLT FOR BANJO

Part No.		Bolt Type	Thread d2	Hose Bore Ins.	mm	lg	lx	lh	d	SW	VOSS Designation	Box Qty.
F15 M		METRIC BOLT FOR BANJO										
		F15 M 10	10	10 x 1		26	21	14				50
		F15 M 12	12	12 x 1.5		30	25	17				50
		F15 M 14	14	14 x 1.5		33	27	19				70
		F15 M 16	16	16 x 1.5		39	31	22				50
		F15 M 18	18	18 x 1.5		45	36	24				50
		F15 M 22	22	22 x 1.5		47	39	27				20
		F15 M 26	26	26 x 1.5		56	44	32				20
		F15 M 30	30	30 x 1.5		58	46	38				15

Widely used in fuel delivery and fluid power applications, especially where high pressure is required.

FEATURES

- Hose fittings with UNF thread and 37°cone (JIC).
- ISO 12151-5 (ISO 8434-2).
- Sometimes referred to as - Joint Industry Council.

DKJ-

JIC FEMALES 74° CONE FITTINGS

DKJ

JIC FEMALES 74° CONE

DKJ 07 06	7/16"	1/4"	6	52	24	14	4	14	HF/37-SWS-6-DN06	100
DKJ 08 06	1/2"	1/4"	6	53	25	15	4	17	HF/37-SWS-8-DN06	125
DKJ 08 08	1/2"	5/16"	8	53	25	15	6	17	HF/37-SWS-8-DN08	100
DKJ 09 06	9/16"	1/4"	6	55	27	17	4	19	HF/37-SWS-10-DN06	100
DKJ 09 08	9/16"	5/16"	8	55	27	17	6	19	HF/37-SWS-10-DN08	100
DKJ 09 10	9/16"	3/8"	10	56	27	17	7	19	HF/37-SWS-10-DN10	75
DKJ 12 10	3/4"	3/8"	10	60	31	19	7	24	HF/37-SWS-12-DN10	50
DKJ 12 13	3/4"	1/2"	12	60	30	19	10	24	HF/37-SWS-12-DN12	40
DKJ 14 10	7/8"	3/8"	10	63	34	20	7	27	HF/37-SWS-16-DN10	40
DKJ 14 13	7/8"	1/2"	12	65	35	21	10	27	HF/37-SWS-16-DN12	30
DKJ 14 16	7/8"	5/8"	16	68	34	20	13	27	HF/37-SWS-16-DN16	30
DKJ 17 13	1.1/16"	1/2"	12	67	38	22	10	32	HF/37-SWS-20-DN12	20
DKJ 17 16	1.1/16"	5/8"	16	72	38	22	13	32	HF/37-SWS-20-DN16	20
DKJ 17 19	1.1/16"	3/4"	19	79	40	24	15	32	HF/37-SWS-20-DN19	15
DKJ 17 25	1.1/16"	1"	25	87	40	24	15	32	HF/37-SWS-20-DN25	10
DKJ 19 19	1.3/16"	3/4"	19	79	40	24	15	32	HF/37-SWS-22-DN19	15
DKJ 21 19	1.5/16"	3/4"	19	81	42	25	15	41	HF/37-SWS-25-DN19	25
DKJ 21 25	1.5/16"	1"	25	89	42	25	20	41	HF/37-SWS-25-DN25	20
DKJ 26 25	1.5/8"	1"	25	91	44	27	20	50	HF/37-SWS-30-DN25	10
DKJ 26 32	1.5/8"	1.1/4"	31	99	44	28	26	50	HF/37-SWS-30-DN31	10
DKJ 30 32	1.7/8"	1.1/4"	31	104	49	30	26	60	HF/37-SWS-38-DN31	8
DKJ 30 38	1.7/8"	1.1/2"	38	107	49	30	32	60	HF/37-SWS-38-DN38	6
DKJ 40 50	2.1/2"	2"	50	132	59	36	42	75	HF/37-SWS-50-DN50	4

AVAILABLE IN STAINLESS STEEL

AVAILABLE IN STAINLESS STEEL

DKJ90-

90° JIC FEMALES 74° CONE FITTINGS

DKJ 90

90° JIC FEMALES 74° CONE

DKJ 90 07 06	7/16"	1/4"	6	57	26	29	4	14	HF/37-SWE-6-DN06	80
DKJ 90 08 06	1/2"	1/4"	6	57	27	29	4	17	HF/37-SWE-8-DN06	40
DKJ 90 09 06	9/16"	1/4"	6	57	28	29	4	19	HF/37-SWE-10-DN06	50
DKJ 90 09 08	9/16"	5/16"	8	58	31	30	6	19	HF/37-SWE-10-DN08	25
DKJ 90 09 10	9/16"	3/8"	10	63	35	34	7	19	HF/37-SWE-10-DN10	40
DKJ 90 12 10	3/4"	3/8"	10	63	37	34	7	24	HF/37-SWE-12-DN10	30
DKJ 90 12 13	3/4"	1/2"	12	72	43	42	10	24	HF/37-SWE-12-DN12	20
DKJ 90 14 10	7/8"	3/8"	10	63	38	34	7	27	HF/37-SWE-16-DN10	20
DKJ 90 14 13	7/8"	1/2"	12	72	44	42	10	27	HF/37-SWE-16-DN12	20
DKJ 90 14 16	7/8"	5/8"	16	87	54	53	13	27	HF/37-SWE-16-DN16	10
DKJ 90 17 13	1.1/16"	1/2"	12	72	45	42	10	32	HF/37-SWE-20-DN12	10
DKJ 90 17 16	1.1/16"	5/8"	16	87	55	53	13	32	HF/37-SWE-20-DN16	10
DKJ 90 17 19	1.1/16"	3/4"	19	97	56	58	15	32	HF/37-SWE-20-DN19	15
DKJ 90 19 19	1.3/16"	3/4"	19	99	59	60	15	36	HF/37-SWE-22-DN19	15
DKJ 90 21 19	1.5/16"	3/4"	19	99	59	60	15	41	HF/37-SWE-25-DN19	6
DKJ 90 21 25	1.5/16"	1"	25	126	71	79	20	41	HF/37-SWE-25-DN25	8
DKJ 90 26 25	1.5/8"	1"	25	126	73	79	20	50	HF/37-SWE-30-DN25	10
DKJ 90 26 32	1.5/8"	1.1/4"	31	151	86	96	26	50	HF/37-SWE-30-DN31	3
DKJ 90 30 32	1.7/8"	1.1/4"	31	151	87	96	26	60	HF/37-SWE-38-DN31	3
DKJ 90 30 38	1.7/8"	1.1/2"	38	176	101	118	32	60	HF/37-SWE-38-DN38	4
DKJ 90 40 50	2.1/2"	2"	50	217	135	144	42	75	HF/37-SWE-50-DN50	2

AVAILABLE IN STAINLESS STEEL

AVAILABLE IN STAINLESS STEEL

DKJ45- 45° JIC FEMALES 74° CONE FITTINGS

DKJ 45 45° JIC FEMALES 74° CONE											
Part No.	Thread d2	Hose Bore Ins. DN (mm)	Dimensions				Nut AF SW	VOSS Designation		Box Qty.	
lg	lh	lx	dx								
DKJ 45 07 06	7/16"	1/4"	6	62	13	34	4	14	HF/37-SWE45-6-DN06	25	
DKJ 45 08 06	1/2"	1/4"	6	62	14	34	4	17	HF/37-SWE45-8-DN06	25	
DKJ 45 09 06	9/16"	1/4"	6	63	14	35	4	19	HF/37-SWE45-10-DN06	30	
DKJ 45 09 08	9/16"	5/16"	8	64	15	36	6	19	HF/37-SWE45-10-DN08	30	
DKJ 45 09 10	9/16"	3/8"	10	71	18	41	7	19	HF/37-SWE45-10-DN10	25	
DKJ 45 12 10	3/4"	3/8"	10	72	19	43	7	24	HF/37-SWE45-12-DN10	30	
DKJ 45 12 13	3/4"	1/2"	12	81	21	51	10	24	HF/37-SWE45-12-DN12	25	
DKJ 45 14 10	7/8"	3/8"	10	73	20	43	7	27	HF/37-SWE45-16-DN10	25	
DKJ 45 14 13	7/8"	1/2"	12	82	22	52	10	27	HF/37-SWE45-16-DN12	20	
DKJ 45 14 16	7/8"	5/8"	16	97	26	63	13	27	HF/37-SWE45-16-DN16	15	
DKJ 45 17 13	1.1/16"	1/2"	12	83	23	53	10	32	HF/37-SWE45-20-DN12	15	
DKJ 45 17 16	1.1/16"	5/8"	16	97	26	63	13	32	HF/37-SWE45-20-DN16	10	
DKJ 45 17 19	1.1/16"	3/4"	19	108	29	69	15	32	HF/37-SWE45-20-DN19	10	
DKJ 45 19 19	1.3/16"	3/4"	19	109	29	70	15	36	HF/37-SWE45-22-DN19	8	
DKJ 45 21 19	1.5/16"	3/4"	19	109	29	70	15	41	HF/37-SWE45-25-DN19	5	
DKJ 45 21 25	1.5/16"	1"	25	135	33	88	20	41	HF/37-SWE45-25-DN25	8	
DKJ 45 26 25	1.5/8"	1"	25	136	34	89	20	50	HF/37-SWE45-30-DN25	6	
DKJ 45 26 32	1.5/8"	1.1/4"	31	161	41	107	26	50	HF/37-SWE45-30-DN31	4	
DKJ 45 30 32	1.7/8"	1.1/4"	31	162	42	108	26	60	HF/37-SWE45-38-DN31	3	
DKJ 45 30 38	1.7/8"	1.1/2"	38	185	47	127	32	60	HF/37-SWE45-38-DN38	5	
DKJ 45 40 50	2.1/2"	2"	51	231	67	159	42	75	HF/37-SWE45-50-DN51	3	

AVAILABLE IN STAINLESS STEEL

AGJ- JIC MALES 74° CONE - UNF FITTINGS

AGJ JIC MALES 74° CONE - UNF											
Part No.	Thread d2	Hose Bore Ins. DN (mm)	Dimensions				Nut AF SW	VOSS Designation		Box Qty.	
lg	lh	lx	dx								
AGJ 07 06	7/16"	1/4"	6	54	11	25	4	14	HF/37-S-6-DN06	60	
AGJ 08 06	1/2"	1/4"	6	54	12	26	4	17	HF/37-S-8-DN06	50	
AGJ 08 08	1/2"	5/16"	8	54	11	25	6	14	HF/37-S-8-DN08	50	
AGJ 09 06	9/16"	1/4"	6	54	11	25	4	17	HF/37-S-10-DN06	50	
AGJ 09 08	9/16"	5/16"	8	54	11	25	6	19	HF/37-S-10-DN08	50	
AGJ 09 10	9/16"	3/8"	10	56	12	26	7	19	HF/37-S-10-DN10	50	
AGJ 12 10	3/4"	3/8"	10	59	13	29	7	22	HF/37-S-12-DN10	60	
AGJ 12 13	3/4"	1/2"	13	60	14	30	10	22	HF/37-S-12-DN12	25	
AGJ 14 10	7/8"	3/8"	13	63	14	33	7	24	HF/37-S-16-DN10	25	
AGJ 14 13	7/8"	1/2"	13	64	14	34	10	24	HF/37-S-16-DN12	25	
AGJ 14 16	7/8"	5/8"	16	68	14	34	13	24	HF/37-S-16-DN16	25	
AGJ 17 13	1.1/16"	1/2"	16	68	16	38	10	27	HF/37-S-20-DN12	15	
AGJ 17 16	1.1/16"	5/8"	16	72	16	38	13	32	HF/37-S-20-DN16	10	
AGJ 17 19	1.1/16"	3/4"	19	79	18	40	15	27	HF/37-S-20-DN19	10	
AGJ 17 25	1.1/6"	1"	25	87	18	40	15	32	HF/37-S-20-DN25	10	
AGJ 19 19	1.3/16"	3/4"	19	80	18	41	15	34	HF/37-S-22-DN19	10	
AGJ 21 19	1.5/16"	3/4"	19	80	18	41	15	34	HF/37-S-25-DN19	10	
AGJ 21 25	1.5/16"	1"	25	89	18	41	20	36	HF/37-S-25-DN25	10	
AGJ 26 25	1.5/8"	1"	25	90	18	43	20	42	HF/37-S-30-DN25	8	
AGJ 26 32	1.5/8"	1.1/4"	32	101	21	46	26	46	HF/37-S-30-DN31	5	
AGJ 30 32	1.7/8"	1.1/4"	32	105	23	50	26	50	HF/37-S-38-DN31	5	
AGJ 30 38	1.7/8"	1.1/2"	38	109	23	51	32	50	HF/37-S-38-DN38	8	
AGJ 40 50	2.1/2"	2"	50	134	27	61	42	65	HF/37-S-50-DN51	2	

AVAILABLE IN STAINLESS STEEL

Higher pressure resistance and functional reliability, even under extreme operating conditions.

FEATURES

- Hose fittings with 24° taper & O-ring
- Fit in bore type
- W DIN 3861/ISO 434-1
- ISO 12151-2 (ISO 8434-1)

ADVANTAGES

- Permanent stability thanks to metallic taper coupling on the fitting body and additional soft seal.
- Reliable over-tightening protection.
- Reduced work effort thanks to reduced tightening distances & tightening forces.
- Maximum tightness thanks to embedded FKM O-ring (standard).
- Improved leak-proofing & precision seal.
- Easy, fast and reliable installation
- Repeat installations can be performed frequently without any issues.

DKOL-


METRIC FEMALES 24° CONE DIN 3865 LIGHT WITH 'O' RING

Part No.	Thread d2	Hose Bore Ins. DN (mm)	Dimensions				Nut AF SW	VOSS Designation	O-ring	Box Qty.
			lg	lh	lx	dx				
DKOL METRIC FEMALES 24° CONE DIN 3865 LIGHT WITH 'O' RING										
										
								</		

AVAILABLE IN STAINLESS STEEL

DKOL 90-


90° METRIC FEMALES 24° CONE DIN 3865 LIGHT WITH 'O' RING

	Part No.	Thread d2	Hose Bore Ins. DN (mm)	Dimensions				Nut AF SW	VOSS Designation	O-ring	Box Qty.		
				lg	lh	lx	dx						
	DKOL 90 90° METRIC FEMALES 24° CONE DIN 3865 LIGHT WITH 'O' RING												
		DKOL 90 06L 06	12 x 1.5	1/4"	6	55	38	27	3	14	HF/24-SWOE-L6-DN06	4 x 1,5	50
		DKOL 90 08L 06	14 x 1.5	1/4"	6	55	34	27	4	17	HF/24-SWOE-L8-DN06	6 x 1,5	70
		DKOL 90 10L 06	16 x 1.5	1/4"	6	55	34	27	4	17	HF/24-SWOE-L10-DN06	7,5 x 1,5	40
		DKOL 90 10L 08	16 x 1.5	5/16"	8	57	34	29	6	19	HF/24-SWOE-L10-DN08	7,5 x 1,5	60
		DKOL 90 10L 10	16 x 1.5	3/8"	10	65	43	36	6	19	HF/24-SWOE-L10-DN10	7,5 x 1,5	40
		DKOL 90 12L 08	18 x 1.5	5/16"	8	58	35	30	6	22	HF/24-SWOE-L12-DN08	9 x 1,5	50
		DKOL 90 12L 10	18 x 1.5	3/8	10	65	37	36	7	22	HF/24-SWOE-L12-DN10	9 x 1,5	40
		DKOL 90 15L 13	22 x 1.5	1/2"	13	72	43	42	10	27	HF/24-SWOE-L15-DN12	12 x 2	20
		DKOL 90 18L 16	26 x 1.5	5/8"	16	87	51	53	13	32	HF/24-SWOE-L18-DN16	15 x 2	30
		DKOL 90 22L 19	30 x 2.0	3/4"	19	99	55	60	15	36	HF/24-SWOE-L22-DN19	20 x 2	20
		DKOL 90 28L 25	36 x 2.0	1"	25	127	67	80	20	41	HF/24-SWOE-L28-DN25	26 x 2	10
		DKOL 90 35L 32	45 x 2.0	1.1/4"	32	153	81	99	26	50	HF/24-SWOE-L35-DN31	32 x 2,5	5
		DKOL 90 42L 38	52 x 2.0	1.1/2"	38	170	99	112	32	60	HF/24-SWOE-L42-DN38	38 x 2,5	6

AVAILABLE IN STAINLESS STEEL

DKOL 45-


45° METRIC FEMALES 24° CONE DIN 3865 LIGHT WITH 'O' RING

Part No.	Thread d2	Hose Bore		Dimensions				Nut AF SW	VOSS Designation	O-ring	Box Qty.		
		Ins.	DN (mm)	lg	lh	lx	dx						
DKOL 45 45° METRIC FEMALES 24° CONE DIN 3865 LIGHT WITH 'O' RING													
		DKOL 45 08L 06	14 x 1.5	1/4"	6	65	18	37	4	17	HF/24-SWOE45-L8-DN06	6 x 1,5	50
		DKOL 45 10L 06	16 x 1.5	1/4"	6	65	18	37	4	19	HF/24-SWOE45-L10-DN06	7,5 x 1,5	70
		DKOL 45 10L 08	16 x 1.5	5/16"	8	68	18	40	6	19	HF/24-SWOE45-L10-DN08	7,5 x 1,5	75
		DKOL 45 10L 10	16 x 1.5	3/8"	10	78	24	48	6	19	HF/24-SWOE45-L10-DN10	7,5 x 1,5	40
		DKOL 45 12L 10	18 x 1.5	3/8"	10	74	20	45	7	22	HF/24-SWOE45-L12-DN10	9 x 1,5	25
		DKOL 45 15L 13	22 x 1.5	1/2"	13	80	22	51	10	27	HF/24-SWOE45-L15-DN12	12 x 2	25
		DKOL 45 18L 16	26 x 1.5	5/8"	16	95	25	61	13	32	HF/24-SWOE45-L18-DN16	15 x 2	15
		DKOL 45 22L 19	30 x 2.0	3/4"	19	108	27	69	15	36	HF/24-SWOE45-L22-DN19	20 x 2	10
		DKOL 45 28L 25	36 x 2.0	1"	25	133	30	86	20	41	HF/24-SWOE45-L28-DN25	26 x 2	5
		DKOL 45 35L 32	45 x 2.0	1.1/4"	32	160	38	106	26	50	HF/24-SWOE45-L35-DN31	32 x 2,5	5
DKOL 45 42L 38	52 x 2.0	1.1/2"	38	181	44	123	32	60	HF/24-SWOE45-L42-DN38	38 x 2,5	8		
AVAILABLE IN STAINLESS STEEL													

AVAILABLE IN STAINLESS STEEL

CEL-

MALES 74° DIN 3861 LIGHT

Part No.	Thread d2	Hose Bore		Dimensions				Nut AF SW	VOSS Designation	O-ring	Box Qty.	
		Ins.	DN (mm)	lg	lh	lx	dx					
CEL MALES 24° DIN 3861 LIGHT												
		CEL 06L 06	12 x 1.5	1/4"	6	50	12	22	4	14	HF/24-S-L6-DN06	50
		CEL 08L 06	14 x 1.5	1/4"	6	50	12	22	4	17	HF/24-S-L8-DN06	50
		CEL 10L 06	16 x 1.5	1/4"	6	51	12	23	4	17	HF/24-S-L10-DN06	70
		CEL 10L 08	16 x 1.5	5/16"	8	51	12	23	6	17	HF/24-S-L10-DN08	50
		CEL 10L 10	16 x 1.5	3/8"	10	54	14	25	7	17	HF/24-S-L10-DN10	50
		CEL 12L 06	18 x 1.5	1/4"	6	52	13	24	4	19	HF/24-S-L12-DN06	50
		CEL 12L 08	18 x 1.5	5/16"	8	52	13	24	6	19	HF/24-S-L12-DN08	50
		CEL 12L 10	18 x 1.5	3/8"	10	54	14	25	7	19	HF/24-S-L12-DN10	50
		CEL 15L 10	22 x 1.5	3/8"	10	55	14	26	7	24	HF/24-S-L15-DN10	30
		CEL 15L 13	22 x 1.5	1/2"	13	57	15	27	10	24	HF/24-S-L15-DN12	40
		CEL 18L 13	26 x 1.5	1/2"	13	58	16	28	10	27	HF/24-S-L18-DN12	20
		CEL 18L 16	26 x 1.5	5/8"	16	62	16	28	13	27	HF/24-S-L18-DN16	25
		CEL 22L 19	30 x 2.0	3/4"	19	71	18	32	15	32	HF/24-S-L22-DN19	10
		CEL 28L 25	36 x 2.0	1"	25	80	19	33	20	41	HF/24-S-L28-DN25	5
		CEL 35L 32	45 x 2.0	1.1/4"	32	93	23	39	26	46	HF/24-S-L35-DN31	5
		CEL 42L 38	52 x 2.0	1.1/2"	38	100	26	42	32	55	HF/24-S-L42-DN38	2
AVAILABLE IN STAINLESS STEEL												

AVAILABLE IN STAINLESS STEEL

Higher pressure resistance and functional reliability, even under extreme operating conditions.

FEATURES


- Hose fittings with 24° taper & O-ring
- Fit in bore type
- W DIN 3861/ISO 434-1
- ISO 12151-2 (ISO 8434-1)

ADVANTAGES

- Permanent stability thanks to metallic taper coupling on the fitting body & additional soft seal.
- Reliable over-tightening protection.
- Reduced work effort thanks to reduced tightening distances & tightening forces.
- Maximum tightness thanks to embedded FKM O-ring (standard).
- Improved leak-proofing & precision seal.
- Easy, fast & reliable installation.
- Repeat installations can be performed frequently without any issues.

DKOS-

METRIC FEMALES 24° CONE DIN 3865 HEAVY WITH 'O' RING


Part No.	Thread d2	Hose Bore Ins. DN (mm)	Dimensions				Nut AF SW	VOSS Designation	O-ring	Box Qty.			
			lg	lh	lx	dx							
DKOS METRIC FEMALES 24° CONE DIN 3865 LIGHT WITH 'O' RING													
		DKOS 08S 06	16 x 1.5	1/4"	6	56	28	26	4	19	HF/24-SWOS-S8-DN06	6 x 1,5	100
		DKOS 10S 06	18 x 1.5	1/4"	6	58	30	28	4	22	HF/24-SWOS-S10-DN06	7.5 x 1,5	75
		DKOS 12S 08	20 x 1.5	5/16"	8	57	29	27	6	24	HF/24-SWOS-S12-DN08	9 x 1,5	50
		DKOS 12S 10	20 x 1.5	3/8"	10	59	29	28	7	24	HF/24-SWOS-S12-DN10	9 x 1,5	50
		DKOS 14S 10	22 x 1.5	3/8"	10	65	35	31	7	27	HF/24-SWOS-S14-DN10	10 x 2	40
		DKOS 16S 13	24 x 1.5	1/2"	12	65	36	32	10	30	HF/24-SWOS-S16-DN12	12 x 2	25
		DKOS 20S 16	30 x 2	5/8"	16	75	41	38	13	36	HF/24-SWOS-S20-DN16	16,3 x 2,4	15
		DKOS 20S 19	30 x 2	3/4"	19	81	42	39	14	36	HF/24-SWOS-S20-DN19	16,3 x 2,4	15
		DKOS 25S 19	36 x 2	3/4"	19	87	48	42	15	46	HF/24-SWOS-S25-DN19	20,3 x 2,4	10
		DKOS 25S 25	36 x 2	1"	25	89	42	36	18	46	HF/24-SWOS-S25-DN25	20,3 x 2,4	5
		DKOS 30S 25	42 x 2	1"	25	98	51	43	20	50	HF/24-SWOS-S30-DN25	25,3 x 2,4	5
		DKOS 38S 32	52 x 2	1.1/4"	31	114	59	50	26	60	HF/24-SWOS-S38-DN31	33,3 x 2,4	8
AVAILABLE IN STAINLESS STEEL													

AVAILABLE IN STAINLESS STEEL

DKOS 90-

90° METRIC FEMALES 24° CONE DIN 3865 HEAVY WITH 'O' RING

Part No.	Thread d2	Hose Bore Ins. DN (mm)	Dimensions				Nut AF SW	VOSS Designation	O-ring	Box Qty.		
			lg	lh	lx	dx						
DKOS 90 90° METRIC FEMALES 24° CONE DIN 3865 HEAVY WITH 'O' RING												
	DKOS 90 08S 06	16 x 1.5	1/4"	6	55	34	27	4	19	HF/24-SWOE-S8-DN06	6 x 1,5	40
	DKOS 90 10S 06	18 x 1.5	1/4"	6	55	34	27	4	22	HF/24-SWOE-S10-DN06	7,5 x 1,5	50
	DKOS 90 12S 08	20 x 1.5	5/16"	8	58	35	30	6	24	HF/24-SWOE-S12-DN08	9 x 1,5	25
	DKOS 90 12S 10	20 x 1.5	3/8	10	65	39	36	7	24	HF/24-SWOE-S12-DN10	9 x 1,5	30
	DKOS 90 14S 10	22 x 1.5	3/8"	10	65	39	36	7	27	HF/24-SWOE-S14-DN10	10 x 2	25
	DKOS 90 16S 13	24 x 1.5	1/2"	12	72	45	42	10	30	HF/24-SWOE-S16-DN12	12 x 2	20
	DKOS 90 20S 16	30 x 2	5/8"	16	88	56	54	13	36	HF/24-SWOE-S20-DN16	16,3 x 2,4	25
	DKOS 90 20S 19	30 x 2	3/4"	19	99	59	60	14	36	HF/24-SWOE-S20-DN19	16,3 x 2,4	15
	DKOS 90 25S 19	36 x 2	3/4"	19	99	60	60	15	46	HF/24-SWOE-S25-DN19	20,3 x 2,4	5
	DKOS 90 25S 25	36 x 2	1"	25	125	81	78	18	46	HF/24-SWOE-S25-DN25	20,3 x 2,4	8
	DKOS 90 30S 25	42 x 2	1"	25	125	71	78	20	50	HF/24-SWOE-S30-DN25	25,3 x 2,4	8
	DKOS 90 38S 32	52 x 2	1.1/4"	31	153	84	99	26	60	HF/24-SWOE-S38-DN31	33,3 x 2,4	4




AVAILABLE IN STAINLESS STEEL

AVAILABLE IN STAINLESS STEEL

DKOS 45-

45° METRIC FEMALES 24° CONE DIN 3865 HEAVY WITH 'O' RING



DKOS 45


45° METRIC FEMALES 24° CONE DIN 3865 HEAVY WITH 'O' RING

Part No.	Thread d2	Hose Bore Ins. DN (mm)	Dimensions				Nut AF SW	VOSS Designation	O-ring	Box Qty.	
			lg	lh	lx	dx					
HEAVY WITH 'O' RING											
DKOS 45 08S 06	16 x 1.5	1/4"	6	66	19	38	4	19	HF/24-SW0E45-S8-DN06	6 x 1,5	40
DKOS 45 10S 06	18 x 1.5	1/4"	6	65	18	37	4	22	HF/24-SW0E45-S10-DN06	7,5 x 1,5	30
DKOS 45 12S 08	20 x 1.5	5/16"	8	69	19	41	6	24	HF/24-SW0E45-S12-DN08	9 x 1,5	25
DKOS 45 12S 10	20 x 1.5	3/8	10	75	21	46	7	24	HF/24-SW0E45-S12-DN10	9 x 1,5	20
DKOS 45 14S 10	22 x 1.5	3/8"	10	76	21	46	7	27	HF/24-SW0E45-S14-DN10	10 x 2	25
DKOS 45 16S 13	24 x 1.5	1/2"	12	82	23	52	10	30	HF/24-SW0E45-S16-DN12	12 x 2	20
DKOS 45 20S 16	30 x 2	5/8"	16	99	28	65	13	36	HF/24-SW0E45-S20-DN16	16,3 x 2,4	10
DKOS 45 20S 19	30 x 2	3/4"	19	111	30	72	14	36	HF/24-SW0E45-S20-DN19	16,3 x 2,4	20
DKOS 45 25S 19	36 x 2	3/4"	19	111	30	72	15	46	HF/24-SW0E45-S25-DN19	20,3 x 2,4	7
DKOS 45 25S 25	36 x 2	1"	25	143	40	96	18	46	HF/24-SW0E45-S25-DN25	20,3 x 2,4	8
DKOS 45 30S 25	42 x 2	1"	25	135	34	88	20	50	HF/24-SW0E45-S30-DN25	25,3 x 2,4	8
DKOS 45 38S 32	52 x 2	1.1/4"	31	162	40	108	26	60	HF/24-SW0E45-S38-DN31	33,3 x 2,4	5
AVAILABLE IN STAINLESS STEEL											

AVAILABLE IN STAINLESS STEEL

CES-

MALES 74° DIN 3861 HEAVY



CES

MALES 24° DIN 3861 LIGHT

Part No.	Thread d2	Hose Bore Ins.	Bore DN (mm)	Dimensions				Nut AF SW	VOSS Designation	O-ring	Box Qty.
				lg	lh	lx	dx				
CES 08S 06	16 x 1.5	1/4"	6	55	15	27	4	17	HF/24-S-S8-DN06		
CES 10S 06	18 x 1.5	1/4"	6	55	15	27	4	19	HF/24-S-S10-DN06		
CES 10S 08	18 x 1.5	5/16"	8	55	15	27	6	19	HF/24-S-S10-DN08		
CES 10S 10	18 x 1.5	3/8"	10	57	16	28	7	19	HF/24-S-S10-DN10		
CES 12S 08	20 x 1.5	5/16"	8	57	17	29	6	22	HF/24-S-S12-DN08		
CES 12S 10	20 x 1.5	3/8"	10	59	18	30	7	22	HF/24-S-S12-DN10		
CES 14S 10	22 x 1.5	3/8"	10	61	18	32	7	24	HF/24-S-S14-DN10		
CES 14S 13	22 x 1.5	1/2"	13	60	16	30	10	24	HF/24-S-S14-DN13		
CES 16S 13	24 x 1.5	1/2"	13	63	19	33	10	27	HF/24-S-S16-DN12		
CES 20S 16	30 x 2	5/8"	16	71	21	37	13	32	HF/24-S-S20-DN16		
CES 20S 19	30 x 2	3/4"	19	78	23	39	15	32	HF/24-S-S20-DN19		
CES 25S 19	36 x 2	3/4"	19	82	25	43	15	36	HF/24-S-S25-DN19		
CES 25S 25	36 x 2	1"	25	90	25	43	20	36	HF/24-S-S25-DN25		
CES 30S 25	42 x 2	1"	25	92	25	45	20	46	HF/24-S-S30-DN25		
CES 38S 32	52 x 2	1.1/4"	31	106	30	52	26	55	HF/24-S-S38-DN31		

AVAILABLE IN STAINLESS STEEL

Higher pressure resistance and functional reliability, even under extreme operating conditions.


FEATURES

- Metric thread Hose fittings with Universal Taper.
- Used to fit in bore Type WDIN 3861/ISO 8434-1 and bore Type Y DIN 3863.
- DIN3868: 1982.

DKML- METRIC FEMALES MULTISEAL 24°/60° DIN 3868


Part No.	Thread d2	Hose Bore Ins. DN (mm)	Dimensions				Nut AF SW	VOSS Designation	Box Qty.		
			lg	lh	lx	dx					
DKML METRIC FEMALES MULTISEAL 24°/60° DIN 3868											
	DKM/L 08L 06	14 x 1.5	1/4"	6	51	23	20	4	17	HF/24/60-SWS-L8-DN06	125
	DKM/L 10L 06	16 x 1.5	1/4"	6	51	23	20	4	19	HF/24/60-SWS-L10-DN06	100
	DKM/L 10L 08	16 x 1.5	5/16"	8	52	24	20	6	19	HF/24/60-SWS-L10-DN08	50
	DKM/L 10L 10	16 x 1.5	3/8"	10	54	24	20	7	19	HF/24/60-SWS-L10-DN10	50
	DKM/L 12L 08	18 x 1.5	5/16"	8	53	25	21	6	22	HF/24/60-SWS-L12-DN08	50
	DKM/L 12L 10	18 x 1.5	3/8"	10	54	25	21	7	22	HF/24/60-SWS-L12-DN10	70
	DKM/L 15L 10	22 x 1.5	3/8"	10	56	26	21	7	27	HF/24/60-SWS-L15-DN10	40
	DKM/L 15L 13	22 x 1.5	1/2"	12	57	27	22	10	27	HF/24/60-SWS-L15-DN12	40
DKM/L 18L 16	26 x 1.5	5/8"	16	63	29	25	13	32	HF/24/60-SWS-L18-DN16	25	

DKML 90- 90° METRIC FEMALES 24°/60° DIN 3868

Part No.	Thread d2	Hose Bore		Dimensions				Nut AF SW	VOSS Designation	Box Qty.		
		Ins.	DN (mm)	lg	lh	lx	dx					
DKML 90 90° METRIC FEMALES MULTISEAL 24°/60° DIN3868												
		DKM/L 90 08L 06	14 x 1.5	1/4"	6	55	30	27	4	17	HF/24/60-SWE-L8-DN06	50
		DKM/L 90 10L 06	16 x 1.5	1/4"	6	56	30	28	4	19	HF/24/60-SWE-L10-DN06	50
		DKM/L 90 10L 08	16 x 1.5	5/16"	8	58	30	30	6	19	HF/24/60-SWE-L10-DN08	40
		DKM/L 90 10L 10	16 x 1.5	3/8"	10	63	38	34	7	19	HF/24/60-SWE-L10-DN10	40
		DKM/L 90 12L 08	18 x 1.5	5/16"	8	58	31	30	6	22	HF/24/60-SWE-L12-DN08	30
		DKM/L 90 12L 10	18 x 1.5	3/8"	10	64	35	35	7	22	HF/24/60-SWE-L12-DN10	40
		DKM/L 90 15L 10	22 x 1.5	3/8"	10	64	36	35	7	27	HF/24/60-SWE-L15-DN10	30
		DKM/L 90 15L 13	22 x 1.5	1/2"	12	72	40	42	10	27	HF/24/60-SWE-L15-DN12	20
		DKM/L 90 18L 16	26 x 1.5	5/8"	16	88	50	54	13	32	HF/24/60-SWE-L18-DN16	25
AVAILABLE IN STAINLESS STEEL												

AVAILABLE IN STAINLESS STEEL

DKML 45- 45° METRIC FEMALES 24°/60° DIN 3868


Part No.	Thread d2	Hose Bore				Dimensions				Nut AF SW	VOSS Designation	Box Qty.
		Ins.	DN (mm)	lg	lh	lx	dx					
DKML 45 45° METRIC FEMALES MULTISEAL 24°/60° DIN 3868												
	DKM/L 45 08L 06	14 x 1.5	1/4"	6	63	15	35	4	17	HF/24/60-SWE45-L8-DN06	50	
	DKM/L 45 10L 06	16 x 1.5	1/4"	6	63	16	35	4	19	HF/24/60-SWE45-L10-DN06	20	
	DKM/L 45 10L 08	16 x 1.5	5/16"	8	65	15	37	6	19	HF/24/60-SWE45-L10-DN08	50	
	DKM/L 45 10L 10	16 x 1.5	3/8"	10	73	20	43	7	19	HF/24/60-SWE45-L10-DN10	40	
	DKM/L 45 12L 08	18 x 1.5	5/16"	8	65	16	37	6	22	HF/24/60-SWE45-L12-DN08	20	
	DKM/L 45 12L 10	18 x 1.5	3/8"	10	71	18	42	7	22	HF/24/60-SWE45-L12-DN10	25	
	DKM/L 45 15L 10	22 x 1.5	3/8"	10	72	19	42	7	27	HF/24/60-SWE45-L15-DN10	30	
	DKM/L 45 15L 13	22 x 1.5	1/2"	12	80	19	50	10	27	HF/24/60-SWE45-L15-DN12	25	
DKM/L 45 18L 16	26 x 1.5	5/8"	16	95	24	61	13	32	HF/24/60-SWE45-L18-DN16	15		
AVAILABLE IN STAINLESS STEEL												

AVAILABLE IN STAINLESS STEEL

DKOK-

METRIC FEMALE 60° INVERTED CONE (KOMATSU)

Part No.	Thread d2	Hose Bore		Dimensions				Nut AF SW	VOSS Designation	Box Qty.
		Ins.	DN (mm)	lg	lh	lx	dx			
DKOK METRIC FEMALE 60° INVERTED CONE (KOMATSU)										
DKOK 14 06	14 x 1.5	1/4"	6	50	16	14	4	19		100
DKOK 18 10	18 x 1.5	3/8"	10	51	23	20	4	19		150
DKOK 22 13	22 x 1.5	1/2"	13	57	23	22	10	27		100
DKOK 24 16	24 x 1.5	5/8"	16	57	23	22	13	32		60
DKOK 30 19	30 x 1.5	3/4"	19	64	25	21	15	36		50
DKOK 33 25	33 x 1.5	1"	25	73	27	23	20	41		50
DKOK 36 32	36 x 1.5	1.1/4"	32	86	30	27	26	46		25
DKOK 42 38	42 x 1.5	1.1/2"	38	90	31	29	32	55		25




Can be used in tandem with a DIN compression fitting to connect a Steel Tube and flexible hose assembly.

FEATURES

- Hose fittings with pipe attachment for cutting rings.
- ISO 8434-1
- Normally referred to as -Standpipes.

BEL-

STANDPIPES FOR DIN 2353 FITTINGS LIGHT

Part No.	Hose Bore		Dimensions					VOSS Designation	Box Qty.
	Ins.	DN (mm)	lg	l1	lx	dx	d1		
BEL STANDPIPES FOR DIN 2353 FITTINGS LIGHT									
									
									
BEL 06L 06	1/4"	6	58	23	30	4	6	HF/24-SWSX-L6-DN06	200
BEL 08L 06	1/4"	6	59	24	31	4	8	HF/24-SWSX-L8-DN06	200
BEL 10L 08	5/16"	8	60	25	32	6	10	HF/24-SWSX-L10-DN08	150
BEL 10L 10	3/8"	10	62	25	33	7	10	HF/24-SWSX-L10-DN10	250
BEL 12L 10	3/8"	10	63	25	33	7	12	HF/24-SWSX-L12-DN10	200
BEL 15L 10	3/8"	10	61	25	32	7	15	HF/24-SWSX-L15-DN10	175
BEL 15L 13	1/2"	12	63	25	34	10	15	HF/24-SWSX-L15-DN12	150
BEL 18L 13	1/2"	12	65	27	36	10	18	HF/24-SWSX-L18-DN12	100
BEL 18L 16	5/8"	16	70	27	36	13	18	HF/24-SWSX-L18-DN16	75
BEL 22L 16	5/8"	16	72	29	38	13	22	HF/24-SWSX-L22-DN16	30
BEL 22L 19	3/4"	19	79	29	40	15	22	HF/24-SWSX-L22-DN19	50
BEL 28L 25	1"	25	87	30	40	20	28	HF/24-SWSX-L28-DN25	30
BEL 35L 32	1.1/4"	31	103	36	49	26	35	HF/24-SWSX-L35-DN31	15
BEL 42L 38	1.1/2"	38	111	40	53	32	42	HF/24-SWSX-L42-DN38	10

AVAILABLE IN STAINLESS STEEL

AVAILABLE IN STAINLESS STEEL

BEL 90-

90° STANDPIPES FOR DIN 2353 FITTINGS LIGHT


</

AVAILABLE IN STAINLESS STEEL

BES- STANDPIPES FOR DIN 2353 FITTINGS HEAVY

Part No.	Hose Bore		Dimensions					VOSS Designation	Box Qty.
	Ins.	DN (mm)	lg	l1	lx	dx	d1		
BES STANDPIPES FOR DIN 2353 FITTINGS HEAVY									
BES 08S 06	1/4"	6	59	24	31	4	8	HF/24-SWSX-S08-DN06	
BES 10S 06	1/4"	6	61	25	33	4	10	HF/24-SWSX-S10-DN06	
BES 12S 06	1/4"	6	60	25	32	4	12	HF/24-SWSX-S12-DN06	
BES 12S 08	5/16"	8	60	25	32	6	12	HF/24-SWSX-S12-DN08	
BES 14S 10	3/8"	10	66	29	37	7	14	HF/24-SWSX-S14-DN10	
BES 14S 13	1/2"	12	67	29	38	10	14	HF/24-SWSX-S14-DN12	
BES 16S 13	1/2"	12	70	32	41	10	16	HF/24-SWSX-S16-DN12	
BES 20S 16	5/8"	16	79	36	45	13	20	HF/24-SWSX-S20-DN16	
BES 20S 19	3/4"	19	86	36	47	15	20	HF/24-SWSX-S20-DN19	
BES 25S 19	3/4"	19	90	40	51	15	25	HF/24-SWSX-S25-DN19	
BES 25S 25	1"	25	97	40	50	20	25	HF/24-SWSX-S25-DN25	
BES 30S 25	1"	25	102	45	55	20	30	HF/24-SWSX-S30-DN25	
BES 38S 32	1.1/4"	31	117	50	63	26	38	HF/24-SWSX-S38-DN31	
AVAILABLE IN STAINLESS STEEL									


AVAILABLE IN STAINLESS STEEL



BES 90- 90° STANDPIPES FOR DIN 2353 FITTINGS HEAVY

Part No.	Hose Bore			Dimensions				VOSS Designation	Box Qty.	
	Ins.	DN (mm)	lg	l1	lx	dx	d1			
BES 90										
BES 90 08S 06	1/4"	6	57	43	29	4	8	HF/24-SWEX-S08-DN06	50	
BES 90 10S 06	1/4"	6	57	44	29	4	10	HF/24-SWEX-S10-DN06	50	
BES 90 12S 06	1/4"	6	57	44	29	4	12	HF/24-SWEX-S12-DN06	70	
BES 90 12S 08	5/16"	8	58	46	30	6	12	HF/24-SWEX-S12-DN08	40	
BES 90 14S 10	3/8"	10	63	55	34	7	14	HF/24-SWEX-S14-DN10	25	
BES 90 14S 13	1/2"	13	72	60	42	10	14	HF/24-SWEX-S14-DN12	25	
BES 90 16S 13	1/2"	13	72	63	42	10	16	HF/24-SWEX-S16-DN12	25	
BES 90 20S 16	5/8"	16	87	78	53	13	20	HF/24-SWEX-S20-DN16	15	
BES 90 20S 19	3/4"	19	99	81	60	15	20	HF/24-SWEX-S20-DN19	10	
BES 90 25S 19	3/4"	19	99	85	60	15	25	HF/24-SWEX-S25-DN19	8	
BES 90 25S 25	1"	25	126	96	79	20	25	HF/24-SWEX-S25-DN25	8	
BES 90 30S 25	1"	25	126	101	79	20	30	HF/24-SWEX-S30-DN25	8	
AVAILABLE IN STAINLESS STEEL										

AVAILABLE IN STAINLESS STEEL



ORFS (O-Ring Face Seal) fittings have a straight thread and a flat face with an O-ring groove machined in the flat face. Sealing takes place by compressing the O-ring onto the flat face of the female connector.

FEATURES

- Exceeds SAE J1453 and ISO 8434-3.
- Sealing takes place by compressing the O-ring.
- Provides a connection between steel tubing and SAE J1926/ ISO 11926-1 O-Ring Ports.


ADVANTAGES

- Reliable over-tightening protection.
- Reduced work effort thanks to reduced tightening distances & tightening forces.
- Maximum tightness thanks to embedded FKM O-ring (standard).
- Improved leak-proofing & precision seal.
- Higher pressure resistance & functional reliability, even under extreme operating conditions.
- Easy, fast & reliable installation repeat installations can be performed frequently without any issues.

ORFS-

FACE SEAL FEMALE FITTINGS ISO 12151-1 (ISO 8434-3)


Part No.	Thread d2	Hose Bore Ins. DN (mm)	Dimensions				Nut AF SW	VOSS Designation	O-ring	Box Qty.
ORFS FACE SEAL FEMALE FITTINGS ISO 12151-1 (ISO 8434-3)										
ORFS 09 06	9/16"	1/4"	6	58	30	22	4	17	HF/90-SWS-6-DN06	60
ORFS 11 06	11/16"	1/4"	6	60	32	24	4	22	HF/90-SWS-10-DN06	50
ORFS 11 08	11/16"	5/16"	8	60	32	24	6	22	HF/90-SWS-10-DN08	50
ORFS 11 10	11/16"	3/8"	10	62	32	24	7	22	HF/90-SWS-10-DN10	50
ORFS 13 10	13/16"	3/8"	10	66	37	27	7	24	HF/90-SWS-12-DN10	30
ORFS 13 13	13/16"	1/2"	12	67	38	28	10	24	HF/90-SWS-12-DN12	30
ORFS 16 13	1"	1/2"	12	74	44	32	10	30	HF/90-SWS-16-DN12	30
ORFS 16 16	1"	5/8"	16	78	44	32	13	30	HF/90-SWS-16-DN16	30
ORFS 19 13	1.3/16"	1/2"	12	79	50	36	10	36	HF/90-SWS-20-DN12	20
ORFS 19 19	1.3/16"	3/4"	19	88	49	36	15	36	HF/90-SWS-20-DN19	15
ORFS 23 19	1.7/16"	3/4"	19	91	52	39	15	41	HF/90-SWS-25-DN19	10
ORFS 23 25	1.7/16"	1"	25	97	50	37	20	41	HF/90-SWS-25-DN25	15
ORFS 27 32	1.11/16"	1.1/4"	31	106	52	38	26	50	HF/90-SWS-30-DN31	10
ORFS 32 38	2"	1.1/2"	38	110	52	38	32	60	HF/90-SWS-38-DN38	4



ORFS 90-

FACE SEAL 90° FEMALE FITTINGS ISO 12151-1 (ISO 8434-3)

Part No.	Thread d2	Hose Bore		Dimensions				Nut AF SW	VOSS Designation	O-ring	Box Qty.
		Ins.	DN (mm)	lg	lh	lx	dx				
ORFS 90 FACE SEAL FEMALE 90° FITTINGS ISO 12151-1 (ISO 8434-3)											
ORFS 90 09 06	9/16"	1/4"	6	55	27	27	4	17	HF/90-SWE-6-DN06		40
ORFS 90 11 06	11/16"	1/4"	6	55	28	27	4	22	HF/90-SWE-10-DN06		30
ORFS 90 11 08	11/16"	5/16"	8	58	28	30	6	22	HF/90-SWE-10-DN08		30
ORFS 90 11 10	11/16"	3/8"	10	64	32	35	7	22	HF/90-SWE-10-DN10		40
ORFS 90 13 10	13/16"	3/8"	10	64	33	35	7	24	HF/90-SWE-12-DN10		20
ORFS 90 13 13	13/16"	1/2"	12	72	37	42	10	24	HF/90-SWE-12-DN12		30
ORFS 90 16 13	1"	1/2"	12	73	41	43	10	30	HF/90-SWE-16-DN12		20
ORFS 90 16 16	1"	5/8"	16	88	48	54	13	30	HF/90-SWE-16-DN16		10
ORFS 90 19 13	1.3/16"	1/2"	12	72	44	42	10	36	HF/90-SWE-20-DN12		10
ORFS 90 19 19	1.3/16"	3/4"	19	100	52	61	15	36	HF/90-SWE-20-DN19		15
ORFS 90 23 19	1.7/16"	3/4"	19	99	56	60	15	41	HF/90-SWE-25-DN19		5
ORFS 90 23 25	1.7/16"	1"	25	125	66	78	20	41	HF/90-SWE-25-DN25		8
ORFS 90 27 32	1.11/16"	1.1/4"	31	152	76	97	26	50	HF/90-SWE-30-DN31		5
ORFS 90 32 38	2"	1 1/2"	38	177	89	119	32	60	HF/90-SWE-38-DN38		3



ORFS 45-

FACE SEAL FEMALE 45° FITTINGS ISO 12151-1 (ISO 8434-3)


Part No.	Thread d2	Hose Bore		Dimensions				Nut AF SW	VOSS Designation	O-ring	Box Qty.
		Ins.	DN (mm)	lg	lh	lx	dx				
ORFS 45 FACE SEAL FEMALE 45° FITTINGS ISO 12151-1 (ISO 8434-3)											
ORFS 45 09 06	9/16"	1/4"	6	60	13	32	4	17	HF/90-SWE45-6-DN06		50
ORFS 45 11 06	11/16"	1/4"	6	61	14	33	4	22	HF/90-SWE45-10-DN06		40
ORFS 45 11 10	11/16"	3/8"	10	69	16	40	7	22	HF/90-SWE45-10-DN10		25
ORFS 45 13 10	13/16"	3/8"	10	70	17	40	7	24	HF/90-SWE45-12-DN10		20
ORFS 45 13 13	13/16"	1/2"	12	77	17	48	10	24	HF/90-SWE45-12-DN12		20
ORFS 45 16 13	1"	1/2"	12	81	20	51	10	30	HF/90-SWE45-16-DN12		20
ORFS 45 16 16	1"	5/8"	16	94	23	60	13	30	HF/90-SWE45-16-DN16		20
ORFS 45 19 19	1.3/16"	3/4"	19	104	25	65	15	36	HF/90-SWE45-20-DN19		10
ORFS 45 23 25	1.7/16"	1"	25	131	28	84	20	41	HF/90-SWE45-25-DN25		5
ORFS 45 27 32	1.11/16"	1.1/4"	31	155	34	101	26	50	HF/90-SWE45-30-DN31		3
ORFS 45 32 38	2"	1.1/2"	38	177	38	119	32	60	HF/90-SWE45-38-DN38		3




AORFS-

FACE SEAL MALE FITTINGS ISO 12151-1 (ISO 8434-3)

Part No.	Thread d2	Hose Bore		Dimensions				Nut AF SW	VOSS Designation	O-ring	Box Qty.
		Ins.	DN (mm)	lg	lh	lx	dx				
AORFS FACE SEAL MALE FITTINGS ISO 12151-1 (ISO 8434-3)											
AORFS 09 06	9/16"	1/4"	6	53	15	25	4	17	HF/90-S-6-DN06	7,65 x 1,78	50
AORFS 11 06	11/16"	1/4"	6	54	15	26	4	19	HF/90-S-10-DN06	9,25 x 1,78	50
AORFS 11 08	11/16"	5/16"	8	54	15	26	6	19	HF/90-S-10-DN08	9,25 x 1,78	50
AORFS 11 10	11/16"	3/8"	10	56	16	27	7	19	HF/90-S-10-DN10	9,25 x 1,78	50
AORFS 13 13	13/16"	1/2"	12	60	18	31	10	22	HF/90-S-12-DN12	12,42 x 1,78	25
AORFS 16 16	1"	5/8"	16	68	19	34	13	27	HF/90-S-16-DN16	15,60 x 1,78	25
AORFS 19 19	1.3/16"	3/4"	19	78	22	39	15	32	HF/90-S-20-DN19	18,77 x 1,78	50
AORFS 23 25	1.7/16"	1"	25	91	26	44	20	41	HF/90-S-25-DN25	23,52 x 1,78	15
AORFS 27 32	1.11/16"	1.1/4"	31	102	30	47	26	46	HF/90-S-30-DN31	29,87 x 1,78	10
AORFS 32 38	2"	1.1/2"	38	109	34	51	32	55	HF/90-S-38-DN38	37,82 x 1,78	5





Jet washing fittings used on all high pressure cleaning machines.

FEATURES


- Plastic coated for ease of removal.
- Standard M22 x 1.5 thread.

DKK- JETWASH COUPLING COMPLETE

Part No.	Thread d2	Hose Bore		Dimensions				Nut AF SW
		Ins.	DN (mm)	lg	lh	lx	dx	

DKK

JETWASH COUPLING COMPLETE




DKK 22 06	22x1.5	1/4"	6	61	30	28	4	35
DKK 22 08	22x1.5	5/16"	8	63	33	30	6	35
DKK 22 10	22x1.5	3/8"	10	63	33	30	7	35

DKKL- JETWASH COUPLING COMPLETE (LONG TYPE)

Part No.	Thread d2	Hose Bore		Dimensions				Nut AF SW
		Ins.	DN (mm)	lg	lh	lx	dx	

DKKL

JETWASH COUPLING COMPLETE (Long Type)




DKKL 22 06	22x1.5	1/4"	6	66	33	30	4	35
DKKL 22 08	22x1.5	5/16"	8	66	36	32	6	35
DKKL 22 10	22x1.5	3/8"	10	66	36	32	7	35

KF - KM ADAPTORS 22MM KARCHER TO BSP FEMALE

Part No.	Thread d2	Hose Bore		Dimensions				Nut AF SW
		Ins.	DN (mm)	lg	lh	lx	dx	

KF

22mm KARCHER TO BSP FEMALE ADAPTR




KF 22 04	22x1.5	1/4"	6	40		31		11
KF 22 06	22x1.5	3/8"	10	40		31		11

22MM KARCHER TO BSP MALE

Part No.	Thread d2	Hose Bore		Dimensions				Nut AF SW
		Ins.	DN (mm)	lg	lh	lx	dx	

KM

22mm KARCHER TO BSP MALE ADAPTR




KM 22 04	22x1.5	1/4"	6	43				11
KM 22 06	22x1.5	3/8"	10	43				11

FL3 90-

90° SAE J518 FLANGES 3000 PSI FITTINGS (CODE61)

Part No.	Flange Size	Flange Head Dia. mm (d)	Hose Bore Ins.	DN (mm)	Dimensions				Nut AF SW	VOSS Designation	Box Qty.
					lg	lh	lx	dx			
FL3 90 90° SAE J 518 FLANGES 3000 PSI (Code 61)											
FL3 90 08 13	1/2"	30.1	1/2"	13	72	44	42	10		HF/F-E-DN12-3S1/2	10
FL3 90 12 13	3/4"	38.1	1/2"	12	72	49	42	10		HF/F-E-DN12-3S3/4	15
FL3 90 12 16	3/4"	38.1	5/8"	16	87	55	53	13		HF/F-E-DN16-3S3/4	10
FL3 90 12 19	3/4"	38.1	3/4"	19	99	57	60	15		HF/F-E-DN19-3S3/4	15
FL3 90 16 19	1"	44.4	3/4"	19	99	60	60	15		HF/F-E-DN19-3S1	15
FL3 90 16 25	1"	44.4	1"	25	126	68	79	20		HF/F-E-DN25-3S1	10
FL3 90 20 25	1.1/4"	50.8	1"	25	126	70	79	20		HF/F-E-DN25-3S11/4	8
FL3 90 20 32	1.1/4"	50.8	1.1/4"	31	150	79	96	26		HF/F-E-DN31-3S11/4	5
FL3 90 24 32	1.1/2"	60.3	1.1/4"	31	151	85	96	26		HF/F-E-DN31-3S11/2	4
FL3 90 24 38	1.1/2"	60.3	1.1/2"	38	169	99	111	32		HF/F-E-DN38-3S11/2	6
FL3 90 32 38	2"	71.4	1.1/2"	38	172	101	114	32		HF/F-E-DN38-3S2	5
FL3 90 32 50	2"	71.4	2"	51	216	116	144	42		HF/F-E-DN51-3S2	3

AVAILABLE IN STAINLESS STEEL




FL3 45-

45° SAE J518 FLANGES 3000 PSI FITTINGS (CODE61)

Part No.	Flange Size	Flange Head Dia. mm (d)	Hose Bore Ins.	DN (mm)	Dimensions				Nut AF SW	VOSS Designation	Box Qty.
					lg	lh	lx	dx			
FL3 45 45° SAE J518 FLANGES 3000 PSI (Code 61)											
FL3 45 08 13	1/2"	30.1	1/2"	12	81	21	52	10		HF/F-E45-DN12-3S1/2	10
FL3 45 12 13	3/4"	38.1	1/2"	12	85	25	55	10		HF/F-E45-DN12-3S3/4	20
FL3 45 12 16	3/4"	38.1	5/8"	16	98	28	64	13		HF/F-E45-DN16-3S3/4	10
FL3 45 12 19	3/4"	38.1	3/4"	19	108	28	69	15		HF/F-E45-DN19-3S3/4	20
FL3 45 16 19	1"	44.4	3/4"	19	110	30	71	15		HF/F-E45-DN19-3S1	8
FL3 45 16 25	1"	44.4	1"	25	132	31	85	20		HF/F-E45-DN25-3S1	10
FL3 45 20 25	1.1/4"	50.8	1"	25	134	32	87	20		HF/F-E45-DN25-3S11/4	10
FL3 45 20 32	1.1/4"	50.8	1.1/4"	31	156	36	101	26		HF/F-E45-DN31-3S11/4	5
FL3 45 24 32	1.1/2"	60.3	1.1/4"	31	160	40	106	26		HF/F-E45-DN31-3S11/2	4
FL3 45 24 38	1.1/2"	60.3	1.1/2"	38	170	46	112	32		HF/F-E45-DN38-3S11/2	3
FL3 45 32 38	2"	71.4	1.1/2"	38	182	46	124	32		HF/F-E45-DN38-3S2	2
FL3 45 32 50	2"	71.4	2"	51	217	50	144	42		HF/F-E45-DN51-3S2	5



AVAILABLE IN STAINLESS STEEL



FSC3-

FLANGE SPLIT CLAMPS 3000 PSI (CODE61)

Part No.	Flange Size	Flange Head Dia. mm (d)	Hose Bore Ins.	DN (mm)	Dimensions				E	dx	VOSS Designation
					lg	lh	lx	dx			
FSC3 FLANGE SPLIT CLAMPS 3000 PSI (Code 62)											
FSC 6 08	1/2"	30.2			57	38.1	31	24.3	8.7	13	
FSC 6 12	3/4"	38.1			66	47.6	38.9	32.2	11.1	14	
FSC 6 16	1"	44.5			71	52.4	45.3	38.5	13.1	16	
FSC 6 20	1.1/4"	50.8			80	58.7	51.6	43.7	15.1	14	
FSC 6 24	1.1/2"	60.3			95	70	61.1	50.8	17.8	16	
FSC 6 32	2"	71.4			103	77.8	72.3	62.8	21.4	16	




FL6 90-

90° SAE J518 FLANGES 6000 PSI FITTINGS (CODE62)

Part No.	Flange Size	Flange Head Dia. mm (d)	Hose Bore		Dimensions				VOSS Designation
			Ins.	DN (mm)	lg	lh	lx	dx	

FL6 90

90° SAE J 518 FLANGES 6000 PSI (Code 62)



FL6 90 08 13	1/2"	31.7	1/2"	12	72	45	42	10	HF/F-E-DN12-6S1/2
FL6 90 12 13	3/4"	41.3	1/2"	12	72	53	42	10	HF/F-E-DN12-6S3/4
FL6 90 12 16	3/4"	41.3	5/8"	16	87	59	53	13	HF/F-E-DN16-6S3/4
FL6 90 12 19	3/4"	41.3	3/4"	19	99	61	60	15	HF/F-E-DN19-6S3/4
FL6 90 16 19	1"	47.6	3/4"	19	99	67	60	15	HF/F-E-DN19-6S1
FL6 90 16 25	1"	47.6	1"	25	126	75	79	20	HF/F-E-DN25-6S1
FL6 90 20 25	1.1/4"	54.0	1"	25	126	82	79	20	HF/F-E-DN25-6S11/4
FL6 90 20 32	1.1/4"	54.0	1.1/4"	31	151	91	96	26	HF/F-E-DN31-6S11/4
FL6 90 24 32	1.1/2"	63.5	1.1/4"	31	151	99	96	26	HF/F-E-DN31-6S11/2
FL6 90 24 38	1.1/2"	63.5	1.1/2"	38	176	109	118	32	HF/F-E-DN38-6S11/2
FL6 90 32 38	2"	79.4	1.1/2"	38	176	125	118	32	HF/F-E-DN38-6S2
FL6 90 32 50	2"	79.4	2"	51	220	140	147	42	HF/F-E-DN51-6S2

AVAILABLE IN STAINLESS STEEL


FL6 45-

45° SAE J518 FLANGES 6000 PSI FITTINGS (CODE62)

Part No.	Flange Size	Flange Head Dia. mm (d)	Hose Bore		Dimensions				VOSS Designation
			Ins.	DN (mm)	lg	lh	lx	dx	

FL6 45

45° SAE J518 FLANGES 6000 PSI (Code 62)



FL6 45 08 13	1/2"	31.7	1/2"	12	82	22	53	10	HF/F-E45-DN12-6S1/2
FL6 45 12 13	3/4"	41.3	1/2"	12	88	28	58	10	HF/F-E45-DN12-6S3/4
FL6 45 12 16	3/4"	41.3	5/8"	16	101	31	67	13	HF/F-E45-DN16-6S3/4
FL6 45 12 19	3/4"	41.3	3/4"	19	112	31	73	15	HF/F-E45-DN19-6S3/4
FL6 45 16 19	1"	47.6	3/4"	19	115	35	76	15	HF/F-E45-DN19-6S1
FL6 45 16 25	1"	47.6	1"	25	137	36	90	20	HF/F-E45-DN25-6S1
FL6 45 20 25	1.1/4"	54.0	1"	25	142	41	95	20	HF/F-E45-DN25-6S11/4
FL6 45 20 32	1.1/4"	54.0	1.1/4"	31	164	44	110	26	HF/F-E45-DN31-6S11/4
FL6 45 24 32	1.1/2"	63.5	1.1/4"	31	170	51	116	26	HF/F-E45-DN31-6S11/2
FL6 45 24 38	1.1/2"	63.5	1.1/2"	38	190	52	132	32	HF/F-E45-DN38-6S11/2
FL6 45 32 38	2"	79.4	1.1/2"	38	201	64	143	32	HF/F-E45-DN38-6S2
FL6 45 32 50	2"	79.4	2"	51	236	68	164	42	HF/F-E45-DN51-6S2

AVAILABLE IN STAINLESS STEEL


FSC6-

FLANGE SPLIT CLAMPS 6000 PSI (CODE62)

Part No.	Flange Size	Flange Head Dia. mm (d)	Hose Bore		Dimensions				VOSS Designation
			Ins.	DN (mm)	lg	lh	lx	dx	

FSC6

FLANGE SPLIT CLAMPS 6000 PSI (Code 62)



FSC 6 08	1/2"				57	40	47	18.3	
FSC 6 12	3/4"				71	50.8	53	23.8	
FSC 6 16	1"				80	57.1	66	27.8	
FSC 6 20	1.1/4"				94	66.7	77	31.6	
FSC 6 24	1.1/2"				103	79.4	89	36.7	
FSC 6 32	2"				135	96.8	123	44.4	

Can be used in tandem with a Split clamps. The split clamps make it easy to assemble the connection in close quarters.


FEATURES

- Hose fittings with CAT flange.
- FLCAT High Pressure Series (9000 PSI)
- ISO 12151-3 (ISO 6162-1)
- SAE J518

ADVANTAGES

- Leak free Advantages.
- Higher pressure resistance and functional reliability, even under extreme operating conditions.
- Ease of assembly.
- Maximum tightness thanks to FKM O-ring (standard).
- Reliable over-tightening protection.
- Repeat installations can be performed frequently without any issues.

FLC- FLANGES TYPE CAT



Part No.	Flange Size	Flange Head Dia. mm (d)	Hose Bore Ins. DN (mm)	Dimensions				Nut AF SW	VOSS Designation	Box Qty.
				lg	lh	lx	dx			
FLC 12 19	3/4"	41.3	3/4"	19	110	71	15		HF/F-CS-DN19-6S3/4	20
FLC 16 19	1"	47.6	3/4"	19	115	76	15		HF/F-CS-DN19-6S1	15
FLC 16 25	1"	47.6	1"	25	127	80	20		HF/F-CS-DN25-6S1	10
FLC 20 25	1.1/4"	54.0	1"	25	132	85	20		HF/F-CS-DN25-6S11/4	10
FLC 20 32	1.1/4"	54.0	1.1/4"	31	144	89	26		HF/F-CS-DN31-6S11/4	8
FLC 24 32	1.1/2"	63.5	1.1/4"	31	148	94	26		HF/F-CS-DN31-6S11/2	5
FLC 24 38	1.1/2"	63.5	1.1/2"	38	156	98	32		HF/F-CS-DN38-6S11/2	5

FLC 90- 90° FLANGES TYPE CAT



Part No.	Flange Size	Flange Head Dia. mm (d)	Hose Bore Ins. DN (mm)	Dimensions				Nut AF SW	VOSS Designation	Box Qty.
				lg	lh	lx	dx			
FLC 90 12 19	3/4"	41.3	3/4"	19	99	67	60	15	HF/F-CE-DN19-6S3/4	10
FLC 90 16 19	1"	47.6	3/4"	19	99	72	60	15	HF/F-CE-DN19-6S1	10
FLC 90 16 25	1"	47.6	1"	25	126	79	79	20	HF/F-CE-DN25-6S1	8
FLC 90 20 25	1.1/4"	54.0	1"	25	126	86	79	20	HF/F-CE-DN25-6S11/4	6
FLC 90 20 32	1.1/4"	54.0	1.1/4"	31	151	95	96	26	HF/F-CE-DN31-6S11/4	4
FLC 90 24 32	1.1/2"	63.5	1.1/4"	31	151	101	96	26	HF/F-CE-DN31-6S11/2	6
FLC 90 24 38	1.1/2"	63.5	1.1/2"	38	176	110	118	32	HF/F-CE-DN38-6S11/2	3

FLC 45- 45° FLANGES TYPE CAT



Part No.	Flange Size	Flange Head Dia. mm (d)	Hose Bore Ins. DN (mm)	Dimensions				Nut AF SW	VOSS Designation	Box Qty.
				lg	lh	lx	dx			
FLC 45 12 19	3/4"	41.3	3/4"	19	114	35	75	15	HF/F-CE45-DN19-6S3/4	15
FLC 45 16 19	1"	47.6	3/4"	19	118	39	79	15	HF/F-CE45-DN19-6S1	10
FLC 45 16 25	1"	47.6	1"	25	141	39	94	20	HF/F-CE45-DN25-6S1	10
FLC 45 20 25	1.1/4"	54.0	1"	25	145	43	98	20	HF/F-CE45-DN25-6S11/4	6
FLC 45 20 32	1.1/4"	54.0	1.1/4"	31	167	47	113	26	HF/F-CE45-DN31-6S11/4	5
FLC 45 24 32	1.1/2"	63.5	1.1/4"	31	171	52	117	26	HF/F-CE45-DN31-6S11/2	4
FLC 45 24 38	1.1/2"	63.5	1.1/2"	38	191	53	133	32	HF/F-CE45-DN38-6S11/2	5

WWW.DISTAG.COM
Get in touch

TULLOW
Distag QCS LTD
Industrial Estate Tullow
Tullow
Co.Carlow
IRELAND
R93 V585

Tel: +353 (0)59 915 1626
Fax: +353 (0)59 915 1264
Email: sales@distag.com

IPSWICH
Distag QCS (UK) LTD
Unit 24
Farthing Road Ind.Est.
Sproughton, Ipswich
Suffolk, UK
IP1 5AP

Tel: +44 (0)1473 744 612
Fax: +44 (0)1473 744 613
Email: info@distag.com

DUNGANNON
Distag QCS (UK) LTD
11 Cookstown Rd
Dungannon
Northern Ireland
BT71 4BB

Tel: +44 (0) 28 92 633380
Fax: +44 (0) 28 92 607231
Email: Nisales@distag.com