



Model	Temperature	Dimension	Volume	Weight	Refrigerant	Power
SUR-K1861S (CHILLER)	-6°C ~ +12°C	Ext: W1800xD600xH800 Int: W1430xD487xH609	415 L	86kg	R134a	Cooling: 100V / 133/133W (50/60Hz) Defrosting: 100V / 145/145W (50/60Hz)
SUF-K1861S (FREEZER)	-20°C	Ext: W1800xD600xH800 Int: W1430xD487xH609	415 L	87kg	R134a	Cooling: 100V / 185/185W (50/60Hz) Defrosting: 100V / 278/278W (50/60Hz)
SUR-K1871S (CHILLER)	-6°C ~ +12°C	Ext: W1800xD750xH800 Int: W1430xD637xH609	546 L	92kg	R134a	Cooling: 100V / 133/133W (50/60Hz) Defrosting: 100V / 145/145W (50/60Hz)
SUF-K1871S (FREEZER)	-20°C	Ext: W1800xD750xH800 Int: W1430xD637xH609	546 L	93kg	R134a	Cooling: 100V / 185/185W (50/60Hz) Defrosting: 100V / 278/278W (50/60Hz)

High energy saving performance

- Inverter compressor
- Automatic frame heater duty optimization
- Automatic condensing fan speed control

