

EXTREME FLOOR STRIPPER

PRODUCT DESCRIPTION

Extreme Floor Stripper is an aggressive product developed to quickly strip multiple coats of floor finish and sealer from resilient tile floors. This fast acting product was specially formulated for professionals to provide effective results with less time and labor.

DIRECTIONS

Strip only a manageable area at one time.

Regular Stripping: 13-oz. per gallon of hot water.

Heavy Duty Stripping: 26-oz. per gallon of hot water.

For best results use a scrubbing machine with a black strip pad, or mop buckets and mops, and wet vac with squeegee. Thoroughly saturate surface and allow to remain for about 5 minutes. Be sure the surface stays wet with stripper solution. Scrub floor surface. After scrubbing, pick up the solution with a wet vac and squeegee or mop and bucket. For best results, rinse with clear water. When the floor is dry it is ready for re-coating.

PACKAGING

4/1 Gallon Case

SPECIFICATIONS

Physical State: Liquid

Color: Clear

Odor: Detergent

pH: 13 - 13.5

Specific Gravity: 1

IDEAL FOR

Acrylic • Metal Crosslinked • Carnauba Wax • Acrylic Co-Polymer • Polymer • Microcrystalline Wax
Water-Based Urethanes • Styrene • Acrylic/Urethane Blends

The Sterling Advantage Solutions cleaning line was formulated for use in virtually any industry. These premium, concentrated cleaning solutions are designed to get the job done.

For more information about the Sterling Advantage Solutions products and a cleaning program designed for your specific cleaning requirements, contact your Bunzl/R3 Sales Representative.



Product No. 883

Sterling
Advantage Solutions

Kalamazoo, MI 49009

SCAN FOR SDS

