Aria Prett RS-X SERIES



Transmit-neck


Combined with the two octaves, 24 frets and the transmit-neck which runs right through the body, RS-X series guitars create ideal response and long sustain. The medium le of 630mm realizes the easy





New Finishes

The fresh colours are prepared for the RS-X series guitars, which fit well to the Canadian ash bodies. Golden Yellow(GY), Padouk Red(PR) and See-thru Red(SR).



RS-X80/X70

Control manual

Life to pickup

2. Rear pickup

2. Rear pickup

RS-X80 is fitted with the renowned

DiMarzio Dual Sound humbuckers

and for RS-X70, powerful

Protomatic-III pickups are fitted.

3. 3-position pickup selector

Normal section

Master volume control

4. Master volume control

Master tone control
 Dual sound switch (front)
 Dual sound switch (rear)
 This switch selects the normal hum-

bucking sound in series connection (down) and a very bright sound in parallel connection (up). Bod nick-ups are in humbucking connection. Mixing of parallel and series connections available by the individual front and rear switches.

8. Phase reversal switch
This switch selects "in" or "out of phase" of the pickups. (up ... out of phase, down ... in phase)
The pickup selector switch must be in center position.

Booster section

In center position.

Booster section

3-position boost mode selector

This rotary switch selects on/off of
the two boosters built-in.

Left ... Booster "OFF" (works as a
bypass switch)

Center ... Booster "ON"

Right ... Booster & Over booster
"ON"

10. Booster volume control
The volume control for the 1st booster.

booster.

11. Over booster volume control
The volume control for the 2nd
booster. Combined with the subtle
setting of (10), various distortion
sounds are produced.

The booster amplifiers are driven by two 9-volt batteries with an average life of 200 hours. Even the battery power is exhausted, normal sound can be obtained with the boost mode selector position in "OFF". Check your batteries regularly with the Aria battery checker, and for maximum battery life always unplug the cable when the guitar is not in use.



RS-X70

Specifications:

■ Body: Solid Canadian ash, walnut stripes, contoured cutaway ■ Neck: 5-ply maple/walnut transmit-neck, heel-less cutaway Fingerboard: Rosewood, 24 frets Scale: 630m/m Pickups: 2 Protomatic-III Controls: Master volume control, Master tone control, 2 Dual sound switches, Phase reversal switch, 3-position boost mode selector, Booster volume control, Over booster volume control, Pickup selector switch Power supply: 2 006P (9V) batteries Hardwares: SPT brass plated bridge, QH brass plated tailpiece, Nickel plated die-cast machine heads, Brass top nut Size: 980mmL x 330mmW x 45mmT, 4.0Kg Finishes: Padouk Red(PR), See-thru Red(SR) and Golden Yellow(GY).

Aria Drall RS-X SERIES

or RS-X80-GY

RS-X SERIES

RS-X series guitars include many innovation from the Aria Development team. RS-X series feature the original Xtronics-I circuit, two dual sound switches, phase reversal switches plant booster mode selector, booster volume and over booster volume controls which, combined, can give the musician a selection of various distortion sounds. The body construction features Canadian ash combined with maple/walnut transmit-neck.

RS-X series include models X80 fitted with DiMarzio Dual Sound humbuckers and X70 with Protomatic III humbuckers.





New Headpiece

Distinctive new design to blend with the traditional graceful appearance of the PE series. Machine heads are nickel plated die-cast.



Transmit-neck/heel-less cutaway

Built with alternative 5-ply laminations of maple and walnut running through the body for transmitting maximum string vibrations to the pickups.



Booster section

Newly developed Xtronics-I circuit is incorporated in the RS-X series guitars. It's individual dual sound switches for the front and rear pickups and the phase reversal switch create tweleve types of tonal colours. With the booster section which include two boosters and mode selector, RS-X series guitar can give the musician a selection of various distortion sounds, from soft to hard. Two 9-volt batteries included.



DiMarzio Pickups

The X80 is fitted with the renowned DiMarzio dual-sound humbuckers: a series/ parallel selector switch provides the usual humbucking sound or a more attacking sound without loss of humbucking effects.

RS-X80

Specifications:

■ Body: Solid Canadian ash, walnut stripes, contoured cutaway ■ Neck: 5-ply maple/walnut transmit-neck, heel-less cutaway Fingerboard: Ebony, 24 frets Scale: 630m/m Pickups: 2 DiMarzio Dual Sound humbuckers Controls: Master volume control, Master tone control, 2 Dual sound switches, Phase reversal switch, 3-position boost-mode selector, Booster volume control, Over-booster volume control, Pickup selector switch Power supply: 2 006P (9V) batteries Hardwares: SPT brass plated bridge, QH brass plated tailpiece, Nickel plated die-cast machine heads, Brass top nut Size: 980mmL x 330mmW x 45mmT, 4.0Kg Finish: Padouk Red(PR), See-thru Red(SR) and Golden Yellow(GY).



