



MODEL	Volume (L)	Temperature	Dimension	Refrigerant	Power	Accessories
SRR-K1261S (CHILLER)	848 112kg	-6 ~ +12°C	Ext: W1200xD650xH1950 Int: W1100xD550xH1450	R134a	Cooling: 100V / 184/184W (50/60Hz) Defrosting: 100V / 329/329W (50/60Hz)	4 Shelves
SRF-K1261S (FREEZER)	842 120kg	-15 ~ -25°C	Ext: W1200xD650xH1950 Int: W1100xD550xH1450	R404A	Cooling: 100V / 388/388W (50/60Hz) Defrosting: 100V / 564/564W (50/60Hz)	4 Shelves
SRR-K1281S (CHILLER)	1087 123kg	-6 ~ +12°C	Ext: W1200xD800xH1950 Int: W1100xD700xH1450	R134a	Cooling: 100V / 184/184W (50/60Hz) Defrosting: 100V / 329/329W (50/60Hz)	4 Shelves
SRF-K1281S (FREEZER)	1081 131kg	-15 ~ -25°C	Ext: W1200xD800xH1950 Int: W1100xD700xH1450	R404A	Cooling: 100V / 388/388W (50/60Hz) Defrosting: 100V / 564/564W (50/60Hz)	4 Shelves

ECONAVI



High energy saving performance

- Inverter compressor
- Automatic frame heater duty optimization
- Automatic condensing fan speed control

