



PRECAUTIONS: Avoid breathing dust, vapors, mist or spray. Use only with adequate ventilation. Do not swallow. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID INFORMATION: **Inhalation:** Remove person to fresh air. If symptoms persist, get medical attention. **Skin Contact:** Wash skin with soap and water. If symptoms persist, get medical attention. **If Swallowed:** Do not induce vomiting. Rinse mouth. If you feel unwell, get medical attention.

CONTAINS: Water (7732-18-5); Aluminum Oxide (1344-28-1); MEDIUM ALIPHATIC SOLVENT NAPHTHA (64742-88-7); GLYCERIN (56-81-5); HYDROTREATED HEAVY NAPHTHA (PETROLEUM) (64742-48-9); HYDROTREATED LIGHT PETROLEUM DISTILLATES (64742-47-8); White mineral oil (petroleum) (8042-47-5); Castor oil (8001-79-4); Triethanolamine (102-71-6)

CHEMTREC (800) 424-9300

Reflect Your Passion™

Formulated by & manufactured for © Meguiar's Inc., Irvine, CA 92618 meguiars.com

MADE IN USA WITH GLOBALLY SOURCED MATERIALS
1-800-347-5700
For free, expert car care advice



PROFESSIONAL

ULTRA PRO FINISHING POLISH

M210

- ◀ Creates deep, glossy finish even on dark & sensitive paints
- ◀ Finishes down without haze, swirls or holograms
- ◀ Easy wipe-off, virtually zero dust or sling with Rotary or DA
- ◀ Follow M110 Ultra Pro Speed Compound for optimal results

**FOR PROFESSIONAL USE ONLY.
NOT INTENDED FOR RETAIL SALE.**

BODY SHOP SAFE

ULTRA PRO FINISHING POLISH is engineered to deliver flawless results on even the most sensitive paints in less time.

DIRECTIONS: SHAKE WELL. Always work on a cool, properly cured paint surface. Prime new or dry pads by misting on M34 Final Inspection.®

1. ROTARY: Set buffer to approximately 1000-1500 RPMs and apply product directly to the paint surface. Use with Meguiar's® Soft Buff™ Pads and begin working in a 2' x 2' area with overlapping passes. Continue working until light film remains.

DA Polisher: Apply directly to appropriate Meguiar's® Soft Buff™ DA Foam Disc. Set machine to 4-5 and begin working in a 2' x 2' area with overlapping passes. Apply moderate pressure on initial 2-3 passes followed with light pressure for following two passes.

2. Wipe off residue immediately after each panel. Inspect finish with light.

TIPS: Best when used after **M110 Ultra Pro Speed Compound**. To achieve swirl free finish, clean pad frequently and apply moderate pressure on initial passes, reducing pressure gradually with final passes.



PRECAUTIONS: Avoid breathing dust, vapors, mist or spray. Use only with adequate ventilation. Do not swallow. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID INFORMATION: **Inhalation:** Remove person to fresh air. If symptoms persist, get medical attention. **Skin Contact:** Wash skin with soap and water. If symptoms persist, get medical attention. **If Swallowed:** Do not induce vomiting. Rinse mouth. If you feel unwell, get medical attention.

CONTAINS: Water (7732-18-5); Aluminum Oxide (1344-28-1); MEDIUM ALIPHATIC SOLVENT NAPHTHA (64742-88-7); GLYCERIN (56-81-5); HYDROTREATED HEAVY NAPHTHA (PETROLEUM) (64742-48-9); HYDROTREATED LIGHT PETROLEUM DISTILLATES (64742-47-8); White mineral oil (petroleum) (8042-47-5); Castor oil (8001-79-4); Triethanolamine (102-71-6)

CHEMTREC (800) 424-9300

Reflect Your Passion™

Formulated by & manufactured for © Meguiar's Inc., Irvine, CA 92618 meguiars.com

MADE IN USA WITH GLOBALLY SOURCED MATERIALS
1-800-347-5700
For free, expert car care advice



PROFESSIONAL

ULTRA PRO FINISHING POLISH

M210

- ◀ Creates deep, glossy finish even on dark & sensitive paints
- ◀ Finishes down without haze, swirls or holograms
- ◀ Easy wipe-off, virtually zero dust or sling with Rotary or DA
- ◀ Follow M110 Ultra Pro Speed Compound for optimal results

**FOR PROFESSIONAL USE ONLY.
NOT INTENDED FOR RETAIL SALE.**

BODY SHOP SAFE

ULTRA PRO FINISHING POLISH is engineered to deliver flawless results on even the most sensitive paints in less time.

DIRECTIONS: SHAKE WELL. Always work on a cool, properly cured paint surface. Prime new or dry pads by misting on M34 Final Inspection.®

1. ROTARY: Set buffer to approximately 1000-1500 RPMs and apply product directly to the paint surface. Use with Meguiar's® Soft Buff™ Pads and begin working in a 2' x 2' area with overlapping passes. Continue working until light film remains.

DA Polisher: Apply directly to appropriate Meguiar's® Soft Buff™ DA Foam Disc. Set machine to 4-5 and begin working in a 2' x 2' area with overlapping passes. Apply moderate pressure on initial 2-3 passes followed with light pressure for following two passes.

2. Wipe off residue immediately after each panel. Inspect finish with light.

TIPS: Best when used after **M110 Ultra Pro Speed Compound**. To achieve swirl free finish, clean pad frequently and apply moderate pressure on initial passes, reducing pressure gradually with final passes.