



## TECHNICAL DATA

### GALAXY RADIATOR COOLANT

**GALAXY RADIATOR COOLANT** is a high quality liquid especially formulated to reduce or regulate the temperature of a cooling system, a high thermal capacity, low viscosity and non-toxic.

**GALAXY RADIATOR COOLANT** is supplied as a Blue Green coloured liquid ready for direct application and on site use.

#### BENEFITS AND ADVANTAGES

- **COOLS ENGINE**  
Quickly cool the engine. Maintain engine working temperature.
- **CONTROLS CORROSION**  
Contains chemicals to help prevent rust.
- **ACID NEUTRALISER**  
Because of its alkalinity **GALAXY RADIATOR COOLANT** neutralises acid.



#### TECHNICAL SUPPORT

PATS PINOY Representative provides a technical advisory service for on-site assistance, application

#### DIRECTION

1. Stop the engine and cool down.
2. Drain out radiator liquid.
3. Flush with water twice.
4. Add **GALAXY RADIATOR COOLANT** for a complete protection on your cooling system.

#### PROPERTIES

Appearance	:	Blue green liquid
Odor	:	Odorless
Color	:	Blue green
Specific Gravity	:	1.07
PH Concentrate	:	9.5
Viscosity CST @ 40°	:	3.7
Rust Test 3 % in tap water, ASTM D-4627	:	Pass
Copper Corrosion 5% 3 hours at 122°C, ASTM D130	:	-1B



## ESTIMATING and PACKAGING

**GALAXY RADIATOR COOLANT** is available in 200 liters - container, 20 liters - container and 1 liter – container



## STORAGE

**GALAXY RADIATOR COOLANT** has minimum shelf life of 12 months provided the temperature is kept within the range of 2°C to 50°C. If the temperature of the product fall outside this range. Contact PATS PINOY Representative for advice.

## HEALTH and SAFETY

**GALAXY RADIATOR COOLANT** does not fall into the hazard classifications of current regulations (see notes 1 and 2 below). However, it should not be swallowed or allowed to come into contact with skin and eyes. Suitable protective gloves and goggles should be worn. Splashes on the skin should be removed with water. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed seek medical attention immediately - **do not** induce vomiting. For further information consult the Material Safety Data Sheet available for this product.

## FIRE

**GALAXY RADIATOR COOLANT** is water based and non-flammable.

## CLEANING and DISPOSAL

Spillages of **GALAXY RADIATOR COOLANT** should be absorbed onto sand, earth or vermiculite and transferred to suitable containers. Remnants should be hosed down with large quantities of water. The disposal of excess or waste material should be carried out in accordance with local legislation under the guidance.

## IMPORTANT NOTE

PATS PINOY products are guaranteed against defective materials and manufacturing, and are sold subject to its standard terms and conditions of sale. Copies of which may be obtained on request. Whilst PATS PINOY endeavors to ensure that the technical information on this data sheet is correct at the time of printing, it is the customer's responsibility to satisfy himself by checking with the company if this information is still current at the time of use,; that the product is suitable for the intended application; and that the actual conditions of use are in accordance with those recommended because PATS PINOY has no control over the conditions of use of its products. All recommendations or suggestions regarding the use of these products are made without guarantee.