

WARNING. Combustible Liquid.

PRECAUTIONS: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Wear protective gloves and eye/face protection. In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish. Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

1% of the mixture consists of ingredients of unknown acute oral, acute dermal and acute inhalation toxicity.

KEEP OUT OF REACH OF CHILDREN.

CONTAINS: Water (7732-18-5); Dearomatized Alkanes (64742-48-9); Alumina (1344-28-1); Light Aromatic Hydrocarbons (64742-47-8); Glycerin (56-81-5); Plant Oil (Withheld as CBI); Mineral Oil (8042-47-5); Triethanolamine (102-71-6); Alkyloammonium Salt (Withheld as CBI)

For more ingredient information, visit www.meguiars.com/ingredients

CHEMTREC (800) 424-9300

Reflect Your Passion™

Formulated by & manufactured for © Meguiar's Inc., Irvine, CA 92618 meguiars.com

MADE IN USA WITH GLOBALLY SOURCED MATERIALS
1-800-347-5700
For free, expert car care advice



PROFESSIONAL

PRO SPEED COMPOUND

M100

- ◀ Fast cutting compound with advanced technology
- ◀ Quick removal of 1200 grit and finer sanding marks for easier polishing
- ◀ Removes deep scratches, acid rain or severe swirls/holograms

FOR PROFESSIONAL USE ONLY. NOT INTENDED FOR RETAIL SALE.

BODY SHOP SAFE

FAST CUTTING BODY SHOP SAFE COMPOUND WITH ADVANCED TECHNOLOGY DESIGNED FOR PROFESSIONALS.

DIRECTIONS: SHAKE WELL. For best results, apply to a clean, cool properly cured paint surface.

1. Set rotary buffer to approximately 1200 – 1800 RPM and work one section at a time using an appropriate cutting pad or disc, such as Meguiar's® Soft Buff Foam Cutting Pad.
2. Apply Pro Speed Compound directly to the paint surface and begin working in a 2' x 2' area with overlapping passes. Buff area using light to medium pressure. Reduce pressure when compound begins to dry. Continue working until defects or sanding marks are removed.
3. Wipe off remaining residue with a quality microfiber towel such as Meguiar's® Supreme Shine™ Microfiber Towel prior to polishing.
4. Clean your pad frequently and inspect the finish with light for best results.

PROFESSIONAL TIP: For best results be sure to remove any compound residue off all door jamb areas before moving on to polishing the surface.

WARNING. Combustible Liquid.

PRECAUTIONS: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Wear protective gloves and eye/face protection. In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish. Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

1% of the mixture consists of ingredients of unknown acute oral, acute dermal and acute inhalation toxicity.

KEEP OUT OF REACH OF CHILDREN.

CONTAINS: Water (7732-18-5); Dearomatized Alkanes (64742-48-9); Alumina (1344-28-1); Light Aromatic Hydrocarbons (64742-47-8); Glycerin (56-81-5); Plant Oil (Withheld as CBI); Mineral Oil (8042-47-5); Triethanolamine (102-71-6); Alkyloammonium Salt (Withheld as CBI)

For more ingredient information, visit www.meguiars.com/ingredients

CHEMTREC (800) 424-9300

Reflect Your Passion™

Formulated by & manufactured for © Meguiar's Inc., Irvine, CA 92618 meguiars.com

MADE IN USA WITH GLOBALLY SOURCED MATERIALS
1-800-347-5700
For free, expert car care advice



PROFESSIONAL

PRO SPEED COMPOUND

M100

- ◀ Fast cutting compound with advanced technology
- ◀ Quick removal of 1200 grit and finer sanding marks for easier polishing
- ◀ Removes deep scratches, acid rain or severe swirls/holograms

FOR PROFESSIONAL USE ONLY. NOT INTENDED FOR RETAIL SALE.

BODY SHOP SAFE

FAST CUTTING BODY SHOP SAFE COMPOUND WITH ADVANCED TECHNOLOGY DESIGNED FOR PROFESSIONALS.

DIRECTIONS: SHAKE WELL. For best results, apply to a clean, cool properly cured paint surface.

1. Set rotary buffer to approximately 1200 – 1800 RPM and work one section at a time using an appropriate cutting pad or disc, such as Meguiar's® Soft Buff Foam Cutting Pad.
2. Apply Pro Speed Compound directly to the paint surface and begin working in a 2' x 2' area with overlapping passes. Buff area using light to medium pressure. Reduce pressure when compound begins to dry. Continue working until defects or sanding marks are removed.
3. Wipe off remaining residue with a quality microfiber towel such as Meguiar's® Supreme Shine™ Microfiber Towel prior to polishing.
4. Clean your pad frequently and inspect the finish with light for best results.

PROFESSIONAL TIP: For best results be sure to remove any compound residue off all door jamb areas before moving on to polishing the surface.