



TECHNICAL DATA

PHILPRIME 008

PHILPRIME 008

PHILPRIME 008 is a black liquid solvent use as prime coat prior to installation of any membrane

CONCRETE REMOVER 808 is supplied as a Light yellow coloured liquid ready for direct application and on site use.

USES and ADVANTAGE

CONCRETE REMOVER 808 and surface renovator. **CONCRETE REMOVER 808** is specially useful in renovating metal equipments, machinery, steel tanks, metal sheets and where concrete deposits must be removed.

- Dissolves concrete bond.
- Highly concentrated.
- Biodegradable, non flammable, and economical.
- Safe on paints, plastics, glass and rubbers.

BENEFITS

- No odor and no fumes
- Dissolves concrete quickly turning it into a soft paste.
- Has corrosion inhibitors to prevent attack of bare iron and steel.
- Also removes rust and hard water-scale
- Has a detergent action so can still work on oily surfaces.



TECHNICAL SUPPORT

PATS PINOY Representative provides a technical advisory service for on-site assistance, application.

PROPERTIES

Appearance	Light Yellow
Flammability	Non Flammable
Toxicity	Acidic harmful if swallowed
Appearance	Liquid

ECONOMICAL

Highly effective simulation that saves labor cost. High concentration allows 1:1 dilution with water in dip tank application.

DIRECTION OF USE



PATS PINOY TRADING CORP.

Chemical & Building Solutions

Brush on, in dip tank method is recommended. In light cement coating. Dilute 1:1 part water. Brush on surface, let soak until the cement softens then scrape to remove all residues.

FOR HEAVY CEMENT COATING

Use full concentration. Repeated brushings and applications may be required.

DIP TANK APPLICATION

Require plastic lined container. Dilution 1:1. Dip all concrete laden metals unto container with **CONCRETE REMOVER 808**, leave it in several minutes. Remove metal part from container and rinse with clean water.

ESTIMATING and PACKAGING

CONCRETE REMOVER 808 is available in 20 liters - container, 4 liters - container and 1 liter – container



STORAGE

CONCRETE REMOVER 808 has minimum shelf life of 12 months provided the temperature is kept within the range of 2°C to 50°C. If the temperature of the product fall outside this range. Contact PATS PINOY Representative for advice.

HEALTH and SAFETY

CONCRETE REMOVER 808 does not fall into the hazard classifications of current regulations (see notes 1 and 2 below). However, it should not be swallowed or allowed to come into contact with skin and eyes. Suitable protective gloves and goggles should be worn. Splashes on the skin should be removed with water. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed seek medical attention immediately - **do not** induce vomiting. For further information consult the Material Safety Data Sheet available for this product.

FIRE

CONCRETE REMOVER 808 is water based and non-flammable.

CLEANING and DISPOSAL

Spillages of **CONCRETE REMOVER 808** should be absorbed onto sand, earth or vermiculite and transferred to suitable containers. Remnants should be hosed down with large quantities of water. The disposal of excess or waste material should be carried out in accordance with local legislation under the guidance.

IMPORTANT NOTE

PATS PINOY products are guaranteed against defective materials and manufacturing, and are sold subject to its standard terms and conditions of sale. Copies of which may be obtained on request. Whilst PATS PINOY endeavors to ensure that the technical information on this data sheet is correct at the time of printing, it is the customer's responsibility to satisfy himself by checking with the company if this information is still current at the time of use; that the product is suitable for the intended application; and that the actual conditions of use are in accordance with those recommended because PATS PINOY has no control over the conditions of use of its products. All recommendations or suggestions regarding the use of these products are made without guarantee.

Gochan Compound, Brgy. Mabolo Cebu City

Email: patspinoy_trading@yahoo.com

Telfax: (032) 256 4326 (PLDT) / (032) 328 7100 (GLOBE)

Mobile: 0942 428 4394 (SUN) / 0917 653 6650 (GLOBE)