

WARNING. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

PRECAUTIONS: Do not swallow. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID INFORMATION: If Swallowed: Do not induce vomiting. Rinse mouth. If you feel unwell, get medical attention.

CONTAINS: Water (7732-18-5); Light Aromatic Hydrocarbons (64742-47-8); Alumina (1344-28-1); Mineral Oil (8042-47-5); Triethanolamine (102-71-6).

For more ingredient information, visit www.meguiars.com/ingredients

CHEMTREC (800) 424-9300

Reflect Your Passion™

Formulated by & manufactured for © Meguiar's Inc., Irvine, CA 92618 meguiars.com

MADE IN USA WITH GLOBALLY SOURCED MATERIALS

1-800-347-5700
For free, expert car care advice



PROFESSIONAL

PRO SPEED POLISH

M200

- ◀ Creates a deep, glossy finish on dark & sensitive paints
- ◀ Easy wipe off & low dusting formula for fast cleanup
- ◀ Tuned for tall & short stroke DA polishers
- ◀ Optimized for long work cycles

**FOR PROFESSIONAL USE ONLY.
NOT INTENDED FOR RETAIL SALE.**

BODY SHOP SAFE

Engineered to deliver incredible results on even the most sensitive paints with a DA.

DA Polisher: Apply directly to appropriate foam discs, such as Meguiar's® Soft Buff DA Foam Polishing Disc. Set machine to 3800-4800 OPM and begin working in a 2' x 2' area with overlapping passes. Apply moderate pressure on initial passes for defect removal and then follow with light pressure to refine finish. Wipe off residue immediately after each panel or section. Clean your pad frequently and inspect the finish with light for best results.

ROTARY: Set buffer to approximately 1000-1500 RPMs and apply product directly to the paint surface. Use with appropriate foam pads, such as Meguiar's® Soft Buff Foam Polishing Pad, and begin working in a 2' x 2' area with overlapping passes. Apply moderate pressure on initial passes for defect removal and then follow with light pressure to refine finish. Wipe off residue immediately after each panel or section. Clean your pad frequently and inspect the finish with light for best results.

PROFESSIONAL TIPS: Use a professional grade compound, such as Meguiar's® Pro Speed Compound M100, if the paint has heavy defects, then follow with Pro Speed Polish M200 for optimal results.

WARNING. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

PRECAUTIONS: Do not swallow. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID INFORMATION: If Swallowed: Do not induce vomiting. Rinse mouth. If you feel unwell, get medical attention.

CONTAINS: Water (7732-18-5); Light Aromatic Hydrocarbons (64742-47-8); Alumina (1344-28-1); Mineral Oil (8042-47-5); Triethanolamine (102-71-6).

For more ingredient information, visit www.meguiars.com/ingredients

CHEMTREC (800) 424-9300

Reflect Your Passion™

Formulated by & manufactured for © Meguiar's Inc., Irvine, CA 92618 meguiars.com

MADE IN USA WITH GLOBALLY SOURCED MATERIALS

1-800-347-5700
For free, expert car care advice



PROFESSIONAL

PRO SPEED POLISH

M200

- ◀ Creates a deep, glossy finish on dark & sensitive paints
- ◀ Easy wipe off & low dusting formula for fast cleanup
- ◀ Tuned for tall & short stroke DA polishers
- ◀ Optimized for long work cycles

**FOR PROFESSIONAL USE ONLY.
NOT INTENDED FOR RETAIL SALE.**

BODY SHOP SAFE

Engineered to deliver incredible results on even the most sensitive paints with a DA.

DA Polisher: Apply directly to appropriate foam discs, such as Meguiar's® Soft Buff DA Foam Polishing Disc. Set machine to 3800-4800 OPM and begin working in a 2' x 2' area with overlapping passes. Apply moderate pressure on initial passes for defect removal and then follow with light pressure to refine finish. Wipe off residue immediately after each panel or section. Clean your pad frequently and inspect the finish with light for best results.

ROTARY: Set buffer to approximately 1000-1500 RPMs and apply product directly to the paint surface. Use with appropriate foam pads, such as Meguiar's® Soft Buff Foam Polishing Pad, and begin working in a 2' x 2' area with overlapping passes. Apply moderate pressure on initial passes for defect removal and then follow with light pressure to refine finish. Wipe off residue immediately after each panel or section. Clean your pad frequently and inspect the finish with light for best results.

PROFESSIONAL TIPS: Use a professional grade compound, such as Meguiar's® Pro Speed Compound M100, if the paint has heavy defects, then follow with Pro Speed Polish M200 for optimal results.