

PRECAUTIONS: Avoid breathing of vapors. Use only with adequate ventilation. Do not swallow. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID INFORMATION: **Inhalation:** Remove person to fresh air. If symptoms persist, get medical attention. **Skin Contact:** Wash skin with soap and water. If symptoms persist, get medical attention. **If Swallowed:** Do not induce vomiting. Rinse mouth. If you feel unwell, get medical attention.

CONTAINS: Diluent (Withheld as CBI); Light Aromatic Hydrocarbons (64742-47-8); Alumina (1344-28-1); Polyalkylsiloxane with functionalized silica (Withheld as CBI); Mineral Oil (8042-47-5); Triethanolamine (102-71-6)

For more ingredient information, visit www.meguiars.com/ingredients

CHEMTREC (800) 424-9300

Reflect Your Passion™

Formulated by & manufactured for © Meguiar's Inc., Irvine, CA 92618 meguiars.com

MADE IN USA WITH GLOBALLY SOURCED MATERIALS
1-800-347-5700
For free, expert car care advice



PROFESSIONAL

So1o™ ALL-IN-ONE

M300

- ◀ SiO₂-based protection leaves behind durable water beading protection
- ◀ Removes 3000 grit sanding marks or finer, even when used with a DA
- ◀ Super Micro Abrasive Technology polishes without hazing

**FOR PROFESSIONAL USE ONLY.
NOT INTENDED FOR RETAIL SALE.**

NON-BODY SHOP SAFE

So1o All-in-One delivers considerable defect removal in a single step, while simultaneously leaving our most durable protection yet from an AiO. Designed for both foam & microfiber discs or pads, and various machine applications, you're sure to dial in the right combination.

DIRECTIONS: SHAKE WELL. For best results work on a vehicle that has been washed and dried. Perform paint decontamination if necessary. Prime new or dry pads by misting with a spray detailer, such as Meguiar's® Final Inspection™ M34.

Recommended baseline speeds:

- DA: 3800-4800 OPM (4-5 speed setting)
- Rotary: 1000-1500 RPM

Recommended baseline pad/disc:

- Foam polishing

Apply product to the pad or disc of your choice and spread evenly across the entire surface. Work a 2'x2' area at a time, applying light to moderate pressure. For each successive pass, apply just 3-5 drops of product to the pad/disc surface and work the area with overlapping passes until high-gloss surface is achieved. Remove immediately with a quality microfiber towel, such as Meguiar's® Supreme Shine™ Microfiber Towel. Clean your pad frequently and inspect the finish with light for best results.

PROFESSIONAL TIP: You can adjust the cut and finish by changing pads and/or adjusting machine speed & pressure. This product does have cutting limitations so you may need to use a dedicated compound if defects remain.



PROFESSIONAL

So1o™ ALL-IN-ONE

M300

- ◀ SiO₂-based protection leaves behind durable water beading protection
- ◀ Removes 3000 grit sanding marks or finer, even when used with a DA
- ◀ Super Micro Abrasive Technology polishes without hazing

**FOR PROFESSIONAL USE ONLY.
NOT INTENDED FOR RETAIL SALE.**

NON-BODY SHOP SAFE

So1o All-in-One delivers considerable defect removal in a single step, while simultaneously leaving our most durable protection yet from an AiO. Designed for both foam & microfiber discs or pads, and various machine applications, you're sure to dial in the right combination.

DIRECTIONS: SHAKE WELL. For best results work on a vehicle that has been washed and dried. Perform paint decontamination if necessary. Prime new or dry pads by misting with a spray detailer, such as Meguiar's® Final Inspection™ M34.

Recommended baseline speeds:

- DA: 3800-4800 OPM (4-5 speed setting)
- Rotary: 1000-1500 RPM

Recommended baseline pad/disc:

- Foam polishing

Apply product to the pad or disc of your choice and spread evenly across the entire surface. Work a 2'x2' area at a time, applying light to moderate pressure. For each successive pass, apply just 3-5 drops of product to the pad/disc surface and work the area with overlapping passes until high-gloss surface is achieved. Remove immediately with a quality microfiber towel, such as Meguiar's® Supreme Shine™ Microfiber Towel. Clean your pad frequently and inspect the finish with light for best results.

PROFESSIONAL TIP: You can adjust the cut and finish by changing pads and/or adjusting machine speed & pressure. This product does have cutting limitations so you may need to use a dedicated compound if defects remain.

PRECAUTIONS: Avoid breathing of vapors. Use only with adequate ventilation. Do not swallow. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID INFORMATION: **Inhalation:** Remove person to fresh air. If symptoms persist, get medical attention. **Skin Contact:** Wash skin with soap and water. If symptoms persist, get medical attention. **If Swallowed:** Do not induce vomiting. Rinse mouth. If you feel unwell, get medical attention.

CONTAINS: Diluent (Withheld as CBI); Light Aromatic Hydrocarbons (64742-47-8); Alumina (1344-28-1); Polyalkylsiloxane with functionalized silica (Withheld as CBI); Mineral Oil (8042-47-5); Triethanolamine (102-71-6)

For more ingredient information, visit www.meguiars.com/ingredients

CHEMTREC (800) 424-9300

Reflect Your Passion™

Formulated by & manufactured for © Meguiar's Inc., Irvine, CA 92618 meguiars.com

MADE IN USA WITH GLOBALLY SOURCED MATERIALS
1-800-347-5700
For free, expert car care advice