

CONTAINS: WATER (7732-18-5); PETROLEUM DISTILLATES (68551-19-9); WHITE MINERAL OIL (8042-47-5); ALUMINUM OXIDE (1344-28-1); TRIETHANOLAMINE (102-71-6); CONDITIONERS (TRADE SECRET); PETROLEUM DISTILLATES (64742-88-7); GLYCERIN (56-81-5).

SUPPLEMENTAL INFORMATION: 14% of the mixture consists of ingredients of unknown acute oral toxicity.

CHEMTREC (800) 424-9300

Reflect Your Passion™

Formulated by & manufactured for © Meguiar's Inc., Irvine, CA 92618 *meguiars.com*

MADE IN USA WITH GLOBALLY SOURCED MATERIALS 1-800-347-5700 For free, expert car care advice

Megular's.

PROFESSIONAL

ULTRA FINISHING Polish

M205

- Advanced technology formula provides deep gloss and rich, swirl-free results
- Permanently removes swirls & light defects from all paints
- Produces deep reflections & high gloss
- Smooth buffing feel and fast wipe-off

FOR PROFESSIONAL USE ONLY. Not intended for retail sale. Body shop safe

DIRECTIONS: SHAKE WELL. Always work on a cool, properly cured paint surface.

DA application: Apply directly to appropriate Soft Buff DA Foam Disc. Set DA polisher to 4800 - 5800 OPM. Apply moderate pressure on initial 2-3 passes followed with light pressure for following two passes. Wipe off residue immediately after each panel.

Rotary application: Work one section at a time. Set rotary polisher to approximately 1000-1500 RPM's. Use with Meguiar's Soft Buff" Rotary Foam Pads. Apply M205 Ultra Finishing Polish directly to the paint surface and begin working in a 2" x 2" area with overlapping passes. Continue working until light film remains. Do not buff dry. Wipe remaining residue with a Meguiar's M9910 Ultimate Wipe* Microfiber Cloth. For extreme gloss, apply with Meguiar's MIS00 Professional Dual Action Polisher with a DFF5 or DFF6 Soft Buff" DA Foam Finishing Disc.

DIRECTIONS: SHAKE WELL. Always work on a cool, properly cured paint surface.

DA application: Apply directly to appropriate Soft Buff DA Foarn Disc. Set DA polisher to 4800 - 5800 OPM. Apply moderate pressure on initial 2-3 passes followed with light pressure for following two passes. Wipe off residue immediately after each panel.

Rotary application: Work one section at a time. Set rotary polisher to approximately 1000-1500 RPM's. Use with Meguiar's Soft Buff" Rotary Foam Pads. Apply M205 Ultra Finishing Polish directly to the paint surface and begin working in a 2 x 2 rae with overlapping passes. Continue working until light film remains. Do not buff dry. Wipe remaining residue with a Meguiar's M9910 Ultimate Wipe" Microfiber Cloth. For extreme gloss, apply with Meguiar's M1300 Professional Dual Action Polisher with a DFF5 or DFF6 Soft Buff" DA Foam Finishing Disc.

CONTAINS: WATER (7732-18-5); PETROLEUM DISTILLATES (68551-19-9); WHITE MINERAL OIL (8042-47-5); ALUMINUM OXIDE (1344-28-1); TRIETHANOLAMINE (102-71-6); CONDITIONERS (TRADE SECRET); PETROLEUM DISTILLATES (64742-88-7); GLYCERIN (56-81-5).

SUPPLEMENTAL INFORMATION: 14% of the mixture consists of ingredients of unknown acute oral toxicity.

CHEMTREC (800) 424-9300

Reflect Your Passion™

Formulated by & manufactured for © Meguiar's Inc., Irvine, CA 92618 *meguiars.com*

MADE IN USA WITH GLOBALLY SOURCED MATERIALS 1-800-347-5700 For free, expert car care advice



PROFESSIONAL

ULTRA FINISHING Polish

M205

- Advanced technology formula provides deep gloss and rich, swirl-free results
- Permanently removes swirls & light defects from all paints
- Produces deep reflections & high gloss
- Smooth buffing feel and fast wipe-off

FOR PROFESSIONAL USE ONLY. Not intended for retail sale.

