




Hex Flange Head Lag Screws



NOTE:
Minimum thread length is 1/2 length of the screw plus 0.50" or 6" whichever is shorter.
Screws too short for the formula shall be threaded as close to the head as practicable.

Inches							
Nominal Size or Basic Bolt Diameter	F		H	B	K	D	
	Width Across Flats		Height of Head	Flange Dia.	Wrench Height	Full Size Body Diameter	
	Max	Min	Max	Max	Min	Max	Min
1/4	0.375	0.367	0.28	0.56	0.17	0.260	0.237
5/16	0.500	0.489	0.32	0.68	0.21	0.324	0.298
3/8	0.562	0.551	0.39	0.81	0.25	0.388	0.360
1/2	0.750	0.736	0.51	1.07	0.34	0.515	0.482
Dimensions: Head Dimensions IFI-111 w/ Lag Threads Material: Low Carbon Steel							

440.606.6557

www.boltsandnuts.com

info@boltsandnuts.com

ONLINE FASTENER GROUP LLC CLAIMS ALL PROPRIETARY RIGHTS TO THIS DRAWING AND THE INFORMATION IT CONTAINS. THIS MATERIAL IS CONFIDENTIAL. DISCLOSURE, REPRODUCTION, AND MANUFACTURING IS STRICTLY PROHIBITED WITHOUT THE EXPRESS WRITTEN PERMISSION OF ONLINE FASTENER GROUP LLC . ALL RIGHTS OF DESIGN OR INVENTION ARE RESERVED.