



PRECAUTIONS: Avoid breathing dust, vapors, mist or spray. Use only with adequate ventilation. Do not swallow. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID INFORMATION: **Inhalation:** Remove person to fresh air. If symptoms persist, get medical attention. **Skin Contact:** Wash skin with soap and water. If symptoms persist, get medical attention. **If Swallowed:** Do not induce vomiting. Rinse mouth. If you feel unwell, get medical attention.

CONTAINS: Water (7732-18-5); Aluminum Oxide (1344-28-1); MEDIUM ALIPHATIC SOLVENT NAPHTHA (64742-88-7); GLYCERIN (56-81-5); HYDROTREATED HEAVY NAPHTHA (PETROLEUM) (64742-48-9); HYDROTREATED LIGHT PETROLEUM DISTILLATES (64742-47-8); White mineral oil (petroleum) (8042-47-5); Castor oil (8001-79-4); Triethanolamine (102-71-6)

CHEMTREC (800) 424-9300

Reflect Your Passion™

Formulated by & manufactured for © Meguiar's Inc., Irvine, CA 92618 meguiars.com

MADE IN USA WITH GLOBALLY SOURCED MATERIALS

1-800-347-5700

For free, expert car care advice



PROFESSIONAL

ULTRA PRO SPEED COMPOUND

M110

- ◀ The next evolution of heavy-cutting high-gloss compounds
- ◀ Quickly removes 1,200 grit or finer sanding marks
- ◀ Easy wipe-off, virtually zero dust or sling with Rotary or DA

**FOR PROFESSIONAL USE ONLY.
NOT INTENDED FOR RETAIL SALE.**

BODY SHOP SAFE

ULTRA PRO SPEED COMPOUND is engineered for body shop safe fast cutting with easy wipe-off and virtual no dusting.

DIRECTIONS: SHAKE WELL. Always work on a cool, properly cured paint surface. Prime new or dry pads by misting on M34 Final Inspection.®

1. ROTARY: Set buffer to approximately 1200-1800 RPMs and apply product directly to the paint surface. Use with Meguiar's® wool or Soft Buff™ Pads and begin working in a 2' x 2' area with overlapping passes. Buff area using light to medium pressure. Reduce pressure when compound begins to dry.

DA Polisher: Apply directly to appropriate Meguiar's® Soft Buff™ DA Foam Disc. Set machine to 4-5 and begin working in a 2' x 2' area with overlapping passes. Apply moderate pressure on initial 2-3 passes followed with light pressure for following two passes.

2. Wipe remaining residue with a Meguiar's microfiber towel. Inspect finish with proper lighting. Continue working until defects or sanding marks are removed.

TIPS: To achieve swirl free finish, clean pad frequently and apply moderate pressure on initial passes, reducing pressure gradually with final passes. Best when followed with **M210 Ultra Pro Finishing Polish.**



PRECAUTIONS: Avoid breathing dust, vapors, mist or spray. Use only with adequate ventilation. Do not swallow. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID INFORMATION: **Inhalation:** Remove person to fresh air. If symptoms persist, get medical attention. **Skin Contact:** Wash skin with soap and water. If symptoms persist, get medical attention. **If Swallowed:** Do not induce vomiting. Rinse mouth. If you feel unwell, get medical attention.

CONTAINS: Water (7732-18-5); Aluminum Oxide (1344-28-1); MEDIUM ALIPHATIC SOLVENT NAPHTHA (64742-88-7); GLYCERIN (56-81-5); HYDROTREATED HEAVY NAPHTHA (PETROLEUM) (64742-48-9); HYDROTREATED LIGHT PETROLEUM DISTILLATES (64742-47-8); White mineral oil (petroleum) (8042-47-5); Castor oil (8001-79-4); Triethanolamine (102-71-6)

CHEMTREC (800) 424-9300

Reflect Your Passion™

Formulated by & manufactured for © Meguiar's Inc., Irvine, CA 92618 meguiars.com

MADE IN USA WITH GLOBALLY SOURCED MATERIALS

1-800-347-5700

For free, expert car care advice



PROFESSIONAL

ULTRA PRO SPEED COMPOUND

M110

- ◀ The next evolution of heavy-cutting high-gloss compounds
- ◀ Quickly removes 1,200 grit or finer sanding marks
- ◀ Easy wipe-off, virtually zero dust or sling with Rotary or DA

**FOR PROFESSIONAL USE ONLY.
NOT INTENDED FOR RETAIL SALE.**

BODY SHOP SAFE

ULTRA PRO SPEED COMPOUND is engineered for body shop safe fast cutting with easy wipe-off and virtual no dusting.

DIRECTIONS: SHAKE WELL. Always work on a cool, properly cured paint surface. Prime new or dry pads by misting on M34 Final Inspection.®

1. ROTARY: Set buffer to approximately 1200-1800 RPMs and apply product directly to the paint surface. Use with Meguiar's® wool or Soft Buff™ Pads and begin working in a 2' x 2' area with overlapping passes. Buff area using light to medium pressure. Reduce pressure when compound begins to dry.

DA Polisher: Apply directly to appropriate Meguiar's® Soft Buff™ DA Foam Disc. Set machine to 4-5 and begin working in a 2' x 2' area with overlapping passes. Apply moderate pressure on initial 2-3 passes followed with light pressure for following two passes.

2. Wipe remaining residue with a Meguiar's microfiber towel. Inspect finish with proper lighting. Continue working until defects or sanding marks are removed.

TIPS: To achieve swirl free finish, clean pad frequently and apply moderate pressure on initial passes, reducing pressure gradually with final passes. Best when followed with **M210 Ultra Pro Finishing Polish.**